

MOBIL OIL CORP -- AVREX S TURBO 256 -- 9150-01-414-8141

===== Product Identification =====

Product ID:AVREX S TURBO 256

MSDS Date:03/28/1996

FSC:9150

NIIN:01-414-8141

MSDS Number: CBRFB

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/703-849-7616

Emergency Phone Num:609-737-4411/CHEMTREC 80

0-424-9300

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWES ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:SALATHE OIL CO. INC. (504-366-4542)

Box:UNKNOW

CAGE:0T5T6

===== Composition/Information on Ingredients =====

Ingred Name:TRICRESYLPHOSPHATE

CAS:1330-78-5

RTECS #:TD0175000

Fraction by Wt: 0.5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SYNTHETIC HYDROCARBON OIL

Other REC Limits:NONE RECOMMENDED

Ingred Name:ADDITIVES

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2G/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGEST:ASPIRATION HAZARD.INHAL:MAY

CAUSE RESPIRATORY IRRITATION.THERMAL DECOMPOSITION

PRODUCTS(TRIMETHYLOL P

ROPANE ESTER AND TRICRESYLPHOSPHATES) MAY BE

NEUROTOXIC;WHEN INHALED THEY IMPAIR CNS FUNCTIONING.IN

ADDITION,COOLED RESIDUES MAY BE NEUROTOXIC.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%

WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:INHAL:DIZZINESS,NAUSEA,UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SKIN:RE

MOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND

WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF

IRRITATION OCCURS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR

ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE

VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,GIVE

1-2 GLASSES OF WATER.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:410F,210C

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXID

E,FOAM.WATER OR

FOAM MAY CAUSE FROTHING.FIRE CONTROL WATER MAY HARM ENVIRONMENT.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND

FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:DECOMPOSITION PRODUCTS MAY BE NEUROTOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT

ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE

CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO

REMOVE

SLIPPERINESS.AVOID RUNOFF INTO WATER WAYS.REPORT SPIL LS RESULTING IN SHEEN UPON WATER TO 800-424-8802.

Neutralizing Agent:NOT APPLICABLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
Exposure Controls/Personal
Protection
=====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.

Ventilation:USE GENERAL DILUTION VENTILATION.

Protective Gloves:USE GOOD PERSONAL HYGIENE.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

TLV FOR OIL MIST IS 5MG/M3

=====
Physical/Chemical
Properties
=====

HCC:V6

Boiling Pt:B.P. Text:>601F,>316C

Melt/Freeze Pt:M.P/F.P Text:-80F,-62C

Vapor Pres: