

CONAP INC. -- CONAP S-8 SOLVENT -- 5970-01-037-4737

===== Product Identification =====

Product ID:CONAP S-8 SOLVENT

MSDS Date:07/01/1997

FSC:5970

NIIN:01-037-4737

MSDS Number: CBSFN

=== Responsible Party ===

Company Name:CONAP INC.

Address:1405 BUFFALO STREET

City:OLEAN

State:NY

ZIP:14760

Country:US

Info Phone Num:716-372-9650

Emergency Phone Num:716-372-9650/800-424-9300(CHEMTREC)

Preparer's Name

:LARRY R. JOHNSON

CAGE:16245

=== Contractor Identification ===

Company Name:CONAP INC.,WHOLLY OWNED SUBSIDIARY OF CYTEC INDUSTRIES
INC.

Address:1405 BUFFALO STREET

Box:City:OLEAN

State:NY

ZIP:14760

Country:US

Phone:716-372-9650

CAGE:16245

Company Name:RUDOLPH BROS AND COMPANY

Address:960 WALNUT STREET

Box:425

City:CANAL WINCHESTER

State:OH

ZIP:43110

Country:US

Phone:614-833-0707

CAGE:6S222

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA 313) (

CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 40-60%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-METHOXY-1-PROPANOL ACETATE

CAS:70657-70-4

RTECS #:AI8967450

Fraction by Wt: 5000MG/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CAUSES EYE IRRIT,MAY CAUSE SKIN

IRRIT.CHRONIC HAZ WARNING:CONTAIN

MATLS WHICH CAUSED BIRTH DEFECTS

& REPRODUCTIVE DSORDERS IN LAB ANIMAL TESTS.RISK DEPENDS ON

DURATION & LEVEL OF EXPO.DIRECT CONTACT W /MATL MAY CAUSE MODERATE

EYE & MILD SKINIRRIT.INHAL OVEREXPO MAY CAUSE IRRIT OF RESP TRACT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:TOLUENE:SEVERE EYE/MOD SKIN

IRRIT.INHAL-HEAD,FTG,NAU,CNS DEPRESS,REVERSIBLE KIDNEY/LIV DMG,PERM

HEARING LOSS,DECR LEARNING CAPABILITES.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MAN

UFACTURER.

===== First Aid Measures =====

First Aid:SKIN:WASH AFFECTED AREAS W/SOAP/WATER.EYE:IMMED IRRIGATE

W/PLENTY OF WATER FOR 15MINS.OBTAIN MED ATTN IF IRRIT

PERSISTS.MATLS NOT EXPECTED TO BE HARMFUL IF INHAL.IF INHAL REMOVE

TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:40.0F,4.4C

Autoignition Temp:Autoignition Temp Text:N/AVAI

Lower Limits:N/AVAI

Upper Limits:N/AVAI

Extinguishing Media:USE WATERSPRAY,ALCOHOL FOAM,CARBON DIOXIDE OR DRY
CHEMICAL TO EXTINGUISH FIRES.

Fire Fighting Procedures:WATERSTREAM MAY BE INEFFECTIVE.USE WATER TO
KEEP CNTNR COOL.WEAR SELF-CONTAIN POSITIVE PRESSURE BREATH APPARATUS
& FULL FIREFIGHTING PROT CLOTH.

Unusual Fire/Explosion Hazard:WARNING:FLAMM LIQUID AND VAPOR.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGN SOURCES.EXPO LEVEL UNK WEAR NIOSH
APPROV +PRESS
SELF-CONTAIN RESPIRATOR.EXPO LEVEL KNOWN WEAR NIOSH
APPROV RESP SUITABLE FOR LEVEL OF EXPO.ADDN TO PROT CLOTH/EQPMT
WEAR IMPERV BOOTS.COVER S PILLS W/INERT ABSORBENT
MATL;SWEEPUP,PLACE(SUPPLE)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FRM HEAT/SPARK/FLAME.AVOID
CONTACT W/EYE/SKIN/CLOTH.KEEP CNTNR CLSD.USE W/ADEQU VENTI.WASH
WORKCLOTH BEF REUSE.STORE SEPAR
ATELY STREET CLOTH
Other Precautions:AREAS CONTAINING MATL SHOULD HAVE FIRE-SAFE PRACTICES
& ELECTRICAL EQPMT IAW ELECTRICAL/FIRE PROTECTION
CODES(NFPA-30)GOVERNING CLASS I FLAMM LIQS.FOOD/BEV/TOBACCO PROD
SHOULD NOT BE CARRIED/STORE/CON SUME WHERE MATL USE.DONT TAKE
WORK(SUPP)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE EXPO ARE BELOW PEL NO RESPIRATORY
PROTECTION IS REQUIRED.WHERE EXPO EXCEED PEL USE RESPIRATOR APPROV
BY NIOSH FOR MATL & LEVEL OF EXPO.SEE INDUSTRIAL RESPIRATORY
PROTECTION(NIOSH).

Ventilation:WHERE MATL NOT USED IN CLSD SYS GOOD ENCLOSURE/LOC EXHAU
VENTI SHOULD BE PROVIDED TO CONTROL EXPO.

Protective Gloves:NEOPRENE IF REPEATED CONTACT POSSIBLE

Eye Protection:CHEM SPLASH PROOF GOGG OR FACE SHIELD

Other Protective Equipment:PROTECTIVE CLOTH-IMPERV
GLOVE,APRON,WORKPANTS,LONG SEELVE,WORKSHIRT,DISPO COVERALLS
RECOMMENDED.EYEWASH/SAF SHOWER.

Work Hygienic Practices:WASH WELL AFT

HNDLG.BEF EAT/DRINK/SMOKE WASH
FACE/HANDS W/SOAP/H2O.SHOWER AFT WORKSHIFT COMPLETION ESPEC IF SIGN
CONTACT
Supplemental Safety and Health
SPILL:IN WASTE DISPO CNTNR.FLUSH AREA W/H2O. OTH PRECAU:CLOTH/SHOES
HOME. DISPO:OF BY THERM TREAT/INCINERATION @EPA APPROV FACIL.PERSON
GENERATING WASTE IS RESPONSIBLE FOR DETERMINING WASTE CLASSIFICA
TION & DISPO METHOD.CONTAINS CHEM SUBJ TO REPORT REQMTS OF SEC 313
CERCLA:TOLUENE RQ1000LBS,2-METHOXY-1-PROPANOL ACETATE

=====

=== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:N/AVAI
Melt/Freeze Pt:M.P/F.P Text:N/AVAI
Decomp Temp:Decomp Text:N/AVAI
Vapor Pres:N/AVAI
Vapor Density:N/AVAI
Spec Gravity:0.912
pH:N/AVAI
Viscosity:NP
Evaporation Rate & Reference:N/AVAI
Solubility in Water:DISPERSIBLE
Appearance and Odor:COLORLESS LIQUID; FRUITY ESTER-LIKE ODOR
Percent Volatiles by Volume:N/AVAI
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stabili
ty Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE KNOWN.
Hazardous Decomposition Products:THERMAL DECOMPO OR COMBUSTION MAY
PRODUCE OXIDES OF CARBON &/OR HYDROGEN FLUORIDE.

===== Disposal Considerations =====

Waste Disposal Methods:APPLIES ONLY TO CYTEC PROD AS SUPPLIED:MATL
ALTER/CONTAM/EXCEEDED SHELF LIFE GUIDANCE MAY BE INAPPLICABLE.REFER
TO 40CFR261.33.ENCOURAGE RECYL/RECOVER/REUSE WHERE PERMITT

ED AS

ALTER TO DISPO AS WASATE .ORG MATL CLASS AS RCRA HAZ WASTE BE DISPO
(SUPPL)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.