View NSN Online: https://aerobasegroup.ae/nsn/5970-01-037-4737

Product ID:CONAP S-8 SOLVENT MSDS Date:07/01/1997 FSC:5970 NIIN:01-037-4737 MSDS Number: CBSFN === Responsible Party === Company Name: CONAP INC. Address:1405 BUFFALO STREET City:OLEAN State:NY ZIP:14760 Country:US Info Phone Num:716-372-9650 Emergency Phone Num:716-372-9650/800-424-9300(CHEMTREC) Preparer's Name :LARRY R. JOHNSON CAGE:16245 === Contractor Identification === Company Name: CONAP INC., WHOLLY OWNED SUBSIDIARY OF CYTEC INDUSTRIES INC. Address:1405 BUFFALO STREET Box:City:OLEAN State:NY ZIP:14760 Country:US Phone:716-372-9650 CAGE:16245 Company Name: RUDOLPH BROS AND COMPANY Address:960 WALNUT STREET Box:425 **City:CANAL WINCHESTER** State:OH ZIP:43110 Country:US Phone:614-833-0707 CAGE:6S222

======= Composition/Information on Ingredients ==========

Ingred Name: TOLUENE (SARA 313) (

CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 40-60% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9596 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:2-METHOXY-1-PROPANOL ACETATE CAS:70657-70-4 RTECS #:AI8967450 Fraction by Wt: 5000MG/KG. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: CAUSES EYE IRRIT, MAY CAUSE SKIN **IRRIT.CHRONIC HAZ WARNING:CONTAIN** MATLS WHICH CAUSED BIRTH DEFECTS & REPRODUCTIVE DSORDERS IN LAB ANIMAL TESTS. RISK DEPENDS ON DURATION & LEVEL OF EXPO.DIRECT CONTACT W /MATL MAY CAUSE MODERATE EYE & MILD SKINIRRIT. INHAL OVEREXPO MAY CAUSE IRRIT OF RESP TRACT. Explanation of Carcinogenicity:NONE Effects of Overexposure:TOLUENE:SEVERE EYE/MOD SKIN IRRIT.INHAL-HEAD, FTG, NAU, CNS DEPRESS, REVERSIBLE KIDNEY/LIV DMG, PERM HEARING LOSS, DECR LEARNING CAPABILITES. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MAN UFACTURER.

First Aid:SKIN:WASH AFFECTED AREAS W/SOAP/WATER.EYE:IMMED IRRIGATE W/PLENTY OF WATER FOR 15MINS.OBTAIN MED ATTN IF IRRIT PERSISTS.MATLS NOT EXPECTED TO BE HARMFUL IF INHAL.IF INHAL REMOVE TO FRESH AIR.

Flash Point Method:CC Flash Point:40.0F,4.4C Autoignition Temp:Autoignition Temp Text:N/AVAI Lower Limits:N/AVAI Upper Limits:N/AVAI

CERCLA)

Extinguishing Media: USE WATERSPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. Fire Fighting Procedures:WATERSTREAM MAY BE INEFFECTIVE.USE WATER TO KEEP CNTNR COOL.WEAR SEL-CONTAIN POSITIVE PRESSURE BREATH APPARATUS & FULL FIREFIGHTING PROT CLOTH. Unusual Fire/Explosion Hazard:WARNING:FLAMM LIQUID AND VAPOR. Spill Release Procedures: REMOVE IGN SOURCES. EXPO LEVEL UNK WEAR NIOSH APPROV +PRESS SELF-CONTAIN RESPIRATOR.EXPO LEVEL KNOWN WEAR NIOSH APPROV RESP SUITABLE FOR LEVEL OF EXPO.ADDN TO PROT CLOTH/EQPMT WEZR IMPERV BOOTS.COVER S PILLS W/INERT ABSORBENT MATL;SWEEPUP,PLACE(SUPPLE) Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: KEEP AWAY FRM HEAT/SPARK/FLAME. AVOID CONTACT W/EYE/SKIN/CLOTH.KEEP CNTNR CLSD.USE W/ADEQU VENTI.WASH WORKCLOTH BEF REUSE.STORE SEPAR ATELY STREET CLOTH Other Precautions: AREAS CONTAINING MATL SHOULD HAVE FIRE-SAFE PRACTICES & ELECTRICAL EQPMT IAW ELECTRICAL/FIRE PROTECTION CODES(NFPA-30)GOVERNING CLASS I FLAMM LIQS.FOOD/BEV/TOBACCO PROD SHOULD NOT BE CARRIED/STORE/CON SUME WHERE MATL USE.DONT TAKE WORK(SUPP) Respiratory Protection: WHERE EXPO ARE BELOW PEL NO RESPIRATORY PROTECTION IS REQUIRED. WHERE EXPO EXCEED PEL USE RESPIRATOR APPROV BY NIOSH FOR MATL & LEVEL OF EXPO.SEE INDUSTRIAL RESPIRATORY PROTECTION(NIOSH). Ventilation:WHERE MATL NOT USED IN CLSD SYS GOOD ENCLOSURE/LOC EXHAU VENTI SHOULD BE PROVIDED TO CONTROL EXPO. Protective Gloves: NEOPRENE IF REPEATED CONTACT POSSIBLE Eye Protection: CHEM SPLASH PROOF GOGG OR FACE SHIELD Other Protective Equipment: PROTECTIVE CLOTH-IMPERV GLOVE, APRON, WORKPANTS, LONG SEELVE, WORKSHIRT, DISPO COVERALLS RECOMMENDED.EYEWASH/SAF SHOWER. Work Hygienic Practices: WASH WELL AFT

HNDLG.BEF EAT/DRINK/SMOKE WASH

FACE/HANDS W/SOAP/H2O.SHOWER AFT WORKSHIFT COMPLETION ESPEC IF SIGN CONTACT

Supplemental Safety and Health

SPILL:IN WASTE DISPO CNTNR.FLUSH AREA W/H2O. OTH PRECAU:CLOTH/SHOES HOME. DISPO:OF BY THERM TREAT/INCINERATION @EPA APPROV FACIL.PERSON GENERATING WASTE IS RESPONSIBLE FOR DETERMINING WASTE CLASSIFICA TION & DISPO METHOD.CONTAINS CHEM SUBJ TO REPORT REQMTS OF SEC 313 CERCLA:TOLUENE RQ1000LBS,2-METHOXY-1-PROPANOL ACETATE

\_\_\_\_\_

## HCC:F2

Boiling Pt:B.P. Text:N/AVAI Melt/Freeze Pt:M.P/F.P Text:N/AVAI Decomp Temp:Decomp Text:N/AVAI Vapor Pres:N/AVAI Vapor Density:N/AVAI Spec Gravity:0.912 pH:N/AVAI Viscosity:NP Evaporation Rate & amp; Reference:N/AVAI Solubility in Water:DISPERSIBLE Appearance and Odor:COLORLESS LIQUID; FRUITY ESTER-LIKE ODOR Percent Volatiles by Volume:N/AVAI Corrosion Rate:NP

Stabili

ty Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE KNOWN. Hazardous Decomposition Products:THERMAL DECOMPO OR COMBUSTION MAY PRODUCE OXIDES OF CARBON &/OR HYDROGEN FLUORIDE.

Waste Disposal Methods:APPLIES ONLY TO CYTEC PROD AS SUPPLIED:MATL ALTER/CONTAM/EXCEEDED SHELF LIFE GUIDANCE MAY BE INAPPLICABLE.REFER TO 40CFR261.33.ENCOURAGE RECYL/RECOVER/REUSE WHERE PERMITT

## ED AS ALTER TO DISPO AS WASATE .ORG MATL CLASS AS RCRA HAZ WASTE BE DISPO (SUPPL)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.