

ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC -- ARCAIR AIR CARBON ARC
ELECTRODES (SUPPLEMENTAL) -- 3439-00-870-9934

===== Product Identification =====

Product ID:ARCAIR AIR CARBON ARC ELECTRODES (SUPPLEMENTAL)

MSDS Date:07/01/1989

FSC:3439

NIIN:00-870-9934

MSDS Number: CBTBL

=== Responsible Party ===

Company Name:ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC

Address:4200 WEST HARRY ST

Box:122

50

City:WICHITA

State:KS

ZIP:67277

Country:US

Info Phone Num:316-942-1421

Emergency Phone Num:316-942-1421

CAGE:09687

=== Contractor Identification ===

Company Name:ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC

Address:4200 WEST HARRY ST

Box:12250

City:WICHITA

State:KS

ZIP:67277

Country:US

Phone:316-942-1421

CAGE:09687

===== Composition/Information on Ingredients =====

Ingred Name:GRAPHITE, SYNTHETIC

CAS:7440-44-0

RTECS #:FF5250100

Fraction by Wt: 20-80%

Other REC Limits:NO

NE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9596

Ingred Name:GRAPHITE, NATURAL
CAS:7782-42-5
RTECS #:MD9659600
Fraction by Wt: 20-80%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MPPCF; Z-3
ACGIH TLV:2 MG/M3 RDUST; 9596

Ingred Name:COPPER (SARA 313) (CERCLA)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 10-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2 MG/M3 FUME; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CARBON BLACK
(FULLY BAKED OUT)
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: SEE ING
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9596

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:FUME:BRONCHITIS,LUNG DEPOSITS & TISSUE
DMG WHICH MAY BE IRREVERSIBLE.EXPO TO ULTR
A-VIOLET ARC RAYS CAN
RESULT IN KERATOCONJUNCTIVITS CAUSING INFLAMM,BLURRED
VISION,HEADACHE-"SUNBURN".
Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NOT CURRENTLY
LISTED.
Effects of Overexposure:BREATHING DIFFICULTY, HEADACHE, NAUSEA, DRYNESS
OR IRRITATION OR NOSE, THROAT, EYES. BURNING SENSATION OF
SKIN/EYES. UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:RESPIRATORY PROBLEMS, ERYTHMAS.

===== First Aid Measures =====

F

First Aid: REMOVE TO FRESH AIR. IF BREATHING IMPAIRED, ASSISTED RESPIRATION MAY BE REQUIRED. TREAT UV EXPOSURE SIMILAR TO SEVERE SUNBURN, SEEK MED ATTN.

===== Fire Fighting Measures =====

Flash Point: NA
Autoignition Temp: Autoignition Temp Text: NA
Lower Limits: NA
Upper Limits: NA
Extinguishing Media: NONE SPECIFIED BY MANUFACTURER. HMIS: USE APPROPRIATE FIRE EXTINGUISHING MEDIA FOR SURROUNDING FIRE/MATERIALS.
Fire Fighting Procedures: NONE SPECIFIED BY MANUFACTURER.
Unusual Fire/Explosion Hazard: NONE.

===== Accidental Release Measures =====

Spill Release Procedures: SWEEP OR PICK UP. BE ALERT TO "HOT ENDS".
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN DRY AREA. ELECTRODES EXPOSED TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING @ 300F FOR 10 HOURS.
Other Precautions: READ/UNDERSTAND AMER NAT STD Z49.1; SUBPART Q OF OSHA 29CFR 1910.252 SAF IN WELD/CUT BY AMER WELD SOC. HEALTH/PHYS HAZ ASSOC W/ AIR CARBON ARC ELECTRODES ARE ATTRIBUTABLE TO FUMES GENERATED WHEN ELECTRODES ARE USED/CONSUMED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AIR SUPPLIED OR FUME RESPIRATOR MUST BE USED IF VENTILATION IS INSUFFICIENT.
Ventilation: LOC EXHAU: ALL AS REQUIRED TO REDUCE FUMES GENERATED BY EACH SPEC APPLICATION BEL ACGIH TLV.
V. OTHER: AIR SMPLING TO (SUPPLEMENT)
Protective Gloves: WELDERS GLOVES.
Eye Protection: FCSHIELD OR WELDERS HELMET W/ #12/DKR LENS
Other Protective Equipment: SEE Z49. DARK, SUBSTANTIAL CLOTHING-APRONS, ETC. SUITABLE FOOTWEAR FOR METAL WORKING.
Work Hygienic Practices: OPERATOR TRAINED TO AVOID ELECTRICAL SHOCK & UV RAY EXPOSURE.
Supplemental Safety and Health
ARCAIR GOUGHING ELECTRODES, COPPERCIAD JETROD; CAT #20-, 21-, 22-, 24-, 35- SERIES. VENTILATION: DETERMINE CORRECTIVE MEASURE.

===== Ph =====

Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:NA

pH:NA

Viscosity:NP

Evaporation Rate & Reference:NA

Solubility in Water:NOT SOLUBLE.

Appearance and Odor:SOLID, NO NOTABLE ODOR, COPPER COATED BLACK ROD.

Percent Volatiles by Volume:NP

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:Y

ES

NONE KNOWN.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
TRACES OF COPPER FUME (OZONE, NITROGEN OXIDE FROM ELECTRIC ARC & UV
RAYS).

===== Disposal Considerations =====

Waste Disposal Methods:SOLID LANDFILL IF LOCAL REGULATIONS ALLOW.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner w

hatsoever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.