

MITTLER SUPPLY INC -- METHANE -- 6830-00-182-6315

=====
Product Identification
=====

Product ID:METHANE
MSDS Date:11/01/1993
FSC:6830
NIIN:00-182-6315
MSDS Number: CCBDY
=== Responsible Party ===
Company Name:MITTLER SUPPLY INC
Address:3607 SOUTH MAIN ST
City:SOUTH BEND
State:IN
ZIP:46614
Country:US
Info Phone Num:219-291-5100
Emergency Phone Num:219-291-5100
CAGE:0B672
=== Contractor Identificati
on ===
Company Name:MITTLER SUPPLY INC
Address:3607 S MAIN ST
Box:City:SOUTH BEND
State:IN
ZIP:46614
Country:US
Phone:219-291-5100
CAGE:0B672

=====
Composition/Information on Ingredients
=====

Ingred Name:METHANE
CAS:74-82-8
RTECS #:PA1490000
Fraction by Wt: 100%
OSHA PEL:N/K
ACGIH TLV:ASPHYXIAN

Ingred Name:SUPDAT:CNTNRS FROM AREA OF FIRE IF W/OUT RISK. ALLOW FIRE
TO BURN OUT. ON-SITE FIRE BRIGADES MUST COMPLY W/OSHA (ING 3)
RTECS #:9999999ZZ

Ingred Name:ING 2: 29 CFR

1910.156.
RTECS #:9999999ZZ

Ingred Name:EXPLO HAZ: MAY SPREAD FROM SPILL. EXPLO ATMS MAY LINGER.
BEFORE ENTERING AREA, ESP CONFINED AREAS. CHECK ATM (ING 5)
RTECS #:9999999ZZ

Ingred Name:ING 4: W/APPRVD DEVICE. NO PART OF CNTNR SHOULD BE
SUBJECTED TO TEMP HIGHER THAN 52C(125F). MOST CNTNRS ARE (ING 6)
RTECS #:9999999ZZ

Ingred Name:ING 5: PROVIDED WITH A PRESS RELIEF DEVICE DESIGNED TO VENT
CONTENTS WHEN THEY ARE EXPOSED TO ELEVATED TEMPS.
RTECS #:9999999ZZ

Ingred Name:MATL TO AV
OID: OXYGEN, OXYGEN DIFLUORIDE MAY EXPLODE.
RTECS #:9999999ZZ

Ingred Name:HAZ DECOMP PRODS: AIR, METHANE MAY DECOMPOSE TO FORM
HYDROGEN.
RTECS #:9999999ZZ

Ingred Name:SPILL PROC: MOVE LEAKING CNTNR TO WELL VENTD AREA. FLAM
VAPS MAY SPREAD FROM SPILL. BEFORE ENTERING AREA, ESP (ING 10)
RTECS #:9999999ZZ

Ingred Name:ING 9: CONFINED AREAS, CHECK ATMOSPHERE W/APPROP DEVICE.
RTECS #:9999999ZZ

Ingred Name:OTHER PRECS: USE W/ADEQ VENT AT ALL TIMES. USE ONLY IN CLSD
SYS. CLOSE VALVE WHEN
NOT IN USE & WHEN EMPTY. KEEP (ING 12)
RTECS #:9999999ZZ

Ingred Name:ING 11: AWAY FROM OXIDIZING AGENTS. WHEN TWO/MORE GASES OR
LIQUEFIED GASES ARE MIXED, THEIR HAZ PROPERTIES MAY (ING 13)
RTECS #:9999999ZZ

Ingred Name:ING 12: COMBINE TO CREATE ADDNL, UNEXPECTED HAZS. OBTAIN &
EVALUATE SAFETY INFO FOR EACH COMPONENT BEFORE YOU (ING 14)
RTECS #:9999999ZZ

Ingred Name:ING 13:PRDCE THE MIX. CONSULT INDUS HYGIENIST/OTHER TRAINED
PERSON WHEN MAKING SFTY EVALS OF END PROD. REMEMBER,(ING

15)
RTECS #:9999999ZZ

Ingred Name:ING 14: GASES & LIQS HAVE PROPERTIES WHICH CAN CAUSE
SERIOUS INJURY/DEATH. BE SURE TO READ & UNDERSTAND ALL (ING 16)
RTECS #:9999999ZZ

Ingred Name:ING 15: LABELS & OTHER INSTRUCTIONS SUPPLIED W/ALL CNTNRS
OF THIS PROD. NOTE: COMPATIBILITY W/PLASTICS SHOULD (ING 17)
RTECS #:9999999ZZ

Ingred Name:ING 16: BE CONFIRMED PRIOR TO USE. FOR SFTY INFO ON GEN
HNDLG OF COMPRESSED GAS CYLS, OBTAIN COPY OF PAMPHLET (ING 18)
RTECS #:9999999ZZ

Ingred Name:ING
17: P-1, "SAFE HANDLING OF COMPRESSED GASES IN
CONTAINERS" FORM THE COMPRESSED GAS ASSOCIATION.
RTECS #:9999999ZZ

Ingred Name:OTHER PROT EQUIP: FOR CYLINDER HANDLING. PROTECTIVE
CLOTHING WHERE NEEDED.
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION
: AN UNLIKELY ROUTE OF
EXPOSURE. SKIN CONTACT/SKIN ABSORPTION: NO EVIDENCE OF ADVERSE
EFFECTS FROM AVAILABLE INFORMATION. INHALATION: METHANE IS AN
ASPHYXIANT. LACK OF OXYGEN CAN CAUSE DEATH. MODERATE
CONCENTRATIONS MAY CAUSE HEADACHE, DROWSINESS, DIZZINESS,
EXCITATION, EXCESS SALIVATION, (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ: VOMITING AND UNCONSCIOUSNESS.
CHRONIC: NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFO
RMATION.
Medical Cond Aggravated by Exposure:A KNOWLEDGE OF AVAIL TOXICOLOGICAL
INFO & PHYSICAL & CHEMICAL PROPERTIES OF MATERIAL SUGGEST THAT
OVEREXPOSURE IS UNLIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

===== First Aid Measures =====

First Aid:INGEST: CALL MD IMMED . THIS PRODUCT IS A GAS AT NORMAL TEMP
& PRESSURE. SKIN: WASH W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR.
GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GIVE OXYGEN IF BREA

T

HING IS DIFFICULT. CALL MD. EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. NOTE TO MD: THERE IS NO SPECIFIC ANTIDOTE. TREATMENT OF OVEREXP SHOULD BE DIRECTED AT CONTROL OF SYMPTOMS & CLINICAL CONDITION.

===== Fire Fighting Measures =====

Flash Point:-306F,-188C

Lower Limits:5%

Upper Limits:15%

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, WATER SPRAY OR FOG.

Fire Fighting Procedures:USE NIOSH APPRVD SCBA & FULL PROT EQUIP .

EVACUATE ALL

PERS FROM DANGER AREA. IMMED COOL CNTNRS W/WATER SPRAY FROM MAX DIST TAKING CARE NOT TO (SUPDAT)

Unusual Fire/Explosion Hazard:FLAM GAS. FORMS EXPLO MIXS W/AIR & OXIDIZING AGENTS. CNTNR MAY RUPTURE DUE TO HEAT OF FIRE. DO NOT EXTING FLAMES DUE TO POSS OF EXPLO RE-IGNIT. FLAM VAPS(ING 4)

===== Accidental Release Measures =====

Spill Release Procedures:DANGER:FORMS EXPLO MIXS W/AIR. IMMED EVACUATE ALL PERS FROM DANGER AREA. USE NIOSH APPRVD SCBA WHERE NEEDED.

REMOVE ALL SOURCES OF IGNIT IF W/OUT RISK. REDUCE VAPS W/FOG OR FINE WATER SPRAY. SHUT OFF LEAK IF W/OUT RISK. VENT AREA OF LEAK OR (ING 9)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN THE SYSTEM BY VENTING TO SAFE PLACE, THEN REPAIR THE LEAK.

Other Precautions:FLAM GAS

UNDER PRESS. USE PIPING & EQUIP ADEQ

DESIGNED TO W/STAND PRESS TO BE ENCOUNTERED. MAY FORM EXPLO MIXS W/AIR. GROUND ALL EQUIP. ONLY USE SPK PROOF TOOLS & EXPLO PROOF EQUIP. KEEP AWAY FROM HEAT, SPKS & OPEN FLAME. STORE & (ING 11)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELECT IN ACCORDANCE WITH OSHA 29 CFR 1910.134. RESPIRATORS SHALL BE ACCEPTABLE TO NIOSH.

Ventilation:LOCAL EXHAUST: EXPLOSION PROOF SYSTEM IS ACCEPTABLE.

M

ECHANICAL (GENERAL): INADEQUATE. SPECIAL/OTHER: NOT APPLICABLE.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER .

SELECT I/A/W OSHA 29 CFR 1910.132 & 1910.133. METATARSAL SHOES (ING 19)

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRE FIGHT PROC: EXTING FLAMES. REMOVE IGNIT SOURCES IF W/OUT RISK. IF FLAMES ARE ACCIDENTALLY EXTINGUISHED EXP

LO RE-IGNIT MAY OCCUR;

THEREFORE, APPROP MEASURES SHOULD BE TAKEN, EG TOTAL EVACUATION. R EAPPROACH W/EXTREME CAUTION. STOP FLOW OF GAS IF W/OUT RISK WHILE CONTINUING COOLING WATER SPRAY. REMOVE ALL (ING 2)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:-259F,-162C

Vapor Pres:GAS @ 20C

Vapor Density:0.554 @ 0C

Spec Gravity:GAS (H*2O=1)

Solubility in Water:SLIGHTLY SOLUBLE

Appearance and Odor:COLORLESS, ODORLESS GAS AT NORMAL TEMPERATURE AN D

PRESSURE.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS. MIXS W/BROMINE PENTAFLUORIDE, CHLORINE & YELLOW MERCURIC OXIDE, NITROGEN TRIFLUORIDE, LIQ (ING 7)

Stability Condition to Avoid:TEMPERATURES IN EXCESS OF 700C.

Hazardous Decomposition Products:THERMAL DECOMPOSITION OR BURNING MAY PRODUCE CO/CO*2. AT TEMPS IN EXCESS OF 700C & IN ABSENCE OF OXYGEN OR (ING 8)

=

===== Disposal Considerations =====

Waste Disposal Methods:DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE

CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warr

ants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.