

ACCUMETRIC INC. -- SILICONE ELASTOMER -- 8040-00-225-4548

=====
Product Identification
=====

Product ID:SILICONE ELASTOMER

MSDS Date:05/11/1995

FSC:8040

NIIN:00-225-4548

Kit Part:Y

MSDS Number: CCBYS

=== Responsible Party ===

Company Name:ACCUMETRIC INC.

Address:350 RING ROAD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385 FAX: 502-765-2412

Emergency Phone Num

:800-424-9300 CHEMTREC

Preparer's Name:GARY HARTLAGE

CAGE:58149

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLTRACETOXYSILANE OR SILANE, METHYLTRACETOXY-

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT ESTABLISHED.

ACGIH TLV:NOT ESTABLI

SHED.

Ingred Name:ETHYLTRIACETOXYSILANE
CAS:17689-77-9
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA, AMORPHOUS OR SILICA, FUMED.
CAS:7631-86-9
Fraction by Wt: 10%
Other REC Limits:8 PPM

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT MAY CAUSE SKIN & EYE
IRRITATION. INHALATION OF VAPOR
MAY CAUSE IRRITATION MAY CAUSE
NASAL & RESPIRATORY IRRITATION. INGESTING LARGE AMOUNTS MAY CAUSE
DIGESTIVE DISCOMFORT. CHRONIC: REPEATED/PROLONGED SKIN CONTACT MAY
CAUSE MODERATE IRRITATION.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:EYES-SLIGHT TO MODERATE IRRITATION WITH REDNESS
& SWELLING. SKIN-IRRITATION. INHALED-IRRITATION. INGESTED-DIGESTIVE
DISCOMFORT

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.
SKIN-WIPE OFF AND FLUSH WITH WATER. INHALED-REMOVE TO FRESH AIR.
INGESTED-NO FIRST AID SHOULD BE NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:=100.C, 212.F
212F,100C
Extinguishing Media:WATER FOG, CARBON DIOXIDE,

DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR SHOULD BE WORN IN FIRES INVOLVING CHEMICALS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT & CONTAIN FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE BELOW 90F/32C. KEEP CONTAINER CLOSED UNTIL READY FOR USE.

Other Precautions:PRODUCT FORMS ACETIC ACID (HOAH) WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL HOAC EXPOSURE WITHIN 10 PPM (TLV) OR USE RESPIRATORY PROTECTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:LOCAL EXHAUST IS RECOMMENDED.

Protective Gloves:WASHING AT MEALTIMES SHOULD BE ADEQUATE.

Eye Protection:SAFETY GLASSES AS MINIMUM.

Other Protective Equipment:NONE SPECIFIED BY MFR.DLA-HMIS:APPROPRIATE CLOTHING TO PREVENT PROLONGED SKIN CONTACT.EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health
KEY1=V5. PART A OF 2 PART KIT.

===== Physical/Chemical Properties =====

HCC:F2

Vapor Pres: