

SCOT INC. -- 6038100-04 AND GATE -- 1377-01-271-5483

===== Product Identification =====

Product ID:6038100-04 AND GATE

MSDS Date:12/04/1991

FSC:1377

NIIN:01-271-5483

MSDS Number: CCGMR

=== Responsible Party ===

Company Name:SCOT INC.

Address:2525 CURTISS ST

City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Info Phone Num:708-969-0620

Emergency Phone Num:800-535-5053

Preparer's Name:NICHOLAS F

TURCIC

CAGE:MO896

=== Contractor Identification ===

Company Name:SCOT INC

Address:2525 CURTISS ST

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Phone:630-969-0620

CAGE:93455

Company Name:SCOT INC.

Address:2525 CURTISS ST

City:DOWNERS GROVE

State:IL

ZIP:60515-0705

Country:US

Phone:708-969-0620

CAGE:MO896

===== Composition/Information on Ingredients =====

Ingred Name:LEAD AZIDE

CAS:13424-46-9

RTECS #:OF8650000

Fraction by Wt: 40%

Ingred Name:HNS HEXANITROSTILBENE

F

raction by Wt: 60%

Ingred Name:ALUMINUM HOUSING

Ingred Name:END FITTING

Ingred Name:SHUTTLE

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:MINIMAL NOXIOUS GASES LIBERATED IF  
HERMETIC SEAL SHOULD RUPTURE.  
Explanation of Carcinogenicity:NONE

===== First Aid Measures =====

First Aid:OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Extinguishing Media:WATER ONLY, NO DRY CHEMICAL, CO2/HALON. LARGE  
FIRES: FLOOD AREA W/WATER FROM A DISTANCE.  
Fire Fighting Procedures:USE FLOODING WATER AS FOG. COOL CONTAINERS  
W/WATER, APPLY FROM A DISTANCE. EVACUATE TO RADIUS OF 1500 FEET.  
Unusual Fire/Explosion Hazard:MOVE CONTAINERS W/O RISK. USE COOL WATER  
TO SIDES OF CONTAINERS. MASSIVE FIRES IN CARGO AREA, USE UNMANNED  
HOSE  
HOLDER/MONITOR NOZZLES, IF IMPOSSIBLE, EVACUATE.

===== Handling and Storage =====

Handling and Storage Precautions:USE CAUTION IN HANDLING ACTUATED  
DEVICE SURFACE TEMP MAY BE 200F. KEEP FIRE AWAY.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health  
THE AND GATE IS USED IN THE CREW ESCAPE SYSTEM OF THE US AIR FORCE,  
B-18 AIRCRAFT. THIS DEVICE CONSISTS OF HOUSING, END FITTING & A  
SHUTTLE COMPRISED OF

TWO PRIMERS & DETONATORS. TWO SEPARATE HIGH  
ENE RGY INPUTS ARE REQUIRED TO ACTUATE THE DEVICE.

===== Physical/Chemical Properties =====

Appearance and Odor:ALUMINUM HOUSING, END FITTING & SHUTTLE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:HEAT, FLAME. MODERATE EXPLOSION HAZARD  
WHEN SHOCKED/EXPOSED TO HEAT.

===== Disposal Considerations =====  
=====

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL  
REGULATIONS. INITIATE BY APPLICATION OF HIGH ENERGY PARTICLE SOURCE  
TO BOTH INPUTS (2) & PLUG OUTPUT. UN0173.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability f  
or its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.