

KRYLON DIV OF SHERWIN WILLIAMS -- 7161 WHITE -- 8010-01-418-8314

===== Product Identification =====

Product ID:7161 WHITE  
MSDS Date:03/01/1995  
FSC:8010  
NIIN:01-418-8314  
MSDS Number: CCGPT  
=== Responsible Party ===  
Company Name:KRYLON DIV OF SHERWIN WILLIAMS  
Address:31500 SOLON RD  
City:SOLON  
State:OH  
ZIP:44139-3908  
Country:US  
Info Phone Num:216-292-7400/800-832-2541  
Emergency Phone Num:216-292-7400  
/800-832-2541  
CAGE:KRYLO  
=== Contractor Identification ===  
Company Name:BORDEN CHEMICAL CO  
Address:180 E BROAD ST  
Box:City:COLUMBUS  
State:OH  
ZIP:43215-3705  
Country:US  
Phone:614-225-6124  
CAGE:86142  
Company Name:KRYLON DIV OF SHERWIN WILLIAMS  
Address:6830 COCHRAN RD  
City:SOLON  
State:OH  
ZIP:44139-3908  
Country:US  
Phone:216-292-7400/800-832-2541  
CAGE:KRYLO

===== Composition/Information on Ingredients =====

Ingred Name:PROPANE (DIMETHYLMETHANE) \*96-2\*  
CAS:74-98-6  
RTECS #:TX2275000

Fraction by Wt: 14%  
Other REC Limits:1800 MG/CUM  
OSHA PEL:1000 PPM  
ACGIH TLV:SIMPLE ASPHYXIAN

Ingred Name:BUTANE, N-BUTANE  
CAS:106-97-8  
RTECS #:EJ4200000  
Fraction by Wt: 14%  
Other REC Limits:800 PPM  
OSHA PEL:800 PPM  
ACGIH TLV:1900 MG/CUM

Ingred Name:TOLUENE (IARC CARC- GROUP 3) \*96-3\*  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 10%  
Other REC Limits:375 MG/CUM  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPARAFFINIC HYDROCARBONS (NAPHTHA PE  
TROLEUM),  
HYDROTREATED HEAVY, NON AROMATIC HEAVY NAPHTHA) ISOPAR G  
CAS:64742-48-9  
Fraction by Wt: 7%

Ingred Name:ACETONE; DIMETHYL KETONE; 2-PROPANONE  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 19%  
OSHA PEL:2400 MG/CUM  
ACGIH TLV:750 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:CARBONIC ACID, CALCIUM SALT (1:1), CALCIUM CARBONATE,  
DURAMITE  
CAS:471-34-1  
RTECS #:FF9335000  
Fraction by Wt: 22%  
Other REC Limits:10 MG/CUM (DUST)

Ingred Name:TITANIUM DIOXIDE, TITANIUM OXIDE (

SUSPECTED ANIMAL  
CARCINOGEN, IARC GROUP 3) \*96-3\*  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 6%  
OSHA PEL:15 MG/CUM  
ACGIH TLV:10 MG/CUM (DUST)

Ingred Name:VOLATILE ORGANIC CONTENT: 63  
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:IRRITATION OF EYES, SKIN & RESPIRATORY  
SYSTEM. MAY CAUSE NERVOUS SYSTEM  
DEPRESSION. EXTREME OVEREXPOSURE  
MAY CAUSE UNCONSCIOUSNESS & POSSIBLY DEATH. REPEATED & PROLONGED  
OVEREXPOSURE TO SOLVENTS MAY CAUSE PERMANENT BRAIN DAMAGE.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA, LOSS  
OF COORDINATION, REDNESS, BURNING SENSATION.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM AIR. RESTORE BREATHING. KEEP WARM &  
QUIET. SKIN: WASH THOROUGHLY W/SO  
AP & WATER. EYES: FLUSH W/LARGE  
AMOUNTS OF WATER FOR 15 MINS. INGESTION: NEVER GIVE ANYTHING BY  
MOUTH TO AN UNCONSCIOUS PERSON. GIVE SEVERAL GLASSES OF WATER.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:120F. HEAT FROM SUNLIGHT, RADIATORS,  
STOVES, HOT WATER & OTHER SOURCES COULD CAUSE CONTAINER TO BURST.  
INTENTIONAL MISUSE CAN BE HARMFUL/FATAL.

===== Exposure Cont

rols/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CAN'T BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR PROPERLY FITTED ORGANIC VAPOR PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA. WHEN SANDING/ABRADING DRIED FILM, WEAR NIOSH/MSHA APPROVED DUST RESPIRATOR.

Ventilation:LOCAL EXHAUST: PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF EXPOSURE IS BELOW ACCEPTABLE MATERIALS.

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY SPECTACLES

Work

Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

EYE PROTECTION:SAFETY SPECTACLES W/PERFORATED SHIELDS. SPEC FIRE CONT'D: WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE AUTOIGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:1

Evaporation Rate & Reference:FASTER THAN ETHER

Appearance and Odor:WHITE

or:WHITE

Percent Volatiles by Volume:>75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:FIRE: CO<sub>2</sub>, CO, OXIDES OF METAL.

===== Disposal Considerations =====

Waste Disposal Methods:DON'T INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.