View NSN Online: https://aerobasegroup.ae/nsn/6750-01-360-5171

EASTMAN KODAK COMPANY -- 825 5549 FLEXICOLOR RA BLEACH REPLENISHER NR 6750-01-360-5171

Product ID:825 5549 FLEXICOLOR RA BLEACH REPLENISHER NR MSDS Date:02/07/1997 FSC:6750 NIIN:01-360-5171 MSDS Number: CCJGD === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-477 -3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

======= Composition/Information on Ingr

edients ==========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 60 - 65% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:AMMONIUM FERRIC PROPYLENEDIAMINETETRAACETIC ACID CAS:111687-36-6 Fraction by Wt: 10 - 15% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM BROMIDE CAS:12124-97-9 RTECS #:BO9170000 Fraction by Wt: 5 - 10% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM NITRATE CAS:6484-52-2 RTECS #:BR9050000 Fr action by Wt: 8% Other REC Limits:NONE RECOMMENDED

Ingred Name:SUCCINIC ACID CAS:110-15-6 RTECS #:WM4900000 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE. ACUTE- EYE:NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIE NT IRRITATION. SKIN:LOW

HAZARD FOR RECOMMENDED HANDLING. INHALE:EXPECTED TO BE A LOW HAZARD. ORAL:EXPECTED TO BE A LOW INGESTIO N HAZARD. CHRONIC-UNKNOWN.

Explanation of Carcinogenicity:NONE Effects of Overexposure:TRANSIENT EYE IRRITATION Medical Cond Aggravated by Exposure:NONE

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. EYES:ANY MATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT

IMMEDIATELY WITH WATER. SKIN:WASH WITH SOAP & WATER. ORAL:DRINK 1-2 GLASSE S OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Flash Point:NONE

Lower Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedures:WEAR PROTECT

IVE CLOTHING AND NIOSH-APPROVED

SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard:MAY CAUSE DECOMPOSITION. DRIED MATERIAL CAN ACT AS AN OXIDIZER.

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNT OF WATER IF PERMITTED. OTHERWISE, ABSORB SPILL WITH INERT MATERIAL SUCH AS VERMICULITE. PLACE IN A CONTAINER FOR DISPOSAL. CLEAN AREA THOR

OUGHLY TO REMOVE RESIDUAL CON TAMINATION. PREVENT RUNOFF FROM ENTERING SEWERS.

Neutralizing Agent:NOT RELEVANT

 Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINER, AWAY FROM INCOMPATIBLE MATERIALS.
 Other Precautions:DO NOT GET IN EYES. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. KEEP OUT OF REACH OF CHILDREN.

Resp

iratory Protection: NONE SHOULD BE NEEDED. Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves: RUBBER FOR PROLONGED/REPEATED CONTACT Eye Protection: SAFETY GLASSES WITH SIDE SHIELD/GOGGLES Other Protective Equipment: EYE BATH, SAFETY SHOWER, WASHING FACILITIES Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health FORMULA AN D/OR PERCENTAGE CHANGED. ECOLOGICAL INFORMATION:A LOW BIOCHEMICAL OXYGEN DEMAND, A LOW POTENTIAL TO AFFECT AQUATIC ORGANISMS. AFTER DILUTION WITH LARGE AMOUNT OF WATER, FOLLOWED BY WASTE TRE ATMENT, IT IS NOT EXPECTED TO CAUSE ADVERSE ENVIRONMENTAL EFFECTS. HCC:C3 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:>212F,>100C Decomp Temp:Decomp Text:>419F,>215C Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravi ty:1.17 pH:4 Solubility in Water:COMPLETE Appearance and Odor: DARK GREEN LIQUID - ODORLESS Percent Volatiles by Volume:60-65 

Stability Indicator/Materials to Avoid:YES
BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG REDUCING AGENTS. BASE LIBERATES FLAMMABLE MATERIAL.
Stability Condition to Avoid:TEMPERATURES ABOVE 115C/239F
Hazardous Decomposition Products:HYDROGEN BROMIDE, AMMONIA, CHLORAMINE, NI
TROGEN OXIDE, CARBON MONOXIDE, CARBON DIOXIDE

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL REGULATIONS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER, IF ALLOWED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.