

ECOLINK INC -- PREPSOLV-PART#0315 -- 6850-01-394-0160

===== Product Identification =====

Product ID:PREPSOLV-PART#0315

MSDS Date:06/11/1996

FSC:6850

NIIN:01-394-0160

MSDS Number: CCJHS

=== Responsible Party ===

Company Name:ECOLINK INC

Address:1481 ROCK MOUNTAIN BLVD

City:STONE MOUNTAIN

State:GA

ZIP:30083

Country:US

Info Phone Num:(800) 886-8240 OR 404-621-8240

Emergency Phone Num:(800) 886-8240

OR 404-621-8240

CAGE:0WU71

=== Contractor Identification ===

Company Name:ECOLINK INC

Address:1481 ROCK MOUNTAIN BLVD

Box:City:STONE MOUNTAIN

State:GA

ZIP:30083-1505

Country:US

Phone:800-886-8240/770-621-8240

CAGE:0WU71

===== Composition/Information on Ingredients =====

Ingred Name:D-LIMONENE

CAS:5989-27-5

RTECS #:GW6360000

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS > 5.0 G/KG

R

outes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION-MAY CAUSE GASTROINTESTINAL
IRRITATION. INHALATION-EXCESSIVE INHALATION OF VAPOR CAN CAUSE
RESPIRATORY TRACT IRRITATION. EYES-UNDILUTED LIQUID MAY BE
IRRITATING TO EYES. SKIN-PROLONGED OR REP EATED EXPOSURE MAY CAUSE
SKIN IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INGESTION-NAUSEA, VOMITING. INHALATION-S
ORE

THROAT, COUGHING, SHORTNESS OF BREATH, NAUSEA AND DIZZINESS.
SKIN-MAY CAUSE EXCESSIVE DRYING OR FLAKING OF SKIN.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INGESTION-DRINK LOTS OF WATER TO DILUTE SUBSTANCE. GET
MEDICAL ATTENTION. INHALATION-REMOVE TO FRESH AIR IMMEDIATELY. IF
BREATHING IS DIFFICULT, GET MEDICAL HELP. EYES-IRRIGATE IMMEDIATELY
WITH WATER FOR AT LEAST 1

5 MINUTES. GET MEDICAL ATTENTION.

SKIN-WASH OFF IN FLOWING WATER OR SHOWER USING SOAP & WATER. REMOVE
CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:122F,50C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:FLAMMABLE LIQUID. AVOID HEAT, SPARKS AND OPEN
FLAMES.

Unusual Fire/Explosion Hazard:CARBON DIOXIDE, CARBON MONOXIDE, ACRID
FUMES. STAY UPWIND
OF FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: SHOULD BE ABSORBED BY "PIG" DIRT,
SAND OR OTHER SUITABLE ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. READ LABEL
BEFORE USE. AVOID EXCESSIVE CONTACT WITH VAPOR OR LIQUID. AVOID
HEAT, SPARKS AND OPEN FLAMES. AVOID WARM STORAGE.

Other Precautions:STORE AWAY FROM STRONG ACIDS AND

BASES. TREAT AS A

COMBUSTIBLE LIQUID. AS WITH ANY COMBUSTIBLE OIL OR SOLVENT. ALL RAGS USED IN CONJUNCTION WITH THIS PRODUCT MUST BE PLACED IN A METAL SEALED CONTAINER AFTER USE TO AVOID COMBUSTION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF VAPOR MIST IS GENERATED, USE A NIOSH CERTIFIED ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER.

Ventilation:LOCAL EXHAUST/HOOD OR FAN MAY BE USED. MECHANICAL EXHAUST MAY BE NEEDED IN CONFINED SPACES.

Protective Gloves:STANDARD INDUSTRIAL RUBBER GLOVES.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:RUBBER APRONS ARE RECOMMENDED IF SPLASHING COULD OCCUR.

Work Hygienic Practices:USE WITH ADEQUATE VENTILATION. WASH HANDS AFTER USE.

Supplemental Safety and Health
NONE.

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:325F,163C

Vapor Pres:1.0

Vapor

Density:4.7

Spec Gravity:0.844

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water: