View NSN Online: https://aerobasegroup.ae/nsn/5970-01-386-6169

VARFLEX CORPORATION -- VARGLAS SILICONE RESIN 500 -- 5970-01-386-6169

Product ID:VARGLAS SILICONE RESIN 500 MSDS Date:07/23/1993 FSC:5970 NIIN:01-386-6169 MSDS Number: CCKPZ === Responsible Party === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET City:ROME State:NY ZIP:13440 Country:US Info Phone Num:315-336-4400 Emergency Phone Num:315-336-4400 С AGE:79074 === Contractor Identification === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET Box:City:ROME State:NY ZIP:13440 Country:US Phone:315-336-4400 CAGE:79074

Ingred Name:FIBROUS GLASS Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST

Ingred Name:SILICONE COATING--METHYL, PHENYL Other REC Limits:NONE RECOMMENDED

============ Hazards Identification ==========

=========

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. DO NOT RUB OR SCRATCH IRRITATED AREAS. INHALED:REMOVE TO FRESH AIR. PROV IDE OXYGEN/CPR IF NEEDED. OR AL:UNLIKELYTO OCCUR.

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL. Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:WEAR APPROVED RESPIRATOR AND CHEMICALLY COMPATIBLE GLOVES IF NEEDED. FOR DUST AND FIBERS GENER ATED DURING FABRICATION, VACUUM OR SWEEP UP. AVOID CREATING DUST. PLACE IN

APPROPRIATE CONTAINER FOR WASTE DISPOSAL. VENTILATE AREA AND WASH SPILL SITE.

Neutralizing Agent:NOT RELEVANT

 Handling and Storage Precautions:STORE AWAY FROM DIRECT SUNLIGHT, AT A RELATIVE HUMIDITY OF 30-60%. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:AVOID INHALATION OF FIBERS. AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGH LY AFTER HANDLING MATERIAL.

Respiratory Protection:NONE NORMALLY REQUIRED. IN DUSTY SITUATION, A NIOSH APPROVED AIR SUPPLIED RESPIRATOR OR DUST RESPIRATOR IS ADVISED.

Ventilation: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE AT THE MINIMUM.

Protective Gloves:LEATHER OR COTTON

Eye Protection: GOGGLES/SAFETY GLASSES

Other Protective Equipment: EYE WASH STATION, EMERGENCY

SHOWER

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.

Supplemental Safety and Health

HCC:N1 NRC/State Lic Num:NOT RELEVANT Spec Gravity:2.54 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:NOT RELEVANT Appearance and Odor:SILICONE RESIN COATED WITH NO ODOR

===== Stabili

ty and Reactivity Data ===============

Stability Indicator/Materials to Avoid:YES NONE Hazardous Decomposition Products:BINDERS MAY PRODUCE CARBON MONOXIDE, CARBON DIOXIDE AND OTHER HYDROCARBONS.

Waste Disposal Methods:DISPOSE IN MUNICIPAL OR INDUSTRIAL LANDFILL. COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated

for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.