View NSN Online: https://aerobasegroup.ae/nsn/8010-01-396-6778

Product ID:TT-P-102F, TY III, CLASS 2, #24108 GREEN 700G115

MSDS Date:05/01/1995

FSC:8010

NIIN:01-396-6778

MSDS Number: CCKRV === Responsible Party === Company Name:GRIGGS PAINT Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ ZIP:85040 Country:US

Info Phone Num:602-243-3293

**Emerg** 

ency Phone Num:800-424-9300 CHEMTREC Preparer's Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification === Company Name:GRIGGS PAINT Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ ZIP:85040 Country:US

Phone:602-243-3293

CAGE:58963

Company Name: GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319 Phone:602-243-3293

CAGE:DO312


======= Composition/Information on Ingredients ========

Ingred Name:ALIPHATIC HYDROCARBONS (STODDARD TYPE)(SARA III)(VAPOR

PRESSURE = 2.0 MMHG @ 68F) CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 16.0% Other REC Limits: NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:100 PPM Ingred Name: MAGNESIUM SILICATE CAS:14807-96-6 RTECS #:WW2710000 Fraction by Wt: 10.0% Other REC Limits: NONE RECOMMENDED OSHA PEL:15 MG/M3 ACGIH TLV:2 MG/M3 ========== Hazards Identification =============== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Haza rds Acute and Chronic:EYES: DIRECT CONTACT MAY CAUSE IRRITATION. PROLONGED CONTACT MAY CAUSE SKIN IRRITATION. INHAL: HIGH VAPOR CONCENTRATIONS MAY LEAD TO LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION, CNS DE PRESSION. INGEST: POSSIBLE GASTROINTESTINAL DISTURBANCES. ASPIRATION OF PRODUCT INTO **LUNGS MAY CAUSE PNEUMONITIS.\*** Effects of Overexposure:\* PULMONARY EDEMA AND HEMORRAGE. EYES: POSSIBLE IRRITATION W/DIRECT CONTACT, SKIN: POSSIBLE IRRITATION &/OR DE RMATITIS. MAY BE ABSORBED THROUGH SKIN. Medical Cond Aggravated by Exposure: INDIVIDUALS WITH PRE-EXISTING DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN, CENTRAL NERVOUS

SYSTEM, LIVER AND KIDNEY.

First Aid:EYES: IMMEDIATELY FLUSH W/LARGE AMOUNTS WATER 15 MINUTES. SEEK MED AID. SKIN: WASH THOROUGHLY W/SOAP & WATER. SEEK MED AID IF IRRATION PERSISTS. INGEST: IMMEDIATELY SEEK MED AID. DO NOT INDUCE VOMITIN



UATE VENTILATION.
Supplemental Safety and Health
**OV/FILTER UNITS OK FOR USE.
========== Physical/Chemical Properties ============
Boiling Pt:B.P. Text:334F,168C
Vapor Density:>AIR
Spec Gravity:1.4 (WATER=1
VOC Grams/Liter:2.03
Viscosity:80-90 KU
Evaporation Rate & Evaporation R
Solubility in Water: ESSENTIALLY NIL
Appearance and Odor:VISCOUS LIQUID WITH TYPICAL PAINT ODOR, GREEN
Percent Volatiles by Volume:30.5
========= Stability and Reactivity Dat
a ====================================
Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:FLAMES, SPARKS, SMOKING & HEAT
Hazardous Decomposition Products:CARBON MONOXIDE & CARBON DIOXIDE
======== Disposal Considerations ============
Waste Disposal Methods:USE INERT ABSORBENT MATERIAL ON SPILLS. DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL REGULATIONS.
======================================
Disclaimer
(provided with this information by the compiling agencies):

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.