

DAUBERT CHEMICAL COMPANY -- NOX RUST 509 -- 8030-00-598-5915

===== Product Identification =====

Product ID:NOX RUST 509

MSDS Date:08/02/1995

FSC:8030

NIIN:00-598-5915

MSDS Number: CCQSN

=== Responsible Party ===

Company Name:DAUBERT CHEMICAL COMPANY

Address:4700 S CENTRAL AVE

City:CHICAGO

State:IL

ZIP:60638

Country:US

Info Phone Num:312-496-7350/FAX 708-496-7367

Emergency Phone Num:312-496-7350/8

00-424-9300(CHEMTREC)

Preparer's Name:J KUKSUK

CAGE:02847

=== Contractor Identification ===

Company Name:DAUBERT CHEMICAL CO

Address:1200 JORIE BLVD

City:OAK BROOK

State:IL

ZIP:60521-2210

Country:US

CAGE:02847

Company Name:DAUBERT CHEMICAL COMPANY

Address:4700 S CENTRAL AVE

Box:City:CHICAGO

State:IL

ZIP:60638

Country:US

Phone:708-496-7350

CAGE:0YMU2

Company Name:RALRUBE INC.

Address:36977 FOX GLEN

Box:City:FARMINGTON HILLS

State:MI

ZIP:48331

Country:US

Phone:248-661-0260, FAX 248-661-3941

CAGE:6

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL (SEVERELY SOLVENT REFINED &/OR SEVERELY
HYDROTREATED).

Fraction by Wt: 55-65%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:5 MG/M3

Ingred Name:PETROLEUM HYDROCARBON (PETROLATUM).

CAS:8009-03-8

Fraction by Wt: 25-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3 FUMES

Ingred Name:PARAFFIN WAX

CAS:8002-74-2

RTECS #:RV0350000

Fraction by Wt: 3-6%

Other REC Limits:NONE RE
COMMENDED

OSHA PEL:2 MG/M3 (FUME)

ACGIH TLV:2 MG/M3 (FUME)

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EXCESSIVE INHAL MAY PRODUCE
DIZZINESS, NAUSEA, HEADACHE, INCOORDINATION. MAY CAUSE REVERSIBLE
EYE & SKIN IRRIT. PROLONGED SKIN EXPOSURE MAY CAUSE DERMITITIS OR
OIL ACNE. BREATHING MISTS MAY CAU SE DIZZINESS O
R PULMONARY IRRIT.

Medical Cond Aggravated by Exposure:EXPOSURE MAY AGGRAVATE PRE-EXISTING
RESPIRATORY OR SKIN PROBLEMS.

=====
First Aid Measures
=====

First Aid:INHAL: REMOVE TO FRESH AIR. CONSULT PHYSICIAN. IF BREATH
DIFFICULT GIVE OXYGEN. NOT BREATH, GIVE ARTIF RESP. EYES: FLUSH
IMMED W/RUNNING WATER >15 MINS. SEEK MED ATTN IMMED. SKIN: WASH
W/SOAP & WATER. REMOVE CONTAM CLOTH/SHOES. INGEST:DONTINDUCE
VOMIT. CALL DR. IF VOMITING SPO

NTANEOUSLY KEEP HEAD BELOW HIPS TO
PREVENT ASPIRATION OF LIQUID INTO LUNGS.

===== Fire Fighting Measures =====

Flash Point:>300F,>149C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY, OR
REGULAR FOAM, FOG.

Fire Fighting Procedures:PRESSURE SCBA/PROTECTIVE CLOTHING. (LIMITED
PROT). EVAC AREA. STAY UPWIND/OUT OF LOW AREA. NOTIFY AUTHORITIES
OF RUNOFF.MOVE CNTNR FROM FIRE AREA IF SAFE.*

Unusual Fire/Explosion Hazard:KEEP AWAY FROM IG
NITS. VAPORS MAY TRAVEL

TO IGNIT SOURCE & FLASHBACK. CNTNR MAY EXPLODE IN HEAT/FIRE. VAPOR
EXPLOSION HAZ INDOORS/OUTDOORS/SEWERS.

===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF IGNITION SOURCES. NO FLARES, SMOKING,
FLAMES IN HAZARD AREA. STOP LEAK IF SAFE. LG SPILLS: DIKE FAR AHEAD
OF SPILL. SM SPILLS: TAKE UP W/SAND/OTHER NONCOMBUSTIBLE ABSORBENT.
PLACE IN CONTAINERS FOR DISPOSAL.

===== Handling and
Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA.
NO FLAME, SPARK, HOT SURFACES. DONT FLAME CUT/WELD ON/NEAR CNTNR.
EMPTY CNTNRS HAZARDOUS.

Other Precautions:NEVER WEAR CONTAM CLOTHING. LAUNDRER BEFORE REWEARING.
DISCARD OIL SOAKED SHOES. WASH W/SOAP/WATER AFTER USE/BEFORE
SMOKING/EATING. AVOID EXCESSIVE SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESP
IRATOR FOR ORGANIC VAPOR AND
MIST CONTROL EXPOUSRE WHERE VENTILATION IS INADEQUATE.

Ventilation:GENERAL AND LOCAL EXHAUST.

Protective Gloves:IMPERVIOUS (VITON, PVOH, ETC).

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS,CHEM GOGGL

Other Protective Equipment:IF SPLASHING IS ANTICIPATED, WEAR RUBBER
APRON/BOOTS/OTHER PROTECTIVE EQPMT TO MINIMIZE CONTACT.

Supplemental Safety and Health

* USE WATER ON CNTNR SIDES EXPOSED TO FIRE UNTIL WELL AFTER FIRE IS
OUT. STAY AWAY FROM ENDS OF TANKS. US

E UNMANNED HOSE HOLDER/MONITOR

NOZ FOR MASSIVE FIRE IN CARGO AREA. WITHDRAW IMMEDIATELY IF RISING SOUND FROM VENTING SAFETY DEVICE OR DISCOLORATION OF TANK.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:1

Spec Gravity:0.9

pH:NA

VOC Grams/Liter:.8

Evaporation Rate & Reference:>1 (BU AC=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK AMBER, SOFT WAXY SOLID, PETROLEUM OIL ODOR.

Percent Volatiles by Volume: