

SIFCO METACHEMICAL DIV OF SIFCO INDUSTRIES,INC. -- DALIC SOLUTION TIN, CODE 2090 --
6850-01-066-8311

=====
===== Product Identification =====

Product ID:DALIC SOLUTION TIN, CODE 2090

MSDS Date:03/15/1995

FSC:6850

NIIN:01-066-8311

MSDS Number: CDGPM

==== Responsible Party ====

Company Name:SIFCO METACHEMICAL DIV OF SIFCO INDUSTRIES,INC.

Address:5708 SCHAAF ROAD

City:CLEVELAND

State:OH

ZIP:44131-1394

Countr

y:US

Info Phone Num:216-881-8600

Emergency Phone Num:216-881-8600, 216-524-0099

Preparer's Name:WERNER A. EHRENSCHNEIDER

CAGE:11924

==== Contractor Identification ====

Company Name:SIFCO SELECTIVE PLATING DIV OF SIFCO INDUSTRIES INC.

Address:5708 SCHAAF ROAD

Box:City:CLEVELAND

State:OH

ZIP:44131-1394

Country:US

Phone:216-524-0099/ FAX: -6331

CAGE:11924

=====
===== Composition/Information on Ingredients =====

Ingred Name:TIN (DESCRIBED ON MSDS AS AN ORGANIC COMPOUND.)

CAS:7440-31-5

RTECS #:XP7320000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9495

Ingred Name:ETHYLENEDIAMINE (SARA 302) (CERCLA)

CAS:107-15-3

RTECS #:KH8575000

Fraction by Wt: 7-13%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:S, 10 PPM; 9495

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 67-83%

Other REC Limits:NONE RECOMMENDED

=====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:MAY CAUSE IRRITATION. SKIN:MAY CAUSE IRRITATION. SKIN ABSORPTION:NOT ABSORBED THROUGH SKIN. INHALATION:MAY CAUSE ;SNEEZING, WATERING OF EYES, NASAL DISCHARGE, COUGHING. INGESTION:HARMFUL IF SWALLOWED. CAN IRRITATE MOUTH, THROAT, STOMACH. MAY CAUSE G/I IRRITATION.

CHRONIC:MAY CAUSE DAMAGE. MAY SENSITIZE ALLERGIES.

Explanation of Carcinogenicity:MANUFACTURER GAVE NO INFORMATION ABOUT CARCINOGENICITY. HMIS FOUND NO LISTING & DOES NOT EXPECT IT TO BE CARCINOGENIC.

Effects of Overexposure:IRRITATION, COUGHING, WATERING EYES, SNEEZING, NASAL DISCHARGE

Medical Cond Aggravated by Exposure:NONE REPORTED

===== First Aid Measures =====

First Aid:IF IRRITATION PERSISTS/IS SEVERE,GET MEDICAL ATTENTION.
E

EYE:FLUSH W/WATER FOR 15 MIN. SKIN:FLUSH W/WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRY BEFORE REUSE. INHALED:REMOVE FROM EXPOSURE. AID/RESTORE BREATHING AS NEEDED. INGESTED:DO NOT INDUCE VOMITING. GIVE LARGE QUANTITY MILK OR WATER TO DRINK THEN COOKING OIL OR FRESH EGGS. GET IMMEDIATE MEDICAL ATTENTION. NOTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:ALL

Fire Fighting Procedures:NIOSH/MSHA APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS. STRUCTURAL FIRE FIGHTERS PROTECTIVE CLOTHING MAY NOT PROVIDE ADEQUATE PROTECTION.

Unusual Fire/Explosion Hazard:CONTAINERS CAN BUILD UP PRESSURE & BURST IF EXPOSED TO HEAT (FIRE). WATER RUNOFF CAN CAUSE ENVIRONMENTAL DAMAGE. DIKE AREA FOR LATER DISPOSAL.

===== Accidental Release Measures =====

Spill Release Procedures:NOTIFY FACILITY EMERGENCY C

COORDINATOR. WEAR

PROTECTIVE CLOTHING. PROVIDE MAXIMUM VENTILATION. ELIMINATE IGNITION SOURCES. CAREFULLY MOP UP/VACUUM SPILL & TRIPLE RINSE W/WATER INTO SUITABLE PLASTIC CONTAINER. FLUSH SPILL AREA WITH PLENTY OF WATER.

Neutralizing Agent: SODA ASH, CRUSHED LIMESTONE

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORE AT 60-90F AWAY FROM INCOMPATIBLE MATERIALS & PHYSICAL HAZARDS. KEEP CONTAINER TIGHTLY CLOSED & UPRIGHT.

HT. DO NOT REMOVE OR DEFACE LABELS.

Other Precautions: USE BUDDY SYSTEM WHEN WORKING W/CHEMICALS. DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT BREATHE VAPOR, MIST, GAS. USE W/ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. DO NOT REUSE CONTAINER; TRIPLE RINSE THEN DISPOSE PROPERLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF ENGINEERING CONTROLS ARE NOT FEASIBLE, THE RESPIRATOR PROGRAM MUST COMPLY W/OSHA 29CFR1910.134, 30CFR11, & ANSI Z88.2.

Ventilation: LOCAL EXHAUST VENTILATION IS REQUIRED TO MEET THE PERMISSIBLE EXPOSURE LIMITS (PEL) DURING THE USE OF THIS PRODUCT.

Protective Gloves: NITRILE, NEOPRENE, VINYL, LATEX

Eye Protection: CHEMICAL SPLASH GOGGLES/SAFETY GLASSES

Other Protective Equipment: IMPERVIOUS BOOTS, APRON, PROTECTIVE CLOTHING REQUIRED BY JOB CONDITIONS. EYE WASH, SAFETY SHOWER & WASHING FACILITIES.

Work Hygienic Practices: MFR GAVE NO INFORMATION OF MSDS.

Supplemental Safety and Health

FACE SHIELD PLUS SAFETY GLASSES W/SIDE SHIELDS ARE ALSO ACCEPTABLE EYE PROTECTION. DO NOT WEAR CONTACTS.

=====
===== Physical/Chemical Properties =====

HCC: C3

NRC/State Lic Num: NONE

Boiling Pt: B.P. Text: >212F, >100C

Melt/Freeze Pt: M.P/F.P Text: