

PRODUCTS RESEARCH & CHEMICAL CORPORATION -- PR-1432 G 50 #1432G12 -- 8030-00-433-9032

===== Product Identification =====

Product ID:PR-1432 G 50 #1432G12

MSDS Date:06/12/1996

FSC:8030

NIIN:00-433-9032

Kit Part:Y

MSDS Number: CDKJX

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORPORATION

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info

Phone Num:818-240-2060

Emergency Phone Num:800-424-9300 CHEMTREC/800-228-5635

Preparer's Name:SEROJE HARTOONIANI

CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCTS RESEARCH & CHEMICAL

Address:NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:818-240-2060

CAGE:DO563

=====

==== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION\_INGREDIENT

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE: BURN/TEAR/RED/TRANSIENT CORNEA  
INJURY. SKIN: HARMFUL/RAPID ABSORPTION. INHAL: LIVER/KIDNEY DAMAGE.  
CHRONIC: MAY CAUSE PENETRATING ULCERS TO SKIN/MUCOUS M  
EMBRANES OF  
NOSE/PERFORATION OF CARTILAGINOUS NASAL SEPTUM.

==== First Aid Measures =====

First Aid:EYE: FLUSH W/LUKE WARM WATER. CALL DR. SKIN: WASH W/SOAP AND  
WATER. CALL DR. INHAL: REMOVE TO FRESH AIR. GET MED AID. INGEST:  
CALL DR.

==== Fire Fighting Measures =====

Flash Point:>200F,>93C  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG.  
Fire Fighting Procedures:USE COMPLETE PERSONAL PRO  
TECTION.

==== Accidental Release Measures =====

Spill Release Procedures:DIKE/COVER SPILL W/NONOXIDIZABLE ABSORBENT.  
SCOOP INTO CONTAINER. SPRINKLE SODIUM THIOSULFATE ON RESIDUE. WORK  
INTO RESIDUE. CLEAN AREA W/WATER. CERCLA RQ FOR SODIUM DICHROMATE  
IS 10 LBS.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN APPLYING IN ANY CIRCUMSTANCES LIKELY TO  
PRODUCE AIRBOURNE LEVEL OF HAZARDOUS INGREDIENTS IN EX  
CESS OF TLV  
USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.  
Ventilation:GENERAL TO MAINTAIN VAPORS BELOW PEL.  
Protective Gloves:NITRILE, BUTYL, NATURAL RUBBER  
Eye Protection:CHEMICAL GOGGLES OR FULL FACE SHIELD  
Other Protective Equipment:GLOVES NOT ADEQUATE PROTECTION FROM  
IMMERSION. PROTECT SKIN W/NITRILE/BUTYL, RUBBER OR POLYETHYLENE  
APRON OR COVERALLS.  
Work Hygienic Practices:AVOID ALL SKIN CONTACT. WASH THOROUGHLY AFTER  
HANDLING/BEFORE SMOKING OR EATING.  
Supplemental

Safety and Health  
NK

===== Physical/Chemical Properties =====

Vapor Density:>AIR  
Spec Gravity:1.3  
pH:NA  
Viscosity:10-30@20RPM  
Evaporation Rate & Reference:SLOWER THAN BUAC  
Solubility in Water:SLIGHT  
Appearance and Odor:BROWN - ORANGE LIQUID  
Percent Volatiles by Volume:84.9  
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
EASILY OXIDIZABLE MATERIALS.  
Hazardous Decomposition Product  
s:OXIDES OF CARBON & NITROGEN, CHROMIUM  
COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:EPA #D007 HAZ WASTE. DISPOSE IN COMPLIANCE  
W/FEDERAL & STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate  
and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.