View NSN Online: https://aerobasegroup.ae/nsn/6850-01-387-5770

EASTMAN KODAK COMPANY -- 131 8062 COLOREDGE CYAN TONER -- 6850-01-387-5770

Product ID:131 8062 COLOREDGE CYAN TONER MSDS Date:01/22/1997 FSC:6850 NIIN:01-387-5770 MSDS Number: CDKRN === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-477-3194 MSDS :800- 242-2424 Emer gency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

Ingred

Name:POLYESTER POLYMER Fraction by Wt: 95-99% Other REC Limits:NONE RECOMMENDED

Ingred Name:PHTHALOCYANINE DYE () Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYMERS Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:NOT GIVEN Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EXPECTED TO B E A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY CAUSE TRANSIENT EYE IRRITATION. LOW SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW INGESTION HAZARD. Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure: EYE IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

======= First Aid Measures

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Flash Poin

t:COMBUSTIBLESOLID Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL Fire Fighting Procedures: USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. Unusual Fire/Explosion Hazard: POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURES. ELEVATED TEMPERATURES CAN CAUSE DECOMPOSITION. Spill Release Procedures: DO NOT USE A VACUUM CLEANER TO CLEAN UP SPILLS OF POW DERED TONERS. THE VERY FINE PARTICLES CAN CAUSE A FIRE OR EXPLOSION. AVOID GENERATION OF DUST. SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER CART ON. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: AVOID BREATHING DUST. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER CLOSED. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. MINIMIZE DUST GENERATION. Other Precautions: MINIMIZE DUST A CCUMULATION. REFER TO NFPA PAMPHLET NO. 654, "PREVENTION OF FIRE AND DUST EXPLOSIONS IN THECHEMICAL, DYE, PHARMACEUTICAL, AND PLASTICS INDUSTRIES." KEEP CONTAINER CLOSED. Respiratory Protection: NONE SHOULD BE NEEDED. Ventilation: GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS. Protective Gloves: IMPERVIOUS Eve Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE. Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.

HCC:N1 Boiling Pt:B.P. Text:NOT GIVEN Melt/Freeze Pt:M.P/F.P Text:NOT GIV EN Vapor Pres:NEGLIGIBLE Vapor Density:NEGLIGIBLE Spec Gravity:NOT GIVEN Evaporation Rate & amp; Reference:NOT GIVEN Solubility in Water:NEGLIGIBLE Appearance and Odor:CYAN SOLID POWDER, SLIGHT ODOR Percent Volatiles by Volume:NIL

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:AVOID TEMPERATURES ABOVE 482F. Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE

======

Waste Disposal Methods:CAN BE INCINERATED WHEN IN COMPLIANCE WITH LOCAL REGULATIONS. CONTRACT WITH A LICENSED CHEMICAL DISPOSAL AGENCY. DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoev er,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.