

SANDVIK STEEL CO -- SANDVIK -- 3439-00-460-7667

=====
Product Identification
=====

Product ID:SANDVIK
MSDS Date:04/01/1991
FSC:3439
NIIN:00-460-7667
MSDS Number: CDPXR
=== Responsible Party ===
Company Name:SANDVIK STEEL CO
Box:1220
City:SCRANTON
State:PA
ZIP:18501-1220
Country:US
Info Phone Num:717-587-5191
Emergency Phone Num:717-587-5191
CAGE:1BT93

==== Contractor Identification ===

Company Name
:SANDVIK STEEL CO.
Box:1220
City:SCRANTON
State:PA
ZIP:18501-1220
Country:US
Phone:717-587-5191
CAGE:1BT93

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE; (CACO*2)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: 1-10%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:CALCIUM FLUORIDE; (CAF*2)
CAS:7789-75-5
RTECS #:EW1760000
Fraction by Wt: 1-10%
OSHA PEL:2.5 MG/M3 (F) (MFR)
ACGIH TLV:2.5 MG/M3 (F) (MFR)

Ingred Name:CHROMIUM; (CR)

(SARA 313) (CERCLA)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 5-30%
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:COPPER; (CU) (SARA 313) (CERCLA)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0-4%
OSHA PEL:0.1MG/M3 FUME;1 DUST
ACGIH TLV:0.2 MG/M3 FUME
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:IRON; (FE)
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: BALANCE
OSHA PEL:10 MG/M3 (MFR)
ACGIH TLV:5 MG/M3 (MFR)

Ingred Name:MANGANESE; (MN) (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 1-10%
OSHA PEL:5 MG/M3 DUST, C
ACGIH TLV:5 MG/M3 DUST

Ingred Name:MOLYBDENUM; (MO)
CAS:7439-98-7
RTECS #:QA4680000
Fraction by Wt: 1-10%
OSHA PEL:10 PPM
ACGIH TLV:10 PPM

Ingred Name:NICKEL; (NI) (SARA 313) (CERCLA)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 1-35%
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3

Ingred Name:NIOBIUM; (NB) (ALSO CALLED COLUMBIUM)
CAS:7440-03-1
RTECS #:QT9900000
Fraction by Wt: 1-10%
OSHA PEL:N/K
ACGIH TLV:N/K

ingred Name:POTASSIUM; (POTASSIUM (K))

CAS:7440-09-7

RTECS #:TS6460000

Fraction by Wt: 1-10%

OSHA PEL:N/K

ACGIH TLV:N/K

ingred Name:SODIUM; (NA) (CERCLA)

CAS:7440-23-5

RTECS #:VY0686000

Fraction by Wt: 1-10%

OSHA PEL:N/K

ACGIH TLV:N/K

ingred Name:SILICON; (SI)

CAS:7440-21-3

RTECS #:VW0400000

Fraction by Wt: 1-10%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST

ingred Name:SODIUM FLUOALUMINATE; (SODIUM ALUMINUM FLUORIDE
(NA*3ALF*2))

CAS:15096-52-3

RTECS #:WA9625000

Fraction by Wt: 1-10

%

OSHA PEL:2.5 MG/M3 (F) (MFR)

ACGIH TLV:2.5 MG/M3 (F) (MFR)

ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE (TIO*2))

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 1-20%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST

ingred Name:SUPP DATA:GOGGLES, IF NECESSARY, TO SHIELD OTHERS.

RTECS #:9999999ZZ

ingred Name:OTHER PROT EQUIP:SPKS & ELEC SHOCK. SEE ANSI Z49.1. THIS
MAY INCL ARM PROTECTORS, APRONS, HATS, SHOULDER PROT & (ING 17)

RTECS #:9999999ZZ

ingred Name:ING 16:DARK SUBSTANTIAL CLOT

HING.
RTECS #:9999999ZZ

Ingred Name:HAZ DECOMP PROD:COATING, ETC, & FUMES & GASES (CARBON DIOXIDE, CARBON MONOXIDE, DINITROGEN TETROXIDE, HYDROGEN (ING 19)
RTECS #:9999999ZZ

Ingred Name:ING 18:FLUORIDE, NITRIC OXIDE, NITROGEN DIOXIDE, OZONE, PHOSGENE & PHOSPHINE). FOR MORE SPECIFIC INFO, CONT NEHC .
RTECS #:9999999ZZ

Ingred Name:EFTS OF OVEREXP:TO BE POTNTL CARCIN IN IARC MONOGRAPHS & LISTED BY OSHA/ACGIH AS POTNTL CARCIN (MFR).
RTECS #:9999999ZZ

=====
entification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:WELDING CONSUMABLES APPLIC TO THIS MSDS AS SHIPPED ARE NON REACTIVE, NON FLAMM, NON EXPLO & ESSNTLY NON HAZ UNTIL WELDED. ELEC ARC WELDING MAY CREATE ONE/MORE OF FOLLOWING HLTH HAZS: FUMES & GASES CAN BE DANGEROUS TO YOUR HLTH. ACUTE:OVEREXP TO WELDIN

G FUMES MAY RSLT IN DISCOMFORT SUCH AS DIZZ, NAUS OR(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NICKEL:IARC MONOGRAPHS ON EVAL OF CARCIN RISK OF CHEMS TO MAN, VOL 49, PG 257, 1990:GRP 2B. NTP 7TH ANNUAL RPT (SUPDAT)

Effects of Overexposure:HLTH HAZ:DRYNESS/IRRIT OF NOSE, THROAT/EYES. CHRONIC:OVEREXP TO WELDING FUMES CAN LEAD TO SIDEROSIS (IRON PRODS IN LUNGS), CNS DMG, SENSIT DERM & BELIEVED BY SOME INVESTIGATORS TO AFFECT PULM FUNC. AR C RAYS CAN INJURE EYES & BURN SKIN. ELEC SHOCK CAN KILL. CHROMIUM IS LISTED IN NTP ANNUAL RPT ON CARCINS & FOUND(ING 20)

Medical Cond Aggravated by Exposure:AGGRAVATION OF RESPIRATORY OR ALLERGIC CONDITIONS MAY AFFECT SOME EXPOSED INDIVIDUALS.

=====
First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE & CALL FOR MEDICAL AID. EMPLOY FIRST AID TECHNIQUE RECOMMENDED BY THE AMERICAN RED CROSS. INGEST:CALL MD IMMEDIATELY . INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING

(GIVE

O*2 /ARTF RESP) . EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD .

=====
Fire Fighting Measures
=====

Flash Point:NONFLAMMABLE

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE .

Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:WELDING ARC & SPARKS CAN IGNITE COMBUSTIBLES & FLA

MMABLES. REFER TO ANSI Z49.1 FOR FIRE PREVENTION DURING USE OF WELDING & ALLIED PROCEDURES.

=====
Accidental Release Measures
=====

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:TRAIN EACH WELDER TO KEEP HIS/HER HEAD OUT OF FUMES. TRAIN EACH WELDER NOT TO TOUCH LIVE ELEC PARTS & TO INSULATE HIS/PER PERSON FROM WORK & GROUND.

Other Precautions:READ

& UNDERSTAND MFR'S INSTRUCTIONS & PRECAUTIONARY

LBL ON PROD. SEE ANSI Z49.1, SAFETY IN WELDING & CUTTING, PUBLISHED BY AWS, P.O. BOX 351040, MIAMI, FL 33195 & OSHA PUBLICATION 2206 (29 CFR 1910), U.S. GOVT PRINTING OFFICE, (SUPP DATA)

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH APPROVED RESPIRABLE FUME RESPIRATOR OR AIR-SUPPLIED RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV/PEL.

Ventilation:USE ENOUGH VENT, LOCAL EXHST AT THE ARC, OR BOTH, TO KEEP FUMES & GASES BELOW TLV/PEL IN WORKER'S BRTHG ZONE & GEN AREA.

Protective Gloves:WELDER'S GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS &(SUPDAT)

Other Protective Equipment:ANSI APPRVD EYE WASH FOUNTAIN & DELUGE SHOWER. WEAR HEAD, HAND & BODY PROT TO HELP PVNT INJURY FROM RADIA,(ING 16)

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

EXPLAN

OF CARCIN:ON CARCINS, 1994:ANTIC TO BE CARCIN. ANIMAL:LUNGS,
NASAL CAVITIES. OTHER PREC:WASHINGTON, D.C. 20402, FOR MORE
DETAILS. EYE PROT:FULL LGTH FCSHLD . WEAR HELMET/USE FCSLD W/FILTE
R LENS. LENS FILTER SHOULD BE AS DARK AS POSS W/OUT OBSTRUCTING
VIEW OF WELD ZONE. PROVIDE PROT SCREENS & FLASH (ING 15)

===== Physical/Chemical Properties =====

HCC:T6

Appearance and Odor:SOLID CORE AND A FLUX COATING.

===== Stability and Reactivity

Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:WELDING FUMES & GASES CANNOT BE
CLASSIFIED SIMPLY. DECOMP PRODS INCL OXIDATION OF INGS FROM BASE
METAL & (ING 18)

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE,
DISPOSABLE CONTAINER OR
LINER IN AN ENVIRONMENTALLY ACCEPTED MANNER, IN FULL COMPLIANCE
W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should see

k competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.