

EASTMAN KODAK COMPANY -- 180 5134 RP X-OMAT FIXER & REPLENISHER, PART A --
6525-01-076-8677

===== Product Identification =====

Product ID:180 5134 RP X-OMAT FIXER & REPLENISHER, PART A

MSDS Date:08/02/1995

FSC:6525

NIIN:01-076-8677

MSDS Number: CDQMW

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716

-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on

Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 40-45%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE
CAS:7783-18-8
RTECS #:XN6465000
Fraction by Wt: 35-40%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM THIOSULFATE
CAS:7772-98-7
RTECS #:XN6476000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM BISULFITE (CERCLA)
CAS:10192-30-0
RTECS #:WT3595000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM ACETATE (CERCLA)
CAS:631-61-8
RTECS #:AF3675000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA)
CAS:7631-90-5
RTECS #:VZ2000000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL:EXPECTED TO BE A LOW HAZARD FOR
RECOMMENDED HANDLING. EYES:NO SPECIFIC HAZARD KNOWN.MAY CAUSE
TRANSIENT IRRITATION. SKIN:LOW HAZARD FOR RECOMMENDED HANDLING.
INGEST:EXPECTED TO BE LOW INGESTION HAZRD.
Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY
CLASSIFICATION:IARC/A
CGIH/NTP/OSHA:NONE.
Effects of Overexposure:TRANSIENT EYE IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHAL:IF SYMPTOMATIC MOVE TO FRESH AIR. GET MED ATTN IF
SYMPTONS PERSIST. EYES:ANY MATL THAT CONTACTS EYE SHOULD BE WASHED
OUT IMMED W/WATER. GET MED ATTN IF SYMPTOMS OCCUR. SKIN:WASH W/SOAP
& WATER. GET MED ATTN IF SYMPTOMS OCCUR. INGEST:DRINK 1-2 GLASSES
OF WATE
R. SEEK MED ATTN.

===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:NP
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL,
ALCOHOL FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS
DECOMPOSITION PRODUCTS.
Unusual Fire/Explosion Hazard:DRIED PRODUCT RESIDUE CAN ACT AS A
REDUCING AGENT.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER W/LG AMTS OF WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE W/ADEQUATE VENTI.KEEP FROM CONTACT
W/OXIDIZING MATLS.KEEP CNTNR TIGHTLY CLOSED.KEEP AWAY FROM
INCOMPATIBLE SUBSTANCES.
Other Precautions:PROPERTIES:MOD BIOCHEM OXY DEMAND,MAY CAUSE OXY
DEPLETION IN AQU SYS.LOW POT

TO AFFECT AQU ORGANISMS/2ND WASTE
TREATMENT MICROBIAL METABOLISM/GERM &/OR EARLY GROWTH OF SOME
PLANTS/PERSIST IN ENVIRO/BI OCONCEN.AFT DILUTION W/LG AMTS OF
(SUPP)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.
Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR)
SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS
Protective Gloves:IMPERVIOUS GLOVES.
Eye Protection:SAFETY GLASSES W/
SIDE SHIELDS, GOGGLES.
Other Protective Equipment:EYEBATH, WASHING FACILITIES, SAFETY SHOWER.
Work Hygienic Practices:WASH THOROUGHLY AFT HNDLG.GOOD INDUSTRIAL HYG
PRAC TO MIN EYE/SKIN CONTACT.
Supplemental Safety and Health
OTHER PRECAUT:WATER/2ND WASTE TREAT MATL NOT EXPECTED TO CAUSE ADVERSE
ENVIRO EFFECTS. TO MAKE 200 GALLONS.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:>212F,>100C
Melt/Freeze Pt:M.P/F.P Text:NP
Decomp Temp:Decom
p Text:NP
Vapor Pres:18 @20C
Vapor Density:0.6
Spec Gravity:1.361
pH:4.1
Viscosity:NP
Evaporation Rate & Reference:NP
Solubility in Water:COMPLETE.
Appearance and Odor:LIQUID, COLORLESS, SLIGHT AMMONIA ODOR.
Percent Volatiles by Volume:45
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, BAES, SODIUM HYPOCHLORITE
(BLEACH).CONTACT W/BASE LIBERATES FLAMMABLE MATL.
Stabili

ty Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:AMMONIA, CHLORAMINE. HAZ COMBUST
PROD:CO2,CO,OXIDES OF NITROGEN,OXIDES OF SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO
NATIONAL/STATE/LOCAL LAWS. FLUSH TO SEWER W/LG AMTS OF WATER.
CHEM(S) SUBJ TO REPORTING REQMTS OF SEC 313 TITLE III
SARA/40CFR372:NONE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.