

NK -- UNI-WELD PVC CEMENT -- 5610-00-236-4946

===== Product Identification =====

Product ID:UNI-WELD PVC CEMENT

MSDS Date:04/15/1989

FSC:5610

NIIN:00-236-4946

MSDS Number: CDVGS

=== Responsible Party ===

Country:US

CAGE:KO756

=== Contractor Identification ===

Country:US

CAGE:KO756

Company Name:UNITED PAINT

Address:404 EAST MALLORY

Box:9037

City:MEMPHIS

State:TN

ZIP:38109

Country:US

Phone:901-775-1

315

CAGE:UNITE

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)

CAS:78-93-3

RTECS #:EL6475000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TETRA HYDROFURAN (THF)

CAS:109-99-9

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANONE (CERCLA)

CAS:10

8-94-1  
RTECS #:GW1050000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM  
ACGIH TLV:50 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: ANESTHETIC, RESPIRATORY TRACT  
IRRIT, SERIOUS NS DEPRESSION, DAMAGE TO KIDNEYS, BLOOD, NERVES,  
LIVER, LUNGS. SKIN: ABSORPTION, IRRIT. EYE:  
IRRITATION. INGEST:  
POISON.

===== First Aid Measures =====

First Aid:WASH W/PLENTY OF WATER. EYE: FLUSH W/PLENTY OF WATER FOR 15  
MINUTES, GET MED AID. INHAL: REMOVE TO FRESH AIR. INGEST: CALL DR  
IMMED. DO NOT INDUCE VOMIT, NEVER GIVE ANYTHING BY MOUTH TO  
UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:TOC  
Flash Point:4F,-16C  
Lower Limits:1.1  
Upper Limits:11.8  
Extinguishing Media  
a:NFPA CLASS B EXTINGUISHERS (CO2 FOAM) FOR CLASS 1 B  
LIQUID FIRES.  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE ON FIRE BUT CAN  
PROTECT FIREFIGHTERS & COOL CONTAINERS. USE FOG NOZZLES IF WATER  
USED & AIR SUPPLIED BREATHING MASKS.  
Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE, MAY EXPLODE  
W/EXTREME HEAT, APPLYING TO HOT SURFACES REQUIRES SPECIAL  
PRECAUTIONS.

===== Accidental Release Measures =====

Spill Release Procedures:ISOLATE F

ROM OXIDIZERS, HEAT/SPARKS/ELECTRICAL  
EQUIPMENT/OPEN FLAME.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA, OBSERVE LABEL  
CAUTIONS & INSTRUCTIONS. VAPORS TRAVEL LONG DISTANCES. PREVENT  
VAPOR BUILDUP, NO IGNITS, DONT STORE >120F, \*

Other Precautions:NK \* STORE LG AMOUNT IN STRUCTURES MADE FOR OSHA  
CLASS 1 B LIQ, AVOID FREEFALL OF LIQ, GROUND CONTNR WHEN POURING,  
DONT FLAMECUT, SAW, BRASE, WELD. E  
MPTY CONTNR HAZARDOUS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SUITABLE FOR USE W/ORGANIC SOLVENTS.  
Ventilation:LOCAL EXHAUST PREFERABLE, MECHANICAL/GENERAL ACCEPTABLE.  
Protective Gloves:SOLVENT RESISTANT. RECOMMENDED.  
Eye Protection:GOGGLES.  
Other Protective Equipment:NONE  
Work Hygienic Practices:USE W/ADEQUATE VENT, OBSERVE ALL LABEL  
CAUTIONS.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====  
=====

Boiling Pt:B.P. Text:155F,68C  
Melt/Freeze Pt:M.P/F.P Text:NA  
Vapor Pres:45  
Vapor Density:3.2  
Spec Gravity:.8  
Evaporation Rate & Reference:5.5+-1 (BUAC)  
Solubility in Water:APPRECIABLE  
Appearance and Odor:VISCUS LIQUID W/KETONE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS.  
Stability Condition to Avoid:ISOLATE FROM IGNIT SOURCES,  
HEAT/SPARKS/OPEN FLAME.  
Hazardous Decomposition Products:CARBO

N MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE/INCINERATE OBSERVING LOCAL/STATE/FEDERAL  
HEALTH SAFETY & POLUTION LAWS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its  
use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.