

EVERSEAL MFG CO -- GRAY WALKWAY COMPOUND, ROUGH -- 5610-00-641-0426

===== Product Identification =====

Product ID:GRAY WALKWAY COMPOUND, ROUGH

MSDS Date:04/20/1987

FSC:5610

NIIN:00-641-0426

MSDS Number: CDVLV

=== Responsible Party ===

Company Name:EVERSEAL MFG CO

Address:475 BROAD AVENUE

City:RIDGFIELD

State:NJ

ZIP:07657

Info Phone Num:(201) 943-4986

Emergency Phone Num:(201) 943-4986

CAGE:72988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN

Fraction by Wt: 19.0%

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 12.0%

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:MAGNESIUM SILICATE

CAS:1480-96-6

Fraction by Wt: 24.0%

Other REC Limits:2 MG/M3

Ingred Name:PUMICE
Fraction by Wt: 8.0%

Ingred Name:ALIPHATIC NAPHTHA, V.M. & P. NAPHTHA, LACOLENE (VP = 30)
ORAL LD50 5 G/KG
CAS:64742-89-8
Fraction by Wt: 29.0%
Other REC Limits:150 PPM

Ingred Name:SILICONE DIOXIDE
CAS:68855-54-9
Fraction by Wt: 6.0%
Other REC Limits:0.08 MG/M3

=====
Hazards Identification
=====

LD50 LC50 Mixture:150 PPM
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health
h Hazards Acute and Chronic:INHALATION: DIZZINESS, NAUSEA,
UNCONSCIOUSNESS. EYE/SKIN: IRRITATION. MAY CAUSE LUNG DISORDERS.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION.
SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER. CONSULT PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:55.0F,12.8C
Lower Limits:1.0%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
WATER NOT A SUITABLE
EXTINGUISHING MEDIUM.
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTAINED
BREATHING APPARATUS.

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB SMALL SPILLS ON DRY ABSORBENT. USE
SPARK-PROOF SCOOP FOR LARGE SPILLS. ENSURE ADEQUATE VENTILATION.
REMOVE OPEN IGNITION SOURCES.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID OPEN FLAMES, H

EAT, SOURCES OF
IGNITION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:VAPOR CARTRIDGE MASK OR AIR-SUPPLIED HOOD.
Ventilation:SUFFICIENT TO KEEP AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:53.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:NA
Hazardous Decomposition Products:CO, CO2

=====

===== Disposal Considerations =====

Waste Disposal Methods:AS PER LOCAL & FEDERAL REGULATIONS FOR HAZARDOUS
WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.