View NSN Online: https://aerobasegroup.ae/nsn/8010-01-426-5513

Product ID:BROWN 383 POLYEURETHANE COATING #0-7106TWU MSDS Date:09/23/1996 FSC:8010 NIIN:01-426-5513 Kit Part:Y MSDS Number: CDWBD === Responsible Party === Company Name: HENTZEN COATINGS, INC Address:6937 WEST MILL ROAD City:MILWAUKEE State:WI ZIP:53218 Country:US Info Phone N um:414-353-4200 Emergency Phone Num:414-353-4200/CHEMTREC 800-424-9300 Preparer's Name: JANE FREEMAN CAGE:09225 === Contractor Identification === **Company Name: HENTZEN COATINGS INC** 

Box:18749 City:MILWAUKEE State:WI ZIP:53218 Country:US Phone:414-353-4200

CAGE:09225

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 30-40% Other REC Limits:NONE RECOMMENDED

Ingred Name: BLACK IRON OXIDE

Address:6937 WEST MILL ROAD

PIGMENT CAS:1317-61-9 Fraction by Wt: 1-5.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3

Ingred Name:CHROMIUM OXIDE (SARA 313) CAS:1308-38-9 RTECS #:GB6475000 Fraction by Wt: 10.531% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG/M3

Ingred Name:RED IRON OXIDE PIGMENT CAS:1309-37-1 RTECS #:NO7400000 Fraction by Wt: 0-5.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:5MG/M3 ACGIH TLV:5 MG/M3

Ingred Name:SILICA CAS:14808-60-7 RTECS #:VV7330000 Fracti on by Wt: 15-20% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3 RDUST

Ingred Name:TALC (CONTAINING ASBESTOS) CAS:14807-96-6 RTECS #:MW2700000 Fraction by Wt: 5-10.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:2.0MG/M3 FIBERS/CC ACGIH TLV:2.0 MG/M3 FIBER/CC

Ingred Name:SILICA CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 1-5.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:20 MPPCF ACGIH TLV:10 MG/M3 TDUST

Ingred Name:1-METHYLPYRROLIDONE CAS:872-50-4 RTECS #:UY579000 0 Fraction by Wt: 4.632% Other REC Limits:200 PPM MFR

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:CHRONIC: INHAL: HEADACHE, NAUSEA, IRRIT TO RESPIRATORY PASSAGES. SKIN: IRRITATION, DEFATTING, DERMATITIS. EYE: IRRITATION., OTHER: BRAIN/NS/LIVER/KIDNEY DAMAGE, DELAYED RESPIRATORY SYSTEM EFFECTS, LUN G INJURY. Explana tion of Carcinogenicity:SILICA IS LISTED AS A PROBABLE HUMAN CARCINOGEN. Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY AILMENTS; CHEMICAL SENSITIZATION.

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. NOTIFY A PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. LIFT LIDS. TAKE TO PHYSICIAN FOR MEDICAL TREATMENT. SK
IN: WASH WITHSOAP & WATER. REMOVE CONTAM CLOTHES, WASH BEFORE REUSE, CALL DR. INGEST: CALL

DR/POISON CONTROL CENTER IMMED.

Flash Point Method:TCC Flash Point:>201F,>94C Autoignition Temp:Autoignition Temp Text:NA Lower Limits:NA1.0 Upper Limits:NA11.2 Extinguishing Media:ALCOHOL FOAM, WATER FOG, CARBON DIOXIDE Fire Fighting Procedures:WEAR PROTECT EQUIP INCLUDING SCBA. WATER MAY BE INEFFECTIVE, USE WATER (FOG NOZZ LES PREFERRED) COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP,AUTOIGNITN,EXPLOSION. Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. NO IGNITS CONTAINER MAY EXPLODE W.HEAT DONT WELD/TORCH ON/NEAR CONTAINER.

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. USE APPROPRIATE PROTECTIVE EQUIPMENT. AVIOD BREATHING VAPORS/SKIN CONTACT. PREVENT ENTRY TO DRAINS/SEWERS/WATERWAYS. NOTI FY AUTHORITIES. CONTAIN & REMOV E WITH INERT ABSORBENT AND NONSPARKING TOOLS.

Handling and Storage Precautions: DONT STORE @>120F. LARGE AMTS IN BUILDINGS COMPLYING W/(OSHA 1910.106). NO IGNITS. KEEP CLOSED/UPRIGHT/TIGHT WHEN NOT IN USE. EMPTY CNTNR HAZARDOUS. Other Precautions: SOAK SOILED RAGS/WASTES IN H2O FILLED CLOSED CNTNR. USE W/ADEQUATE VENT, AVOID VAPOR BREATHING/SKIN CONTACT, GROUND/BOND WHEN TRANSF ERRING, AVOID FREEFALL OF LIQ >FEW INCHES, USE SPARKPROOF TOOLS/EXPL OSION PROOF EQUIPMENT. Respiratory Protection: OUTDOOR/SANDING/GRINDING: NIOSH MECHANICAL FILTER RESPRTR. CONFINED AREA: NIOSH AIR SUPPLIED RESPIRATOR/HOOD. AIR MONITORING MAY BE REQUIRED. Ventilation: GENERAL DILUTION/LOCAL EXHAUST TO KEEP BELOW PEL/TLV. Protective Gloves: CHENICAL RESISTANT Eye Protection: SAFETY EYEWEAR W/SPLASH GUARDS/SIDE SHLD Ot her Protective Equipment: APPROPRIATE TO PREVENT PROLONGED SKIN CONTACT. Work Hygienic Practices: WASH HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED SMOKING AREAS ONLY. Supplemental Safety and Health MORE INFORMATION ON FILE. 

Boiling Pt:B.P. Text:209 TO 400F Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C Vapor Pres:20 @ 68F Vapor Density:> AIR Spec Gravity:1.41 pH:NA VOC Grams/Liter:1.29 Evaporation Rate & amp; Reference:S

LOWER THAN BUTYL ACETATE
Solubility in Water: APPRECIABLE
Appearance and Odor:OPAQUE LIQUID, MILD ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION AS IN WELDING. MAY CONTAIN CARBON MONOXIDE & CARBON DIOXIDE.

Waste Disposal Methods:RECYCLE OR INCIN ERATE IN ACCORDANCE WITH LOCAL, STATE, & FEDERAL REGULATIONS.

\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all

liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.