

FEL-PRO INC DIV OF FELT PRODUCTS MFG CO -- CLOVER SILICON CARBIDE GREASE MIX,
LAPPING COMPOUND. -- 5350-00-193-1340

=====
Product Identification
=====

Product ID:CLOVER SILICON CARBIDE GREASE MIX, LAPPING COMPOUND.

MSDS Date:10/14/1986

FSC:5350

NIIN:00-193-1340

MSDS Number: CDXQP

==== Responsible Party ====

Company Name:FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

Address:7450 N MCCORMICK

City:SKOKIE

Sta

te:IL

ZIP:60076-4046

Country:US

Info Phone Num:708-674-7700

Emergency Phone Num:708-674-7700

Preparer's Name:DIANNE GALLAGHER

CAGE:73165

==== Contractor Identification ====

Company Name:FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

Address:7450 N MCCORMICK

Box:1103

City:SKOKIE

State:IL

ZIP:60076-4046

Country:US

Phone:847-674-7700 OR 312-761-4500

CAGE:73165

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Other REC Limits:NONE RECOMMENDED

OSHA P

EL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:POSSIBLE MECHANICAL IRRITATION IF
INTRODUCED INTO EYE DUE TO ABRASIVE GRIT PRESENT.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH W/TEPID WATER FOR 15 MINUTES, HOLD EYELIDS APART.
DO NOT RUB EYES,

GET MED AID.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>300F,>149C

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:CO2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. USE EYE PROTECTION & SCBA WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:NONE EXCEPT AS FOR PETROLEUM GREASE FIRES.

===== Accidental Release Measures =====

Spill Release Procedures

:SCOOP UP. WIPE UP W/RAGS OR USE ABSORBENT

MATERIAL. COMPLETE CLEANUP W/DETERGENT & WATER, HIGH FLASH POINT SOLVENT OR CHLORINATED SOLVENT CLEANER W/ADEQUATE VENT.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL STORAGE & HANDLING FOR PETROLEUM GREASE PRODUCTS.

Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.

Ventila

tion:LOCAL EXHAUST ACCEPTABLE. MECHANICAL, (GENERAL) ACCEPTABLE.

Protective Gloves:NONE REQUIRED.

Eye Protection:YES

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:NO SPECIAL WORK OR HYGENIC PRACTICE REQUIRED.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:NEGLIGIBLE

Vapor Density:NA

Spec Gravity:1.15

Evaporation Rate & Reference:NA

Solubilit

y in Water:INSOLUBLE.

Appearance and Odor:GRAY PASTE, SLIGHT PETROLATUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:PYROLISIS YIELDS CO, CO2, &
INCOMPLETELY BURNED HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED INCINERATION OR BURY IN POSTED
LANDFILL IN
ACCORDANCE W/FEDERAL/STATE/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability o
f this information to their
particular situation.