

RACAL COMMUNICATIONS INC -- 3100424-501;B4044015(WAS84009009) NICAD
BATT,RECHARGEABLE -- 6140-01-251-8652

===== Product Identification =====

Product ID:3100424-501;B4044015(WAS84009009) NICAD BATT,RECHARGEABLE

MSDS Date:10/06/1996

FSC:6140

NIIN:01-251-8652

MSDS Number: CFLFJ

=== Responsible Party ===

Company Name:RACAL COMMUNICATIONS INC

Address:5 RESEARCH PL

City:ROCKVILLE

State:MD

ZIP:20850-3213

Country:US

Info Phone Num:301-948-4420

Emergency Phone Num:301-948-4420

CAGE:23386

=== Contractor Identification ===

Company Name:RACAL COMMUNICATIONS INC

Address:5 RESEARCH PL

Box:City:ROCKVILLE

State:MD

ZIP:20850-3213

Country:US

Phone:301-948-4420

CAGE:23386

===== Composition/Information on Ingredients =====

Ingred Name:NICKEL (SARA 313) (CERCLA) (20-30% AS NI) INCLUDES INGRED
2.

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 20-30%

Other REC Limits:NONE RECOMMENDED

O

SHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9596

Ingred Name:NICKEL HYDROXIDE (SARA 313) (CERCLA)
CAS:12054-48-7
RTECS #:QR7040000
Fraction by Wt: SEE #1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG(NI)/M3
ACGIH TLV:0.1 MG(NI)/M3; 9596
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM (SARA 313) (CERCLA) (13-15% AS CA) INCLUDES INGRED
4.
CAS:7440-43-9
RTECS #:EU9800000
Fraction by Wt: 13-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 MG/M3 DUST; Z-2
ACGIH TLV:0.01 MG/M3 DUST;9596
EP
A Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM HYDROXIDE
CAS:21041-95-2
Fraction by Wt: SEE #3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG CD/M3
ACGIH TLV:0.05 MG CD/M3

Ingred Name:COBALT (SARA 313) (1-2% AS CO) INCLUDE INGRED 6.
CAS:7440-48-4
RTECS #:GF8750000
Fraction by Wt: 1-2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.02 MG/M3; A3; 9596

Ingred Name:COBALT HYDROXIDE
CAS:1307-86-4
RTECS #:GG0904000
Fraction by Wt: SEE #5%
Other REC Limits:NONE RECOMM

ENDED
OSHA PEL:0.05 MG/M3(COBALT)
ACGIH TLV:0.1 MG/M3

Ingrid Name:POTASSIUM HYDROXIDE (CERCLA) (2-4% AS DRY KOH)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 2-4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO
IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ELECTROLYTE (KOH)IS CAUSTIC, CONTACT
W/SKIN OR EYES MAY CAUSE IRRIT.
Explanation of Carcinogenicity:PER
MSDS:CARCINOGENICITY:NTP/IARC/OSHA:NO.

===== First Aid Measures =====

First Aid:IF LIQUID FROM LEAKER COMES IN CONTACT W/SKIN, REMOVE IMMED
W/WATER.FOR EYE CONTACT FLUSH W/RUNNING WATER FOR @LEAST 15MINS AND
CONTACT PHYSICIAN.

===== Fire Fighting Measures =====
=====

Flash Point:NA
Autoignition Temp:Autoignition Temp Text:NA
Lower Limits:NA
Upper Limits:NA
Unusual Fire/Explosion Hazard:MAY BURST WHEN SUBJ TO EXTREME
HEAT.CADMIUM FUMES MAY BE RELEASE DURING BURNING.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID SKIN AND EYE CONTACT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT EL

ELECTRICALLY SHORT CIRCUIT, USE
PROPER BATTERY CHARGER.
Other Precautions:AVOID INCINERATION OR MUTILATION.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:NA

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NA

Solubility in Water:NA

Appearance and Odor:5 CYLINDRICAL NICAD BATT CELLS INSIDE

CASE,7.6"LX1.0"DIA,MAX WT=5LBS.

Percent Volatiles by Volume:NP

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH LCO STATE AND FEDERAL
REGULATIONS, USUALLY MAY BE DISPOSED OF IN SECURE
D LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular

cular situation.