

MOBIL OIL CORP -- SHC 626 -- 9150-00-001-9395

===== Product Identification =====

Product ID:SHC 626

MSDS Date:01/01/1995

FSC:9150

NIIN:00-001-9395

MSDS Number: CFMPB

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-737-4411/800-424-9300(CHEMTREC)

CA

GE:3U728

=== Contractor Identification ===

Company Name:HOC INDUSTRIES, INC

Address:3511 N. OHIO

Box:2609

City:WICHITA

State:KS

ZIP:67219

Country:US

Phone:316-838-4663

CAGE:0A9L8

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

Other R

EC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS >2,000 MG/KG.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:NONE. ACUTE- PRACTICALLY
NON-IRRITATING TO EYES AND SKIN. INHALATION IS UNLIKELY. HARMFUL
CONCENTRATIONS OF MISTS AND/OR VAPORS ARE UNLIKELY TO BE
ENCOUNTERED THROUGH ANY CUSTOMARY OR R
EASONABLY FORESEEABLE, USE,
OR MISUSE OFTHIS PRODUCT. PRACTICALLY NON-TOXIC BY INGESTION.
CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:NONE
Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:NOT EXPECTED TO
BE A PROBLEM. EYES:FLUSH WITH PLENTY OF WATER, HOLDING EYELIDS
OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:NOT EXPECTED TO BE A

PROBLEM. HOWEVE R, IF MORE THAN 1/2 LITER (PINT) INGESTED &
CONSCIOUS, IMMEDIATELY DRINK 1-2 GLASSES OF WATER & CALL PHYSICIAN.
DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS
PERSO

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:COC
Flash Point:>455F,>235C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, DRY CHEMICAL OR
FOAM. WATER OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE E
QUIPMENT AND
NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE
EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. PROVIDE ADEQUATE
VENTILATION. REMOVE SPILL WITH INERT ABORBENT SUCH AS SAND, CLAY,
EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF
TO ENTER SEWERS OR WATE RWAYS. REPORT SPILLS AS REQUIRED TO

AUTHORITIES.

Neutralizing Agent:NOT RELEVANT

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM HIGH HEAT & STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDRY BEFORE RE-USE.

=
=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY NEEDED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED ORGANIC VAPOR AND MI ST RESPIRATOR (REFER TO 29 CFR 1910.134)

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILE/NEOPRENE FOR REPEATED C ONTACT

Eye Protection:SAFETY GLASSES, FACE SHIELD RECOMMENDED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>600F,>316C

Melt/Freeze Pt:M.P/F.P Text:-50F,-46C

Vapor Pres:

2

Spec Gravity:0.85

Viscosity:>61.2CST@104F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:STRAW LIQUID - MILD ODOR

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXTREME HEAT

Hazardous Decomposition Products:MAY PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, ELEMENTAL OXIDES, METAL OXIDES.

=====
Disposal Considerations
=====

Waste Disp

osal Methods:DISPOSE OF WASTE IN COMPLIANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS. RCRA EMERGENCY NUMBER: 800-424-9346. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.