

I T W DEVCON INDUSTRIAL CORP -- 5 MINUTE EPOXY HARDENER PART NO. 14210 --
8040-00-264-6816

===== Product Identification =====

Product ID:5 MINUTE EPOXY HARDENER PART NO. 14210

MSDS Date:02/19/1996

FSC:8040

NIIN:00-264-6816

MSDS Number: CFMYW

=== Responsible Party ===

Company Name:I T W DEVCON INDUSTRIAL CORP

Address:30 ENDICOTT ST

City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Info Phone Num:508

-777-1100

Emergency Phone Num:508-777-1100

CAGE:JO305

=== Contractor Identification ===

Company Name:DEVCON CORP

Address:30 ENDICOTT ST

Box:City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Phone:1-508-777-1100

CAGE:16059

Company Name:I T W DEVCON INDUSTRIAL CORP

Address:30 ENDICOTT ST

Box:City:DANVERS

State:MA

ZIP:01923

Country:US

Phone:508-777-1100

CAGE:JO305

===== Composition/Information on Ingredients =====

Ingred Name:2,4,6-TRIS(DIMETHYLAMINO METHYL) PHENOL (ORAL LD50 1200

MG/KG RAT, DERMAL 1350 MG/KG RABBIT, INHAL LC50 >0.5 MG/L/RAT).

CAS:90-72-2

RTECS #:SN3500000

Fraction by Wt: 10-20%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MERCAPTAIN AMINE BLEND

Fraction by Wt: 80-90%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION, SENSITIZATION. EYES

:

IRRITATION, PERMANENT DAMAGE, BLINDNESS. INHAL: IRRITATION, DELAYED LUNG INJURY, CHEMICAL PNEUMONIA. INGEST: FATIGUE, MUSCLE WEAKNESS, GI IRRITATION, NAUSEA, VOMIT, DIARRHEA.

Medical Cond Aggravated by Exposure:SKIN, EYE & LUNG DISORDERS.

=====
===== First Aid Measures =====
=====

First Aid:EYE: FLUSH W/CLEAN WATER FOR >15 MINUTES, LIFT LIDS. GET IMMED MED AID. SKIN: REMOVE CONTAM CLOTHES/SHOES. WASH THOROUGHLY W/SOAP & WARM WATER, CALL DR. INHA

L: REMOVE TO FRESH AIR. GIVE

OXYGEN IF BREATHING IS DIFFICULT, CALL DR. INGEST: DONT INDUCE VOMIT. GIVE LARGE AMOUNTS OF WATER FOLLOWED BY MILK IF AVAILABLE. CALL DR.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:PMCC

Flash Point:>200F,>93C

Lower Limits:NE

Upper Limits:NE

Extinguishing Media:WATER, CO2, DRY CHEMICAL & FOAM.

Fire Fighting Procedures:USE SCBA & PROTECTIVE CLOTHING IN CONFINED AREAS. COOL CONTAINERS W/WATER SPRAY.

Unusual

Fire/Explosion Hazard:TOXIC SMOKE & VAPORS MAY FORM DURING COMBUSTION.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITS. VENT AREA. DIKE. ABSORB. PUMP TO CONTAINER. FLUSH RESIDUE W/WATER.

===== Handling and Storage =====

Handling and Storage Precautions:LAUNDER CONTAM CLOTHES/GEAR BEFORE REUSE. DISCARD CONTAM LEATHER GOODS. HANDLE ACCORDING TO OF POTENTIAL HAZARD OF CURING AGENT.

Other Precautions:PROTECT AGAINST NUISANCE DUST DURING SANDING/GRINDING. STORE IN COOL, DRY AREA AWAY FROM IGNITS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR.
Ventilation:MECHANICAL (GENERAL): ADEQUATE. LOCAL EXHAUST: RECOMMENDED.
Protective Gloves:CHEMICAL RESISTANT, RUBBER.
Eye Protection:SAFETY GLASES W/SIDE SHIELD.
Other Protective Equipment:EMERGENCY SHOWER, EYEWASH STATION & CHEMICAL RESIS TANT GEAR.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NE
Melt/Freeze Pt:M.P/F.P Text:NE
Vapor Pres: