View NSN Online: https://aerobasegroup.com/nsn/8010-00-527-2050

Product ID:N5217 BLACK A/D ENAMEL. #17038 MSDS Date:10/22/1996 FSC:8010 NIIN:00-527-2050 MSDS Number: CFMZM === Responsible Party === Company Name: NILES CHEMICAL PAINT CO Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Info Phone Num:616-683-3377 **Emergency Phon** e Num:219-236-5856 Preparer's Name: MICHAEL LICHATOWICH CAGE:02388 === Contractor Identification === Company Name: NILES CHEMICAL PAINT Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Phone:616-683-3377/219-236-5856 CAGE:02388

Ingred Name:ALKYD RESIN SOLUTION CAS:66070-60-8 Fraction by Wt: 52.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:150PPM/STEL 150

Ingred Name:N-BUTYL ACETATE (CE

RCLA) (VP = 10 @ 20C) CAS:123-86-4 RTECS #:AF7350000 Fraction by Wt: 31.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:150 PPM ACGIH TLV:150 PPM/STEL 200 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ACRYLIC RESINS Fraction by Wt: 1.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SARA 313) (CERCLA) (VP = 7 @ 20C) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 1.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:100 PPM/STEL 150 EPA Rpt Qty:1000 LBS DOT Rpt Qty:10 00 LBS

Ingred Name:ORGANOLPHYLLIC CLAY CAS:1335-30-4 Fraction by Wt: AIR. Spec Gravity:1.056 pH:NA Viscosity:70-75 KU Evaporation Rate & amp; Reference:SLOWER THAN ETHER. Solubility in Water:YES Appearance and Odor:LIQUID, ODOR OF SOLVENTS. Percent Volatiles by Volume:42.44 Corrosion Rate:MINIMAL.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS, NITRATES, ALKALIS & ACIDS. Stability Condition to Avoid:HIGH TEMPERATU Waste Disposal Methods: ACCORDING TO FEDERAL, STATE, LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should s eek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.