

AIR LIQUIDE AMERICA CORPORATION -- NITROGEN -- 6830-01-347-3568

=====
Product Identification
=====

Product ID:NITROGEN
MSDS Date:08/24/1989
FSC:6830
NIIN:01-347-3568
MSDS Number: CFRJH
=== Responsible Party ===
Company Name:AIR LIQUIDE AMERICA CORPORATION
Box:3047
City:HOUSTON
State:TX
ZIP:77253
Country:US
Info Phone Num:713-868-0440/713-896-2140 MSDS
Emergency Phone Num:713-868-0302
CAGE:AIRLI

==
= Contractor Identification ===
Company Name:AIR LIQUIDE AMERICA CORPORATION
Address:2700 POST OAK DRIVE
Box:City:HOUSTON
State:TX
ZIP:77056-8229
Country:US
Phone:713-896-2896;800-231-1366
CAGE:17688
Company Name:AIR LIQUIDE AMERICA CORPORATION
Box:3047
City:HOUSTON
State:TX
ZIP:77253
Country:US
Phone:713-896-2140
CAGE:AIRLI

=====
Composition/Information on Ingredients
=====

Ingred Name:NITROGEN
CAS:7727-37-9
RTECS #:QW9700000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMM

ENDED
ACGIH TLV:ASPHYXIAN; 9596

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV NONE ESTABLISHED
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NITROGEN NON-TOXIC BUT MAY CAUSE
SUFFOCATION BY DISPLACING OXY IN AIR.EXPO TO OXYGEN-DEFICIENT
ATMOSPHERS MAY CAUSE DIZZ,NAU,VOMIT,DIMINISHED MENTAL
ALERTNESS,LOSS OF CONSCIOUSNESS,DEATH.IT SHOULD BE RECO
GNIZED THAT
COLLAPSE & ASPHYXIATIONMAY OCCUR W/OUT EXPERIENCING ANY OF ABOVE
SYMPTOMS.NITROGEN SIMPLE ASPHYXIAN.
Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NOT LISTED BY
IARC/NTP/OSHA.
Effects of Overexposure:NON-TOXIC, SUFFOCATION BY DISPLACING OXYGEN IN
AIR-DIZZINESS,NAUSEA,VOMTING,DIMISHED MENTAL ALERTNESS,LOSS OF
CONSCIOUSNESS,DEATH. COLLAPSE & ASPHYXIATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First A
id Measures
=====

First Aid:PERSONS SUFFERING FROM LACK OF OXYGEN SHOULD BE MOVED INTO
FRESH AIR.IF VICTIM IS NOT BREATHING ADMINISTER ARTIFICIAL
RESPIRATION.IF BREATHING IS DIFFICULT ADMINISTER OXYGEN.OBTAIN
PROMPT MED ATTN.SEL F-CONTAINED BREATHING APPARATUS MAY BE REQUIRED
FOR RESCUE WORKERS.

=====
Fire Fighting Measures
=====

Autoignition Temp:Autoignition Temp Text:NA
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:
MATL IS NON-FLAM.NITROGEN NEITHER BURNS NOR
SUPPORTS COMBUSTION.USE EXTINGUISHING MEDIA APPROPRIATE FOR
SURROUNDING FIRE
Fire Fighting Procedures:NONE.NITROGEN WILL ACT AS SIMPLE ASPHYXIAN IF
IT DISPLACES OXY.IF POSSIBLE REMOVE NITROGEN CYL FRM FIRE AREA OR
COOL W/WATER-AVOIDS EXCESSIVE PRESSURE(SUPPLEM)
Unusual Fire/Explosion Hazard:PRESSURE CAN BUILDUP DUE TO HEAT & CYL
MAY EXPLODE IF PRESSURE RELIEF DEVICES SHOULD FAIL TO RELIEVE
PRESSURE. ELECTRICAL CLASSIFICATION:NO

N-HAZARDOUS.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL UNNECESSARY PERSONS FROM AREA.SHUT OFF SOURCE IF POSSIBLE.VENTILATE ENCLSD AREA/REMOVE CYL TO OUTDOOR LOCATION TO PREVENT FORMATION OF OXY-DEFICIENT ATMS.IF LEAKING FRM CNTNR/VALVE CONTA CT CLOSEST BIG THREE INDUSTRIES LOCATION/SUPPLIER

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Hand
ling and Storage Precautions:STORE/USE W/ADEQU VENTI.CYL SHOULD BE STORED UPRIGHT W/VALVE PROTECTION CAP IN PLACE & FIRMLY SECURE TO PREVENT FALLING/BEING KNOCKED OVER.

Other Precautions:PROTECT CYL FRM PHYS DMG:DONT DRAG,ROLL,SLIDE,DROP.USE SUITABLE HAND TRUCK FOR CYL MOVEMENT.DONT ALLOW TEMP WHERE CYL STORED TO EXCEED 125F(52C).NEVER STRIKE WELD ARC ON ANY COMPRESSED GAS CYL.REFILL CYL W/O CONSENT OF CYL OWNER IS (SUPPLE)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS OR POSITIVE PRESSURE AIR LINE W/MASK IN OXYGEN-DEFICIENT ATMOSPHERES.RESPIRATORS WILL NOT FUNCTION.

Ventilation:ADEQUATE TO AVOID LOWERING OXYGEN CONTENT TO BELOW 19.5%(OXYGEN-DEFICIENT ATMOSPHERE).LOC EXHAU:YES.MECHANICAL:YES.

Eye Protection:SAF GLASSES RECOMMENDED

Other Protective Equipment:SAF SHOES WHEN HNDLG CYLINDERS.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety a
nd Health

FIREFIGHT:BUIULDUP.SELF-CONTAINED BREATHING APPARATUS MAY BE REQUIRED FOR RESCUE WORKERS. OTHER PRECAUT:VIOLATION OF FED LAW(49CFR).FURTHER INFO ON NITROGEN FOUND IN PAMPHLETS FRM COMPRESSED GAS ASSOC (CGA),1235 JEFF DAVIS HIGHWAY,ARLINGTON,VA 22202,703-979-4341:G-10.1,P-1,P-9,P-14,SB-2

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-320F,-196C

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vap

or Density:NP
Spec Gravity:0.967 @70F
pH:NP
Viscosity:NP
Evaporation Rate & Reference:NA-GAS
Solubility in Water:2.33 SCC/100CC @32F
Appearance and Odor:COLORLESS, ODORLESS, TASTELESS GAS
Percent Volatiles by Volume:NA-GAS
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

===

Waste Disposal Methods:DONT ATTEMPT TO DISPOSE OF RESIDUAL OR UNUSED QUANTITIES.RETURN TO YOUR SUPPLIER FOR DISPOSAL.FOR EMERG DISPOSAL SECURE CYLINDER & VENT SLOWLY TO ATMOSPHERE IN WELL-VENTILATED AREA OR OUTDOORS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.