

ITW DEVCON/ A DYKEM COMPANY -- 71912-0351 SAFETAP PLUS -- 9150-01-386-7693

===== Product Identification =====

Product ID:71912-0351 SAFETAP PLUS

MSDS Date:02/02/1997

FSC:9150

NIIN:01-386-7693

MSDS Number: CFRKB

=== Responsible Party ===

Company Name:ITW DEVCON/ A DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST. LOUIS

State:MO

ZIP:63114-5905

Country:US

Info Phone Num:800-452-5823

Emergency Phone N

um:800-424-9300(CHEMTREC)

Preparer's Name:DEBBIE MAKITA

CAGE:98148

=== Contractor Identification ===

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

CAGE:6A908

Company Name:ITW DYKEM/ DYMON

Address:805 E OLD 56 HWY

Box:City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:800-443-9536

CAGE:98148

===== Composition/Information on Ingredients =====

Ingred Name:PER MSDS:PRODUCT CONTAINS NO COMPONENTS

SUBJ TO REPORTING

REQMTS OF OSHA'S HAZ COMM STD 1910.1200.

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION RISKS ARE UNLIKELY AT
NORMAL ROOM TEMPERATURES. AT ELEVATED TEMPERATURES EYE, NOSE &
THROAT IRRITATION MAY OCCUR. SKIN & EYE CONTACTS RISKS ARE SLIGHT
IRRITATION. SKIN ABSORPTION RISKS ARE SLIGHT IRRITATION. INGESTION
HEALTH RISKS ARE SLIGHT NAUSEA & VOMITING. CHRONIC: NO KNOWN
EFFECTS.

Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NTP/IARC/OSHA/
ACGIH:NO.

Effects of Overexposure:INGESTED-NAUSEA, VOMITING. SKIN-IRRITATION.
EYES-IRRITATION. INHALATION-POSSIBLE IRRITATION OF EYES, NOSE,
THROAT FROM VAPORS PRODUCED AT HIGH TEMPERATURES.

Medical Cond Aggravated by Exposure:SKIN DISORDERS.

===== First Aid Measures =====

First Aid:EYE-FLUSH WELL WITH WATER. CONTACT PHYSICIAN IF IRRITATION
PERSISTS. SKIN-WASH WITH SOAP & WATER. INHAL-NO EMERGENCY CARE
ANTICIPATED UNDER NORMAL CONDITIONS. INGEST-DO NOT INDUCE VOMITING.
CONTACT PHYSICIAN. IF VOMITING OCCURS KEEP HEAD BELOW HIPS TO
PREVENT ASPIRATION OF LIQUID INTO LUNGS.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point

:>200F,>93C

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:WATER, CO2, DRY CHEMICAL, FOAM, ALCOHOL FOAM.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED
BREATHING APPARATUS IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:PREVENT SKIN & EYE CONTACT. MOP UP OR USE
ABSORBENT MATERIAL, WASH AREA, DISCARD IN SUITABLE CONTAINER

S.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED AT NORMAL HANDLING TEMPERATURES.
Ventilation:LOCAL EXHAUST IS RECOMMENDED FOR CONFINED AREAS. GENERAL
MECHANICAL VENTILATION IS ADEQUATE FOR NORMAL US

E.
Protective Gloves:CHEMICAL RESISTANT-PVC.
Eye Protection:SAFETY GLASSES, SPLASH PROOF GOGGLES.
Other Protective Equipment:PROTECTIVE GEAR AS REQUIRED TO MINIMIZE SKIN
CONTACT. EYE BASH, SAFETY SHOWER.
Work Hygienic Practices:FOLLOW CURRENT HMIS REGULATIONS.
Supplemental Safety and Health
NEW RECORD PRODUCED BECAUSE OF USE OF NEW/DIFFERENT MFR PART NUMBER &
TRADE NAME. MSDS RECEIVED PER SOLICITATION/CONTRACT NUMBER(S)
SP0400-97-T6496/SP0450-97-MN625 FROM CAGE 6A908.

=====

==== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:163F,73C
Vapor Density:>1
Spec Gravity:1.01
VOC Grams/Liter:.09
Evaporation Rate & Reference: