View NSN Online: https://aerobasegroup.ae/nsn/6810-01-449-5127

Product ID:C298-4 CHLOROFORM MSDS Date:07/03/1997 FSC:6810 NIIN:01-449-5127 MSDS Number: CFWBC === Responsible Party === Company Name: FISHER SCIENTIFIC, CHEMICAL DIV. Address:1 REAGENT LANE City:FAIR LAWN State:NJ ZIP:07410 Country:US Info Phone Num:201-796-7100 Emergency Phone Num:201-796-7100/800-424-9300(CHEMTREC) CAGE:1B464 === Contractor Identification === Company Name: FISHER SCIENTIFIC CO. CHEMICAL MFG DIV Address:1 REAGENT LANE Box:City:FAIRLAWN State:NJ ZIP:07410-2802 Country:US Phone:201-796-7100 CAGE:1B464 Ingred Name: CHLOROFORM (SARA 302/313) (CERCLA) CAS:67-66-3

RTECS #:FS9100000 Fraction by Wt: >99%

OSHA PEL:C 50 PPM

EPA Rpt Qty:10 LBS

D

ACGIH TLV:10 PPM; A2; 9596

Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:ORAL,RAT LD50: 908MG/KG. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:CONTACT MAY CAUSE SKIN & EYE

IRRITATION.INHALATION & INGESTION MAY CAUSE CNS DEPRESSION.MAY CAUSE RESPIRATORY & GI TRACT IRRITATION.INGESTION MAY CAUSE KIDNEY & LIVER DAMAGE.INHALATION MAY CAUSE CARDI AC SENSI

TIZATION &

POSSIBLE FAILURE.CHRONIC:PROLONGED/REPEATED EXPOSURE MAY CAUSE KIDNEY INJURY,CANCER,LIVER DAMAGE.

Explanation of Carcinogenicity:LISTED BY IARC (GROUP 2B CARCINOGEN), NTP (SUSPECT CARCINOGEN), ACGIH (A2-SUSPECT CARCINOGEN), OSHA (POSSIBLE SELECT).

Effects of Overexposure: EYES-SEVERE BURNS, POSSIBLE IRREVERSIBLE EYE DAMAGE. SKIN-BURNING PAIN, ITCHING, REDNESS. INGESTED-NAUSEA, VOMITING, DIARRHEA, CARDIAC DISTURBANCES. INHALED-HEADACHE, DIZZINESS, UNCONSCIOUS

NESS, COMA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. TARGET ORGANS: KIDNEYS, HEART, CENTRAL NERVOUS SYSTEM, LIVER, GASTROINTESTINAL SYSTEM, EXCRETORY SYSTEM.

First Aid:IN ALL CASES GET IMMEDIATE MEDICAL ATTENTION. EYES-FLUSH WITH WATER FOR 15 MINUTES, LIFT LIDS. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH MILD SOAP & WATER. INHALED-REMOVE TO FRESH AIR. GIVE OXYGEN O R ARTIFICIAL

RESPIRATION AS NEEDED. INGESTED-DO NOT INDUCE VOMITING! IF CONSCIOUS/ALERT, GIVE 2-4 CAPFULS MILK/WATER.

Flash Point:NOT AVAILABLE

Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM. USE EXTINGUISHING MEDIA MOST APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:NON-FLAMMABLE.

===================

Spill Release Procedures: ABSORB SPILL WITH INERT MATERIAL, THEN PLACE IN A CHEMICAL WASTE CONTAINER. AVOID RUNOFF INTO STORM SEWERS & DITCHES WHICH LEAD TO WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:DO NOT STORE IN DIRECT SUNLIGHT. STORE IN A COOL, DRY, WELL-VENTILATED PLACE AWAY FROM INCOMPATIBLE MATERIAL

S. KEEP AWAY FROM ACIDS.

Other Precautions:DO NOT STORE NEAR ALKALINE SUBSTANCES. USE WITH ADEQUATE VENTILATION. DO NOT GET ON SKIN OR IN EYES. AVOID INGESTION & INHALATION.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: FOLLOW THE OSHA RESPIRATOR REGULATIONS FOUND IN 29 CFR 1910.134. ALWAYS USE A NIOSH-APPOROVED RESPIRATOR WHEN NECESSARY.

Ventilation: USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW

TLV(S).

Protective Gloves: APPROPRIATE PROTECTIVE GLOVES.

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT SKIN EXPOSURE. DLA-HMIS: EYE WASH STATION & SAFETY SHOWER AVAILABLE.

Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health

INCOMPATIBLES CONTINUED: NITROGEN TETROXIDE, PHOSPHOROUS PENTOXIDE,

POTASSIUM, POTASSIUM HYDROXIDE, METHYL ALCOHOL, POTASSIUM TER-BUTOXIDE, SODIUM METHYLATE, SODIUM-POTASSIUM ALLOY, TRIISOPROPYLPHOSPH INE, CALCIUM HYDROXIDE, FLUORINE.

HCC:T3 Boiling Pt:B.P. Text:143F,62C Melt/Freeze Pt:M.P/F.P Text:-82F,-63C Decomp Temp:Decomp Text:NOT AVAIL.. Vapor Pres:160 Vapor Density:4.12 Spec Gravity:1.5 Viscosity:5.63 MP @ 68F Evaporation Rate & amp; Reference:11.6 (N-BUTYL ACETATE=1) Solub

ility in Water:INSOLUBLE Appearance and Odor:CLEAR, COLORLESS, VOLATILE LIQUID; SWEET ODOR.

Stability Indicator/Materials to Avoid:YES

ACETONE, ALKALIS, STRONG OXIDIZING AGENTS, DISILANE, LITHIUM,

MAGNESIUM, NITROGEN TETROXIDE, PERCHLORIC ACID, SODIUM....

Stability Condition to Avoid:HIGH TEMPERATURES, INCOMPATIBLE MATERIALS, LIGHT.

Hazardous Decomposition Products:HYDROGEN CHLORIDE, CARBON DIOXIDE, CHLORINE, PHOSG

ENE GAS.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its

use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.