View NSN Online: https://aerobasegroup.ae/nsn/8010-01-334-0902

Product ID:TT-E-2784A MSDS Date:09/15/1997 FSC:8010 NIIN:01-334-0902 **MSDS Number: CFXFN** === Responsible Party === **Company Name: DURANT PAINT** Address:960 BROADWAY City:REVERE State:MA ZIP:02051 Country:US Info Phone Num:617-289-1400 Emergency Phone Num:617-289-1400 CAGE:NO367 === Contractor Identification === Company N ame:DURANT PAINT Address:950 BROADWAY Box:City:REVERE State:MA ZIP:02051 Country:US Phone:617-289-1400 CAGE:NO367 Company Name: DURANT PAINTS INC Address:112 RAILROAD ST Box:City:REVERE State:MA ZIP:02151-4007 Country:US Phone:781-289-8415 CAGE:3F338

Ingred Name:GLYCOL ETHER (VAPOR PRESSURE 25%) CAS:111-77-3 RTECS #:KL6125000 Fraction by Wt: 7.20% Other REC Limits:NONE RECOMMENDED

Ingred Name: GLYCOL ETHER (VAPOR PRESSURE 0.1%

) CAS:770-35-4 Fraction by Wt: 1.30% Other REC Limits:NONE RECOMMENDED
Ingred Name:VOC = 1.46 G/L, NON-EXEMPT SOLVENT PER ADJUSTED GALLON. RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION. INHAL: IRRITATING TO NOSE/THROAT. INGEST:TOXIC. Effects
of Overexposure:INHAL: HEADACHE, NAUSEA, VOMITING, DROWSINESS. Medical Cond Aggravated by Exposure:HEART CONDITIONS, ASTHMA.
======================================
First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH W/SOAP & WATER. REMOVE CONTAIM CLOTHES. INHAL: GET FRESH AIR. OXGEN IF NEEDED. INGEST: GIVE TWO GLASSES OF WATER. INDUCE VOMIT.
======================================
Flash Point:NONFLAMMBLE
Ext inguishing Media:CO2, FOAM. Fire Fighting Procedures:USE FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:COOL CONTAINERS W/WATER STEAM IN EVENT OF A FIRE.
======================================
Spill Release Procedures:DIKE & CONTAIN. SOAK UP RESIDUE W/ABSORBENT MATERIAL.
======================================
Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. PROTECT FROM FREEZING.
Europeuro O

====== Exposure C

ontrols/Personal Protection =========

Respiratory Protection:REQUIRED. Ventilation:REQUIRED. Protective Gloves:REQUIRED. Eye Protection:REQUIRED. Other Protective Equipment:APRON. Work Hygienic Practices:WASH AFTER HANDLING. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:212F,156C Vapor Density:>AIR Evaporation Rate & amp; Reference:VALUE NOT STATED Solubility in Water:100% Percent Volatiles by Volume:58.9

=====

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS. Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME. Hazardous Decomposition Products:CARBON MONOXIDE & UNIDENTIFIED ORGANIC COMPOUNDS.

Waste Disposal Methods: DISPOSE OF IN RECKA APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is for mulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.