

DEL PAINT CORP. -- TT-E-2784 GRAY #36628 -- 8010-01-418-7185

=====  
Product Identification  
=====

Product ID:TT-E-2784 GRAY #36628  
MSDS Date:06/14/1995  
FSC:8010  
NIIN:01-418-7185  
MSDS Number: CFXPT  
=== Responsible Party ===  
Company Name:DEL PAINT CORP.  
Address:3105 E. RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Info Phone Num:405-672-1431/FAX 405-672-0804  
Emergency Phone Num:800-424-9300  
24 HRS  
Preparer's Name:ONEY FLEMING  
CAGE:JO954  
=== Contractor Identification ===  
Company Name:DEL PAINT CORP.  
Address:3105 E. RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431/FAX 405-672-0804  
CAGE:JO954  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
Box:City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:39934

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPYLENE GLYCOL  
CAS:57-55-6  
RTECS #:TY2000000  
Fraction b

y Wt: 6.25%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3,3,-PENTANEDIOL MONOISOBUTYRATE  
CAS:25265-77-4  
RTECS #:UF6000000  
Fraction by Wt: 4.86%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL  
CAS:108-01-0  
RTECS #:KK6125000  
Fraction by Wt: 0.38%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE  
CAS:26530-20-1  
Fraction by Wt: 0.18%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS  
Fraction by Wt: 88.33%  
Oth  
er REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:VOC = 1.6 LBS/GL  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: HEADACHE, NAUSEA, IRRITATION.  
EYE: IRRITATION. SKIN: IRRITATION.  
Medical

Cond Aggravated by Exposure:LUNG DISEASE.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES, CALL DR.  
SKIN: WASH THOROUGHLY W/SOAP & WATER. INGEST: GIVE 2 GLASSES OF  
WATER TO DRINK. CALL DR.

=====  
Fire Fighting Measures  
=====

Flash Point Method:SCC  
Flash Point:>212F,>100C  
Autoignition Temp:Autoignition Temp Text:216F  
Lower Limits:NONE  
Upper Limits:NA  
Extinguishing Media  
:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL & WATER FOG.  
Fire Fighting Procedures:WEAR SCBA & FULL PROTECTIVE GEAR.  
Unusual Fire/Explosion Hazard:MATERIAL MAY SPLATTER ABOVE 212F. POLYMER  
FILM MAY BURN.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:EVAC AREA. FLOOR MAY BE SLIPPERY. CONTAIN  
SPILL W/INERT MATERIAL. TRANSFER LIQUID/ABSORBENT TO SEPARATE  
SUITABLE CONTAINER FOR RECOVERY/DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP FROM FREEZING.  
Other Precautions:KEEP AWAY FROM CHILDREN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:MECHANICAL FILTER RESPIRATOR.  
Ventilation:NORMAL (FAN).  
Protective Gloves:RUBBER.  
Eye Protection:SAFETY GLASSES OR GOGGLES.  
Other Protective Equipment:EYEWASH STATION.  
Supplemental Safety and Health  
NK

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. T

ext:212 TO 644F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:350F,177C

Vapor Pres:NONE

Vapor Density:>AIR

Spec Gravity:1.14

pH: