

SPRAY-ON PRODUCTS INC. -- UPSIDEDOWN MARKING PAINTS & STRIPPING PAINTS --
8010-01-418-7648

=====
===== Product Identification =====

Product ID:UPSIDEDOWN MARKING PAINTS & STRIPPING PAINTS

MSDS Date:07/20/1994

FSC:8010

NIIN:01-418-7648

MSDS Number: CFXPV

=== Responsible Party ===

Company Name:SPRAY-ON PRODUCTS INC.

Address:26300 FARGO AVE

City:BEDFORD HEIGHTS

State:OH

ZIP:44146-1310

Country:US

Info Phone

Num:800-832-2541

Emergency Phone Num:216-566-2917

CAGE:IO713

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

Company Name:SPRAY-ON PRODUCTS

Address:26300 FARGO AVE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400

CAGE:IO713

=====
===== Composition/Information on Ingredients =====

Ingred Nam

e:PROPANE (VP = 760)
CAS:74-98-6
RTECS #:TX2275000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM

Ingred Name:ETHYL BENZENE (SARA 313) (VP = 7.1)
CAS:100-41-4
RTECS #:DA0700000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/STEL 125
ACGIH TLV:100 PPM/STEL 125
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE (SARA 313) (CERCLA) (VP = 5.9)
CAS:1330-20-7
RTECS #:ZE2100000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/STEL 150
ACGIH TLV:100 PPM/150 PPM
EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA) (VP = 180)
CAS:67-64-1
RTECS #:AL3150000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:750 PPM/1000
ACGIH TLV:750PPM/STEL 1000
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:2-METHYL PROPANE (VP = 780)
CAS:75-28-5
RTECS #:TZ4300000
Other REC Limits:NONE RECOMMENDED

Ingred Name:METHYL ETHER (VP = 7

60)

CAS:115-10-6

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ingred Name:MINERAL SPIRITS (VP = 2.0)

CAS:64642-88-7

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:TOLUENE (SARA 313) (CERCLA) (VP = 22.0)

CAS:108-88-3

RTECS #:XS5250000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/STEL 150

ACGIH TLV:50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:V. M. & P. NAPHTHA (VP = 12.0)

CAS:64742-48-9

Other REC Limits:NONE RECO

MMENDED

OSHA PEL:300 PPM/STEL 400

ACGIH TLV:300 PPM

Ingred Name:METHYLENE (SARA 313) (VP = 92.0)

CAS:67-56-1

RTECS #:PC1400000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/STEL 250

ACGIH TLV:200 PPM/STEL 250

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:1-BUTANOL (SARA 313) (VP = 5.5)

CAS:71-36-3

RTECS #:EO1400000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL (SARA 313) (VP = .06)

CAS:1

11-76-2
RTECS #:KJ8575000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:25 PPM
ACGIH TLV:25 PPM

Ingred Name:CALCIUM CARBONATE
CAS:471-34-1
RTECS #:FF9335000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS DUST
ACGIH TLV:10 MG/M3 AS DUST

Ingred Name:BARIUM SULFATE (SARA 313)
CAS:7727-43-7
RTECS #:CR0600000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS DUST
ACGIH TLV:10 MG/M3 AS DUST

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
AS DUST
ACGIH TLV:10 MG/M3 AS DUST

Ingred Name:VOC = 56-84 LBS/GL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: HEADACHE, DIZZY, NAUSEA, LOSS
OF COORDINATION, RESPIRATORY SYSTEM IRRIT, NS DEPRESSION,
UNCONSCIOUS, DEATH.

SKIN: IRRITATION, REDNESS, ITCHING, BURNING.
EYE: IRRITATION, REDNESS, ITCHING, BURNING.

=====
First Aid Measures
=====

First Aid: INHAL: GET FRESH AIR. RESTORE BREATHING. KEEP WARM/QUIET.
SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES, WASH BEFORE REUSE. EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. INGEST: DONT INDUCE VOMIT , DRINK SEVERAL GLASSES WATER, GET MED AID.

=====
Fire Fighting Measures
=====

Flash Point: ETHER
Solubility in Water: NA
Percent Volatiles by Volume: 47.18

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid: YES
NK
Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE.

=====
Disposal Considerations
=====

Waste Disposal Methods: DONT INCINERATE. DEPRESSURIZE CONTAINERS.
DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.