

P-T TECHNOLOGIES INC -- REMOVE-HP -- 6850-01-446-8063

=====  
Product Identification  
=====

Product ID:REMOVE-HP  
MSDS Date:04/29/1997  
FSC:6850  
NIIN:01-446-8063  
MSDS Number: CFYJW  
=== Responsible Party ===  
Company Name:P-T TECHNOLOGIES INC  
Address:108 4TH AVENUE, SOUTH  
City:SAFETY HARBOR  
State:FL  
ZIP:34695  
Country:US  
Info Phone Num:800-441-7874/813-726-4644  
Emergency Phone Num:813-726-4644  
CAGE:0JVH6

=== Contractor Identification ===  
Company Name:P-T TECHNOLOGIES INC  
Address:108 4TH AVENUE, SOUTH  
Box:City:SAFETY HARBOR  
State:FL  
ZIP:34695  
Country:US  
Phone:813-726-4644  
CAGE:0JVH6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HEAVY AROMATIC NAPHTHA (SOLVENT NAPHTHA)  
CAS:64742-94-5  
RTECS #:WF3100000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYL LACTATE  
CAS:97-64-3  
RTECS #:OD5075000  
Other REC Limits:NONE RECOMMENDED

=====  
Hazards Iden  
=====

tification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE-MAY CAUSE IRRITATION. SKIN-MAY  
CAUSE DEFATTING OR DRYNESS OF SKIN. CONTINUED DRYNESS MAY CAUSE  
DERMATITIS. INHALATION-CAN CAUSE IRRITATION OF THE RESPIRATORY  
TRACT. INGESTION-MAY CAUSE GASTROINTESTINAL IRRITATION.  
Explanation of Carcinogenicity:NOT CARCINOGENIC.  
Effects of Overexposure:EYE-TEARING AND REDNESS. INHALATION-NAUSEA,  
DIZZINESS OR HEADACHE. INGESTION-NAUSEA AND VOMITING.  
Medical Conditions Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS,  
CONTACT PHYSICIAN. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. REMOVE  
CONTAMINATED CLOTHING. INHALATION-IF AFFECTED BY VAPOR, GET TO  
FRESH AIR. IF BREATHING IS DIFFICULT, SEE PHYSICIAN.INGESTION-DO  
NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBONS. CONSULT  
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:133F,56C  
Autoignition Temp:Autoignition Temp Text:410F  
Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY  
CHEMICAL. CLASS B FIRE PROCEDURES.  
Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM COMBUSTIBLE  
MIXTURES AT OR ABOVE FLASH POINT.  
Unusual Fire/Explosion Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. CONTAIN THE SPILL.  
RECOVER FREE PRODUCT. ABSORB WITH SUITABLE CHEMICAL ABSORBENT FOR  
DISPOSAL VIA INCINERATION OR BURIAL IN APPROVED LANDFILL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AMBIENT.  
Other Precautions:KEEP AWAY FROM HEAT SOURCES, OPEN FLAMES, AND OTHER  
IGNITION SOURCES.

TION SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:NORMAL ROOM VENTILATION IS USUALLY ADEQUATE. USE FANS OR OTHER MECHANICAL VENTILATION IN ENCLOSED AREAS.

Protective Gloves:SOLVENT RESISTANT GLOVES RECOMMENDED.

Eye Protection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and He

alth

RCRA HAZARD CLASS: NOT HAZARDOUS. KEEP OUT OF REACH OF CHILDREN.

===== Physical/Chemical Properties =====

HCC:F4

Vapor Pres:1

Spec Gravity:.9631

Solubility in Water: