

EASTMAN KODAK COMPANY -- 159 7392 FLEXICOLOR FIXER AND REPLENISHER, CONCENTRATE
-- 6750-01-135-5686

===== Product Identification =====

Product ID:159 7392 FLEXICOLOR FIXER AND REPLENISHER, CONCENTRATE

MSDS Date:06/05/1997

FSC:6750

NIIN:01-135-5686

MSDS Number: CFYPD

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

In

fo Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition

/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 50-60%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE
CAS:7783-18-8
RTECS #:XN6465000
Fraction by Wt: 35-40%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM SULFITE (CERCLA)
CAS:10196-04-0
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA)
CAS:7631-90-5
RTECS #:VZ
2000000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BISULFITE (CERCLA)
CAS:10192-30-0
RTECS #:WT3595000
Fraction by Wt: < 1%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT): NOT GIVEN
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of C

arcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY LIBERATE SULFUR DIOXIDE GAS WHICH IS IRRITATING TO RESPIRATORY TRACT. EYE CONTACT CAUSES IRRITATION. SKIN CONTACT MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Eff

ects of Overexposure:EYE IRRITATION, ALLERGIC SKIN REACTION, RESPIRATORY TRACT IRRITATION, DIFFICULT BREATHING.

Medical Cond Aggravated by Exposure:SOME ASTHMATICS OR HYPERSENSITIVE INCIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING.

===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKI

N: WASH WITH

SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR.

INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION.

NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:NONFLAMMABLE. USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND

PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUA L CONTAMINATION.

Neutralizi

ng Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING MIST. AVOID CONTACT WITH EYES & PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:KEEP AWAY FROM OXIDIZING AGENTS. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOU
LD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACI
LITIES.

Supplemental Safety and Health

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.35

pH:6.2

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT YELLOW LIQUID, NO ODOR

Percent Volatiles by Volume:30-40%

===== Stability and Reactivity Da

ta =====

Stability Indicator/Materials to Avoid: YES

BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG ACIDS.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: OXIDES OF NITROGEN, SULFUR DIOXIDE, AMMONIA, CHLORAMINE.

===== Disposal Considerations =====

Waste Disposal Methods: DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER IF ALLOWABLE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of the information to their particular situation.