

INLAND VACUUM INDUSTRIES INC -- INVOIL 940 -- 9150-00-930-4945

===== Product Identification =====

Product ID:INVOIL 940  
MSDS Date:01/23/1996  
FSC:9150  
NIIN:00-930-4945  
MSDS Number: CFYYG  
=== Responsible Party ===  
Company Name:INLAND VACUUM INDUSTRIES INC  
Address:35 HOWARD AVE  
Box:373-T  
City:CHURCHVILLE  
State:NY  
ZIP:14428  
Country:US  
Info Phone Num:716-293-3330  
Emergency Phone Num:716-293-3330  
Preparer's Name:SANDRA J.EMLAMR  
CAGE:59256  
=== Contractor Identification ===  
Company Name:INLAND VACUUM INDUSTRIES INC  
Address:35 HOWARD AVE  
Box:373  
City:CHURCHVILLE  
State:NY  
ZIP:14428  
Country:US  
Phone:716-293-3330  
CAGE:59256  
Company Name:SDB CONSULTANTS LTD  
Address:401 WHITNEY AVE SUITE 120  
Box:City:GRETNA  
State:LA  
ZIP:70056  
Country:US  
Phone:504-366-9105  
CAGE:0PGK2

===== Composition/Information on Ingredients =====

Ingred Name:TETRAMETHYL,TETRAPHENYL,TRISILOXANE (METHYLPHENYL SILI

CONE)  
CAS:3982-82-9

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Health Hazards Acute and Chronic:MANUFACTURER STATES DETAILED STUDIES  
HAVE NOT BEEN MADE BUT MATERIAL IS NOT EXPECTED TO BE DERMATITIC.  
Effects of Overexposure:NONE KNOWN TO MFR;MAY IRRITATE EYES OR SKIN ON  
PROLONGED CONTACT.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O2  
IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Extinguishing Media:CHEMICAL FOAM,CO2  
Fire Fighting Procedures:USE NIOSH APPROVED SCBA IN FIRES AND IN  
CONFINED AREA  
Unusual Fire/Explosion Hazard:NONE NOTED BY THE MFR.

===== Accidental Release Measures =====

Spill Release P  
rocedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE  
INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTION.STORE IN COOL  
DRY AND GOOD VENTILATED AREA.KEEP CONTAINER TIGHTLY CLOSED.  
Other Precautions:AVOID CONTACT WITH SKIN AND EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE REQUIRED UNDER NORMAL

USE.  
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION  
Protective Gloves:OIL RESISTANT RUBBER  
Eye Protection:GOGGLES OR SAFETY GLASSES W.SIDE SHIELDS  
Other Protective Equipment:NONE SHOULD BE REQUIRED NORMAL USE.  
Work Hygienic Practices:USED OIL FROM VACUUM PUMPS IS HOT (>122F,>50C).  
AVOID SKIN CONTACT TO PREVENT BURNS.--SEE SUPPLEMENTAL S&H DATA--  
Supplemental Safety and Health  
WORK HYGENIC PRACTICES,CONTINUED:IF VACUUM PUMP IS USED TO PUMP CORROSIVE GASES,RE  
SPIRATORS MAY BE REQUIRED BY PUMP MAINTENANCE PERSONNEL.

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>392F,>200C  
Spec Gravity:1.07  
Evaporation Rate & Reference:NIL (BU AC=1)  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:CLEAR TO PALE YELLOW TRANSPARENT, VISCOUS LIQUID, WITH NO ODOR.  
Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
  
STRONG OXIDIZERS,ACIDS,ALKALIS  
Stability Condition to Avoid:HEAT,FLAMES  
Hazardous Decomposition Products:INCOMPLETE COMBUSTION PRODUCES CO.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.  
  
Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States o

f America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.