

KRYLON/SPRAYON INDUS PRODS,SHWERWIN-WILLIAMS -- 1301 CRYSTAL CLEAR ACRYLIC --  
8010-00-990-7289

===== Product Identification =====

Product ID:1301 CRYSTAL CLEAR ACRYLIC

MSDS Date:09/01/1996

FSC:8010

NIIN:00-990-7289

MSDS Number: CFYYP

=== Responsible Party ===

Company Name:KRYLON/SPRAYON INDUS PRODS,SHWERWIN-WILLIAMS

Address:31500 SOLON ROAD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Phone Num:

800-777-2966/800-247-3266

Emergency Phone Num:216-566-2917

CAGE:MO454

=== Contractor Identification ===

Company Name:KRYLON/SPRAYON INDUS PRODS,SHWERWIN-WILLIAMS

Address:31500 SOLON ROAD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-777-2966/800-247-3266

CAGE:MO454

Company Name:NASCO INTL INC., NASCO DIV

Address:901 JANESVILL AVE

Box:City:FORT ATKINSON

State:WI

ZIP:53538-0901

Country:US

Phone:920-563-2446

CAGE:33089

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FA

RGO AVENUE  
Box:City:BEDFORD HEIGHTS  
State:OH  
ZIP:44146  
Country:US  
Phone:216-292-7400 OR 216-595-8634  
CAGE:09800

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 15%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9596

Ingred Name:BUTANE  
CAS:106-97-8  
RTECS #:EJ4200000  
Fraction by Wt: 15%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:800 PPM  
ACGIH TLV:800 PPM; 9596

Ingred Name:LIGHT ALI  
PHATIC HYDROCARBON  
CAS:64742-89-8  
Fraction by Wt: 6%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYL BENZENE (SARA 313)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: 4%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/125STEL;9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 23%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/150STEL;9596  
EPA Rpt

Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:MED. AROMATIC HYDROCARBONS  
CAS:64742-94-5  
RTECS #:WF3100000  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETONE (SARA 313) (CERCLA)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 26%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:750PPM/1000STEL;9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Ro

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPO MAY BE BY INHAL &/OR SKIN/EYE

COTNACT DEPENDING ON CONDITIONS OF USE.TO MIN EXPO FOLLOW  
RECOMMENDATIONS FOR PROPER USE/VENTI/PPE.IRRIT EYE/SKIN/RESP  
SYS.MAY CAUSE NERV SYS DEPRESS.EXTREME OVEREXP O MAY RESULT IN  
UNCONSC,POSSIBLY DEATH.

Explanation of Carcinogenicity:PER MSDS:CHROMATES LISTED BY  
IARC/NTP.STUDIES HAVE ASSOC EXPO TO CR

VI CMPDS W/INCR RISK OF  
RESPIRATORY CANC.CA PROP 65.

Effects of Overexposure:HEAD,DIZZ,NAU,LOSS OF COORDINATION INDICATIONS  
OF EXCESSIVE EXPO TO VAP/SPRAY MISTS.REDNESS,ITCHING OR BURNIG SENS  
MAY INDICATE EYE/EXCESSIVE SKIN EXPO.PROL OVEREXPO TO SLVT INGREDIENTS  
MAY CAUSE ADVERSE EFFECTS TO  
LIVER/URINARY/BLOOD-FORMING,CARDIOVASCULAR/REPRODUCTIVE  
SYST.REPORTS HAVE ASSOC REP/PROL OVEREXPO TO (SUPPLE)

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

=====

===== First Aid Measures =====

First Aid: INHAL: IF AFFECTED REMOVE FROM EXPO. RESTORE BREATH. KEEP WARM/QUIET. SKIN: WASH AREA THOROUGHLY W/SOAP/WATER. REMOVE CONTAM CLOTH. EYE: FLUSH W/LG AMTS OF WATER FOR 15MINS. GET MED ATTN. INGEST: NEVER GIVE ANYTHING BY MOUTH IF UNCONSC. DONT INDUCE VOMITING. GIVE CONSC PATIENT SEVERAL GLASSES OF WATER. SEEK MED ATTN.

===== Fire Fighting Measures =====

Flash Point Method: PMCC  
Flash Point: