

AGA GAS INC -- HEXANE IN AIR,400 PPM,517400 -- 6830-01-303-4937

===== Product Identification =====

Product ID:HEXANE IN AIR,400 PPM,517400

MSDS Date:01/01/1995

FSC:6830

NIIN:01-303-4937

MSDS Number: CGDYJ

=== Responsible Party ===

Company Name:AGA GAS INC

Address:6225 OAKTREE BLVD

Box:94737

City:CLEVELAND

State:OH

ZIP:44131

Country:US

Info Phone Num:216-642-6600

Emergency Phone Num:216-642-6600

CA

GE:0KPC9

=== Contractor Identification ===

Company Name:AGA GAS INC

Address:6225 OAKTREE BLVD

Box:94737

City:CLEVELAND

State:OH

ZIP:44101-4737

Country:US

Phone:216-642-6600

CAGE:0KPC9

Company Name:C F C RECLAMATION AND RECYCLING SERVICE INC

Address:318 N TREADAWAY

Box:560

City:ABILENE

State:TX

ZIP:79604

Country:US

Phone:9150-675-5311 FAX: 915-675-5324

CAGE:0XXK5

===== Composition/Information on Ingredients =====

Ingred Name:HEXANE (N-HEXANE) (CERCLA)

CAS:110-54-3

RTECS #:MN9

275000  
Fraction by Wt: 400% PPM  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:500 PPM  
ACGIH TLV:50 PPM; 9596  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:AIR  
RTECS #:AX5275000  
Fraction by Wt: BALANCE  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NOT RELEVANT  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:TARGET ORGANS:LUNG. ACUT  
E- THESE

MIXTURES SHOULD BE CONSIDERED SIMILAR TO AIR. AIR IS NONTOXIC AND IS NECESSARY TO SUPPORT LIFE. INHALATION OF AIR IN A HIGH PRESSURE ENVIRONMENT SUCH AS UNDERWATER DIVING CAN RESULT IN SYMPTOMS SIMILAR TO OVEREXPOSURE TO PURE OXYGEN SUCH AS TINGLING OF FINERS, CNS EFFECTS. CHRONIC- NONE

Explanation of Carcinogenicity:NONE  
Effects of Overexposure:NONE IN NORMAL CONDITION OF USE. IF IN HIGH PRESSURE ENVIRONMENT: TINGLING OF FINGERS AND TOES, ABNORMAL SENSATION  
S, IMPAIRED COORDINATION, CONFUSION, HEADACHE  
Medical Cond Aggravated by Exposure:NONE.

===== First Aid Measures =====

First Aid:NONE NORMALLY NEEDED. IN CASE OF HIGH PRESSURE ENVIRONMENT, DECOMPRESSION EQUIPMENT MAY BE REQUIRED.

===== Fire Fighting Measures =====

Flash Point:NONE  
Lower Limits:NOT RELEVANT  
Upper Limits:NOT RELEVANT  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR SURRO

UNDING FIRE. KEEP FIRE-EXPOSED CYLINDERS COOL WITH WATER.

Fire Fighting Procedures:AS WITH ANY FIRE, WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS IF NEEDED.

Unusual Fire/Explosion Hazard:THE MIXTURE AT HIGH PRESSURES WILL ACCELERATE THE BURNING OF MATERIALS TO A GREATER RATE THAN THEY BURN AT ATMOSPHERIC PRESSURE.

===== Accidental Release Measures =====

Spill Release Procedures:NOT RELEVANT

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE CYLINDERS SECURE, IN COOL, DRY, VENTILATED AREA BELOW 125F. PROTECT CYLINDERS FROM PHYSICAL DAMAGE. FULL & EMPTY CYLINDERS SHOULD BE SEGREGATED.

Other Precautions:VENTING OF AIR FROM CYLINDER MUST BE ACCOMPLISHED SLOWLY. USE A "FIRST IN-FIRST OUT" INVENTORY SYSTEM. CLOSE VALVE AFTER EACH USE AND WHEN EMPTY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NEEDED.

Ventilation:NONE

Protective Gloves:LEATHER WHEN HANDLING CYLINDERS

Eye Protection:GOGGLES RECOMMENDED

Other Protective Equipment:EAR PROTECTION WHEN VENTING AIR

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

THE MANUFACTURER PROVIDED A MSDS FOR HEXANE. THE INFORMATION FOR AIR WAS TAKEN FROM MSDS PROVIDED BY THIS MANUFACTURER FOR NSN 6830-01-424-2499.

===== Physical/Chemical Properties =====

HCC:G3

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:-318F,-194C

Vapor Pres:14978;CTDF

Vapor Density:1.0

Spec Gravity:0.87 (LIQUID)

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT (GAS)

Solubility in Water:VERY SLIGHTLY

Appearance and Odor:COLORLESS, ODORLESS GAS

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:EXCESSIVE HEATING CYLINDER

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:NOT RELEVANT

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.