

DEFT INC CHEMICAL COATING DIV -- MIL-C-85285B, 35237, TYPE I (03BL159) -- 8010-01-285-2495

===== Product Identification =====

Product ID:MIL-C-85285B, 35237, TYPE I (03BL159)

MSDS Date:04/13/1995

FSC:8010

NIIN:01-285-2495

Kit Part:Y

MSDS Number: CGFDT

=== Responsible Party ===

Company Name:DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

In

fo Phone Num:714-474-0400

Emergency Phone Num:714-474-0400/800-424-9300 CHEMTREC

Preparer's Name:NORM GAUL

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

Routes of Entry: Inhal

ation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: IRRIT RESP TRACT/NOSE/THROAT,
ACUTE NS DEPRESSION. SKIN/EYES: IRRITATION. ABSORPTION: POS
MODERATE IRRIT/DRYING/DEFATTING/CRACKING W/PROLONGED/REPEATED
EXPOSE. INGEST: IRRIT/CORROSIVE ACTION IN MOUTH/STOMACH
TISSUE/DIGESTIVE TRACT, ASPIRATION OF LIQ RESULTING IN CHEM
PNEUMONITIS.

Effects of Overexposure:INHAL: HEADACHE, DIZZINESS, STAGGERING GATE,

CONFUSION, UNCONSC OR COMA, DIFFICULT BREATHING, ASTHMA. SKIN:
SENSITIZATION, OTHER ALLERGIC RESPONSES, SWELLING, REDNESS, RASH.
EYES: TEARING, REDNESS, SW ELLING W/STINGING SENSATION.

Medical Cond Aggravated by Exposure:ASTHMA & ANY OTHER RESP DISORDERS.
SKIN: ALLERGIES, EXCEMA, DERMATITIS.

=====
===== First Aid Measures =====

First Aid:INHAL: GET FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPICAL
SYMPTOMS MAY DEVELOP, MAY BE IMMED OR DELAYED BY
SEVERAL HRS. GET
MED AID. SKIN: REMOVE CONTAM CLOTHES. WASH THOROUGHLY W/SOAP &
WATER. EYES: FLUSH W/CLEAN LUKE WARM WATER (LOW PRESSURE) AT LEAST
15 MIN, LIFTING LIDS. GET MED AID. INGEST: DON'T INDUCE VOMITING.
DON'T GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON. GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:23.0F,-5.0C

Lower Limits:1.0

Upper Limits:11.4

Extinguishing Media:FOAM, ALCOHOL-FOAM, CARBON DIOXI
DE, DRY CHEMICAL,
WATER FOG, WATER SPRAY.

Fire Fighting Procedures:FIREFIGHTERS: FULL EQUIPMENT W/SCBA, FULL
PROTECTIVE CLOTHING. USE WATER TO COOL CLOSED CONTAINERS TO PREVENT
PRESSURE BUILD-UP, AUTOIGNITION, EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CLOSED TIGHT. CLOSED CNTNR MAY
EXPLODE W/EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES
SPECIAL PRECAUTIONS. POS HEALTH HAZ W/OVEREXPOSURE DECOMP PRODS

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE NONESSENTIAL PERSONNEL. REMOVE ALL IGNITION SOURCES. VENT. AREA. CONTAIN/REMOVE W/INERT ABSORBENT & NONSPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDING COMPLYING W/OSHA 1910.106. AVOID STORING NEAR HI TEMP/FIRE/OPEN FLAME/SPARK SOURCES. STORE IN TIGHT CLOSED CNTNR/WELL VENTED AREA.

Other Precautions:KEEP CNTNR TIGHT/UPRIGHT TO PREVENT LEAKAGE. PREVENT PR

OLONGED BREATHING VAPOR/SPRAY MISTS. POS ALLERGIC REACTION W/PROLONGED OVEREXPOSURE. AVOID SKIN/EYE CONTACT. DON'T TAKE INTERNALLY. DON'T HANDLE TIL READ/UNDERSTAND MFG PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESP THAT IS RECOMMENDED/APPROVED FOR USE IN ORG VAPOR ENVIRONMENT (AIR PURIFYING/FRESH AIR SUPPLIED) NECESSARY. OBSERVE OSHA REGS FOR RESP. PROVIDE VENTILATION TO KEEP EXPOSURE LEVELS