

LUCENT TECHNOLOGIES -- 105-501-415,EPOXY RESIN PART A FOR CONSUMABLE

=====  
MSDS Safety Information  
=====

FSC: 6080  
NIIN: 01-358-9686  
MSDS Date: 01/28/1998  
MSDS Num: CGLGT  
Product ID: 105-501-415,EPOXY RESIN PART A FOR CONSUMABLE KIT,RESIN  
MFN: 01  
Kit Part: Y  
Responsible Party  
Cage: 05YC5  
Name: LUCENT TECHNOLOGIES  
Address:  
600 MOUNTAIN AVE  
City: MURRAY HILL NJ 07974  
Info Phone Number: 908-582-3700  
Emergency Phone Number: 908-582-3700,800-424-9300(CHEMTREC)  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 2X264  
Name: ALL-SAFE INC  
Address: 4767 LANGTON RD  
Box: 116  
City: HILLIARD OH 43026  
Phone: 614-876-4041  
Cage: 05YC5  
Name: LUCENT TECHNOLOGIES  
Address: 600 MOUNTAIN AVE  
City: MURRAY HILL NJ 07974  
Phone  
: 908-582-3700

=====  
Item Description Information  
=====

Item Manager: S9E  
Item Name: INSTALLATION KIT,FIBER OPTIC  
Specification Number: NONE  
Type/Grade/Class: NONE  
Unit of Issue: EA  
UI Container Qty: 0  
Type of Container: PACKAGE

=====  
Ingredients  
=====

Cas: 2426-08-6  
RTECS #: TX4200000  
Name: 1-BUT

OXY-2,3-EPOXY PROPANE, N-BUTYL GLYCIDYL ETHER (BGE)

% Wt: 9.9

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 50 PPM

ACGIH TLV: 25 PPM; 9596

-----  
Cas: 25068-38-6

RTECS #: SL6475000

Name: EPOXY RESIN

% Wt: 60-100

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

=====  
Health Hazards Data  
=====

LD50 LC50 Mixture: ORAL LD50 (RAT) IS 2050 M

G/KG.

Route Of Entry Inds - Inhalation: NO

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: IRRITATING TO SKIN AND EYES. REPEATED CONTACT MAY CAUSE ALLERGIC SKIN REACTIONS IN SENSITIVE INDIVIDUALS. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES MAY CAUSE THERMAL BURNS.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: EYES: IRRITATION. SKIN: IRRITATION, ALLERGIC SKIN REACTIONS, BURNS.

Medical Cond Aggravated By Exposure: M

AY AGGRAVATE PREEXISTING SKIN AND EYE

DISORDERS. PREEXISTING SKIN OR LUNG DISORDERS MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOSURE TO THIS PRODUCT.

First Aid: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH SKIN AREA WITH LARGE AMOUNTS OF WATER. IF IRRIATION PERSISTS, GET MEDICAL ATTENTIO N. INHALATION: MOVE TO FRESH AIR. IF NOTBREATHING, GIVE CPR. IF BREATHING DIFFICULT,GIVE OXYGEN.

GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING.DRINK A GLASS OF WATER.GET MEDICAL ATTENTION.

=====  
Handling and Disposal  
=====

Spill Release Procedures: SCRAPE UP AND TRANSFER TO METAL CONTAINER FOR DISPOSAL. USE A RAG OR PAPER TOWEL WITH DETERGENT TO WIPE AND CLEAN OF REMAINING RESIDUE.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSE OF WASTE I

IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS.

Handling And Storage Precautions: STORE IN A COOL DRY PLACE. USE ONLY WITH  
ADEQUATE VENTILATION. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID  
BREATHING VAPOR OR MIST.

Other Precautions: WEAR APPROPRIATE PERSONAL PROTECTION WHEN HANDLING. WASH  
AFTER HANDLING.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point: =68.3C  
, 155.F

Lower Limits: 0.4%

Upper Limits: 1.3%

Extinguishing Media: DRY CHEMICAL OR CARBON DIOXIDE FOR SMALL FIRES. WATER  
SPRAY OR FOAM FOR LARGE FIRES.

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR POSITIVE PRESSURE SELF  
CONTAINED BREATHING APPARATUS AND THERMAL PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard: NONE

=====  
Control Measures  
=====

Respiratory Protection: RESPIRATORS ARE NOT REQUIRED UNDER NORMAL CONDITIONS OF  
USE. USE NIOSH APPROVED REPIRATOR IF CONCENTRATIONS EXCEED EXPOSURE LIMITS.

Ventilation: LOCAL EXHAUST VENTILATION IS RECOMMENDED. GENERAL VENTILATION MAY  
BE ACCEPTABLE.

Protective Gloves: REQUIRED. IMPERVIOUS PLASTIC/RUBBER TYPE.

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment: PROVIDE EYE WASH STATION AND SAFETY SHOWER. USE  
COVERALLS OR APRON TO PROTECT AGAINST SKIN AND CLOTHING CONTAMINATION.

Work Hygienic Practic

es: WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR  
SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSING.

Supplemental Safety and Health: KEY1:V4. THIS ENTRY DESCRIBES PART A OF A TWO  
PART KIT. SEE THIS SAME NSN, P/N IND B, FOR PART B DATA.

=====  
Physical/Chemical Properties  
=====

HCC: B2

Boiling Point: =140.C, 284.F

Vapor Pres: 2 MM HG

Vapor Density: 3.8

Spec Gravity: 1.14

Evaporation R

ate & Reference: >1

Appearance and Odor: MILKY WHITE PASTE WITH A PLEASANT ODOR.

Corrosion Rate: UNKNOWN

=====  
Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: NONE

Materials To Avoid: STRONG ACIDS, AMINES, MERCAPTANS, BASES.

Hazardous Decomposition Products: CARBON MONOXIDE, ALDEHYDES, OTHER ORGANICS.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Poly

merization: WILL NOT OCCUR. HEAT GIVEN OFF DURING CURE.

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 05YC5

Trans ID NO: 129075

Product ID: 105-501-415,EPOXY RESIN PART A FOR CONSUMABLE KIT,RESIN

MSDS

Prepared Date: 01/28/1998

Review Date: 03/09/1998

MFN: 1

Net Unit Weight: 90 GMS/UI

Multiple KIT Number: 0

Kit Part IND: Y

Review IND: Y

Unit Of Issue: EA

Container QTY: 0

Type Of Container: PACKAGE

Additional Data: EACH KIT, 105-501-415, CONTAINS 15 PACKAGES. EACH PACKAGE

CONTAINS 6 GMS OF PART A AND 2 GMS OF PART B. THEREFORE, EACH KIT CONTAINS A  
TOTAL OF 90 GMS OF PART A AND 30 GMS OF PART B.

=====  
Detail DOT Information  
=====

=====  
DOT PSN Code: ZZZ  
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

Detail IMO Information

=====  
IMO PSN Code: ZZZ  
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION  
=====

Detail IATA Information

=====  
IATA PS  
N Code: ZZZ  
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

Detail AFI Information

=====  
AFI PSN Code: ZZZ  
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

HAZCOM Label

=====  
Product ID: 105-501-415,EPOXY RESIN PART A FOR CONSUMABLE KIT,RES  
IN

Cage: 05YC5

Company Name: LUCENT TECHNOLOGIES

Street: 600 MOUNTAIN AVE

City: MURRAY HILL NJ

Zipcode: 07974

Health Emergency Phone: 908-582-3700,800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 03/10/1998

Status Code: C

Label Date: 03/10/1998

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Moderate

Reactivity Hazard: None

Hazard And Precautions: IRRITATING TO SKIN AND EYES. REP

EATED CONTACT MAY CAUSE

ALLERGIC SKIN REACTIONS. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES MAY CAUSE THERMAL BURNS. STORE IN A COOL DRY PLACE. USE WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. FIRST AID: EYES: FLUSH WITH WATER. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH SKIN AREA WITH WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR. IF BREATHING DIFFICULT, GIVE OXYGEN  
. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. DRINK A GLASS OF WATER. GET MEDICAL ATTENTION. TARGET ORGANS: EYES, SKIN.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or liability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.