View NSN Online: https://aerobasegroup.ae/nsn/5970-01-004-3377

Product ID:SCOTCHCAST PORCELAIN TERMINATION KIT 5903, PART B (POLYOL) MSDS Date:08/23/1996 FSC:5970 NIIN:01-004-3377 Kit Part:Y **MSDS Number: CGLTC** === Responsible Party === Company Name: 3M CENTER, ELECTRICAL PRODUCTS DIVISION Address:3M CENTER С ity:ST PAUL State:MN ZIP:55144-1000 Country:US Info Phone Num:800-364-3577/612-737-6501 Emergency Phone Num:800-364-3577/612-737-6501 CAGE:75037 === Contractor Identification === Company Name: MINNESOTA MINING AND MFG CO ELECTRICAL PRODUCTS DIV Address:3M AUSTIN CTR Box:City:AUSTIN State:TX ZIP:78769-2963 Country:US Phone:512-984-1800 CAGE:75037 Company Name: REUBEN BURTON INC **Box:UNKNOW** CAGE:2U475

Ingred Name:POLYBUTADIENE CAS

:69102-90-5 Fraction by Wt: 35-40% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIUNDECYL PHTHALATE CAS:3648-20-2 RTECS #:TI1980000 Fraction by Wt: 20-25% Other REC Limits:NONE RECOMMENDED

Ingred Name:GLYCOLS, POLYPROPYLENE CAS:25322-69-4 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:N,N BIS-(2-HYDROXYPROPYL)-ANILINE CAS:3077-13-2 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIPROPYLENE GLYCOL CAS:25265-71-8 RTECS #:UB8765000 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:ZEOLITE CAS:1318-02-1 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:CASTOR OIL CAS:8001-79-4 RTECS #:FI4100000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chron ic:EYE:MILD IRRITATION.SKIN:ALLERGIC SKIN REACTION.MILD SKIN IRRIT.INHAL:PROLONGED/REPEATED EXPO MAY CAUSE ALLERGIC RESIRATORY REACTION & IRRIT (UPPER RESPIRATORY).INGEST:NOT LIKELY ROUTE OF EXPO TO THIS PRODUCT. Effects of Overexposure: EYE: REDNESS, SWELLING, PAIN, TEARING. ALLERGIC SKIN RX:REDNESS,SWELLING,BLISTERING,ITCHING.SKIN IRRIT:REDNESS,SWELLING,ITCHING.ALLERGIC RESP RX:DIFFICULTY BREATHING, WHEEZING, TIGHTNESS OF CHEST, RESPIRATORY FAILURE. UPPER **RESP IRRIT:SORENES** S OF NOSE & THROAT, COUGHING, SNEEZING. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:EYE:IMMED FLUSH W/LG AMTS OF WATER.GET IMMED MED ATTN.SKIN:FLUSH W/LG AMTS OF WATER.IRRIT PERSISTS GET MED ATTN.INHAL:REMOVE PERSON TO FRESH AIR.NOT BREATH GIVE ART RESP; DIFFI BREATH GET IMMED MED ATT N.INGEST: DONT INDUCE VOMITING.DRINK TWOGLASSES OF WATER.CALL PHYSICIAN. _____ Flash Point Method:CC Flash Point:>320F,>160C Autoignition Temp: Autoignition Temp Text:ND Lower Limits:ND Upper Limits:ND Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING, INCLUDE HELMET, SELF-CONTAIN, POSITIVE PRESSURE OR PRESSURE DEMAND BREATH APPARATUS, BUNKER COAT/PANTS, BANDS AROUND ARMS/WAIST(SUPPL) Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. _____

Spill Release Procedures:REFER TO MSDS SECS ON PHY/HEALTH HAZ,RESP PROT,VENTI,PPE.POUR ISOCYANATE DECONT SOLN(90%H2O,8%CONC AMMONIA,2%DETERGENT)ONSPILL;ALLOW TO RX FOR 10MINS.ALTERNAT POUR H2O ON SPILL,ALLOW TO RX FOR MORE TH AN 30MINS.COVER W/ABSORBENT.PLACE IN APPROV(SUPPL) Neutralizing Agent:NEUTRALIZE SPILL RESIDUE W/DECONTAM SOLN(90%H2O,8%CONC AMMONIA,2%DETERGENT)

_____ Handling and Storage Precautions: KEEP CNTNR IN WELL-VENTI AREA. KEEP OUT OF REACH OF CHILDREN.KEEP CNTNR TIGHTLY CLOSED.DONT HEAT UNDER CONFINEMENT. Other Precautions: PER JIM TOME (3M) SAID MDI IS BOUND UP AS COPOLYMER; THEREFORE KIT IS NOT REGULATED BY ANY MODE OF TRANSPORTATION(A.QURESHI,HMIS,03MAR98 PHONE CALL). Respiratory Protection: AVOID BREATHING VAPORS. SELECT ONE OF FOLLOWING **NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCEN OF CONTAMINANTS** & IN ACCORDANCE WITH OSHA REGS: HALF-MASK ORGANIC VAPOR RSPIRATOR. Ventilation: PROVIDE SUFFIC VENTI TO MAINTAIN EMISSIONS BEL RECOMMENDED EXPO LIMITS.EXHAUST VENTI NOT ADEQUATE USE APPROP RESP PROTEC Protective Gloves: GLOVES WHEN HNDLG THIS MATERIAL Eye Protection: SAFETY GLASSES W/SIDE SHIELDS Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: AVOID EYE CONTACT. AVOID PROL/REP SKIN CONTACT.DONT INGEST

Supplemental Safety and Health

FIREFIGHT:LEGS, FACE MASK, PROTECTIVE COVERING FOR EXPO AREAS OF HEAD. SPILL:DR, BUT DONT SEAL DRM FOR 48HRS-AVOID POSSIBLE PRESSURE BUILDUP.NEUTRALIZE SPILL RESIDUE W/DECONTAMINANT SOLN. KIT 3-PART(SCOT CHCAST BRAND ELECTRICAL INSULATING RESIN 2100), SEE PNIND:A(PREPOLYMER),C(CABLE CLEANER).

HCC:N1 Boiling Pt:B.P. Text:NA Melt/Freeze Pt:M.P/F.P Text:ND Decomp Temp:Decomp Text:NP V apor Pres:NA Vapor Density:NA Spec Gravity:0.97 pH:NA Viscosity:10P Evaporation Rate & amp; Reference:NA Solubility in Water:REACTS Appearance and Odor: OPAQUE VISCOUS LIQUID Percent Volatiles by Volume:0 Corrosion Rate:NP

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:C0,C02,OXIDES OF NITROGEN,HYDROGEN

YANIDE, ISOCYANATES, TOXIC VAP, GASES OR PARTICULATES, IRRITANT VAPORS OR GASES.

Waste Disposal Methods:INCINERATE IN INDUSTRIAL OR COMMERCIAL FACILITY.DISPO OF COMPLETELY CURED(OR POLYMERIZED)MATL IN SANITARY LANDFILL.SINCE REGS VARY CONSULT APPLICABLE REGS/AUTHORITIES BEF DISPO.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Depa rtment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.