

MINNESOTA MINING/ADH COATINGS/SEALERS -- 1751B ALUMINUM EPOXY ADHESIVE --
8040-00-123-6954

===== Product Identification =====

Product ID:1751B ALUMINUM EPOXY ADHESIVE

MSDS Date:01/01/1995

FSC:8040

NIIN:00-123-6954

Kit Part:Y

MSDS Number: CGNCC

=== Responsible Party ===

Company Name:MINNESOTA MINING/ADH COATINGS/SEALERS

Address:3M CTR

City:ST PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:

612-733-1110

Emergency Phone Num:612-733-1110

Preparer's Name:C A EISENHARD

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN
CAS:25068-38-6
RTECS #:KD4380000
Fraction by Wt: 40-50%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM PIGMENTS
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: 30-40%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/3
ACGIH TLV:10 MG/3

Ingred Name:CLAY
CAS:68953-58-2
RTECS #:UZ2996400
Fraction by Wt: 1-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL GLYCIDYL ETHER
CAS:2426-08-6
RTECS #:TX
4200000
Fraction by Wt: 1-10%
Other REC Limits:25 PPM
OSHA PEL:270 MG/CUM
ACGIH TLV:133 MG/CUM

Ingred Name:AMORPHOUS SILICA
CAS:7631-86-9
Fraction by Wt: 1-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:RESORCINOL
CAS:108-46-3
RTECS #:UG9625000
Fraction by Wt: 1-10%
Other REC Limits:10 PPM
ACGIH TLV:45 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carc

inogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: REDNESS, SWELLING, PAIN, TEARING, HAZY VISION. SKIN: REDNESS, SWELLING, BLISTERS, ITCHING, ALLERGIC REACTION. INHAL: RESPIRATORY IRRIT, SORE NOSE/THROAT, COUGHING, SNEEZING. INGEST: GI TISSUE IRRIT, PAIN, VOMIT, TENDER ABDOMIN, NAUSEA, BLOOD IN VOMIT/FECES.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLO
THES, WASH BEFORE REUSE. DISPOSE OF CONTAM SHOES. INHAL: REMOVE TO FRESH AIR. INGEST: DONT INDUCE VOMITING. DRINK 2 GLASSES OF WATER. IN ALL CASES, GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point:NA
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:USE PROTECTIVE CLOTHES W/HELMET, SCBA (POSITIVE PRESSURE), BUNKER COAT AND PANTS, BANDS AROUND ARMS, WAIST, LEGS, FA
CE MASK, PROTECTIVE COVER FOR HEAD.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:COVER W/ABSORBENT MATERIAL. COLLECT SPILLED MATERIAL. PLACE IN A DOT APPROVED CONTAINER AND SEAL. CALL 612-733-1110/612-733-6100, 24 HOUR SPILL ASSISTANCE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY AREA AWAY FROM HEAT.
Other Precautions:KEEP AWAY FROM CHILDREN. KEEP CONTAINER TIGHTLY CLOSED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELECT A NIOSH APPROVED RESPIRATOR BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS AND IN ACCORDANCE W/OSHA REGULATIONS: HALF-MASK DUST RESPIRATOR. IF EXHAUST VENT IS NOT ADEQUATE, USE APPROPRIATE RES PIRATORY PROTECTION.
Ventilation:LOAL EXHAUST. VENT EXHAUST CURING OVENS TO OUTDOORS OR EMISSION CONTROL DEVICE. USE IN A WELL VENTED

AREA.

Protective Gloves:IMPERVIOUS

Eye Protection:VENTED GOGGLE/SAFETY GLASS W/SIDE SHIELD

Other Protective Equipment:IMPERVIOUS CLOTHES, EYEWASH FOUNTAIN AND QUICK DRENCH SHOWER.

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:1.3

pH:NE

Evaporation Rate & Reference:NA

Solubility in Water:VERY SLIGHT

Appearance and Odor:GRAY VISCOUS PAINT W/LITTLE ODOR.

Percent Vol

atiles by Volume:0

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT IS GENERATED DURING CURE. DONT CURE A MASS LARGER THAN 50G IN A CONFINED SPACE.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES, KETONES, HYDROCARBONS, TOXIC VAPORS, GASES & PARTICULATES.

=====
Disposal Considerations
=====

=

Waste Disposal Methods:INCINERATE UNCURED WASTE IN AN INDUSTRIAL OR COMMERCIAL INCINERATOR. DISPOSE OF COMPLETELY CURED OR POLYMERIZED MATERIAL IN A SANITARY LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any

person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.