

I T W DEVCON INDUSTRIAL CORP -- 5-MINUTE EPOXY HARDENER -- 8040-00-273-8703

===== Product Identification =====

Product ID:5-MINUTE EPOXY HARDENER

MSDS Date:02/19/1996

FSC:8040

NIIN:00-273-8703

Kit Part:Y

MSDS Number: CGNDM

=== Responsible Party ===

Company Name:I T W DEVCON INDUSTRIAL CORP

Address:30 ENDICOTT ST

City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Info Phone Num:508-777-1100

Emergency

Phone Num:800-424-9300

CAGE:JO305

=== Contractor Identification ===

Company Name:DEVCON CORP

Address:30 ENDICOTT ST

Box:City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Phone:1-508-777-1100

CAGE:16059

Company Name:I T W DEVCON INDUSTRIAL CORP

Address:30 ENDICOTT ST

Box:City:DANVERS

State:MA

ZIP:01923

Country:US

Phone:508-777-1100

CAGE:JO305

===== Composition/Information on Ingredients =====

Ingred Name:2,4,6-TRI(DIMETHYLAMINOMETHYL)PHENOL

Fraction by Wt: 10-20%

Other REC Limit

s:NONE RECOMMENDED

Ingred Name:MERCAPTAN AMINE BLEND

Fraction by Wt: 80-90%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 RAT 12000 MG/KG, RABBIT 1350 MG/KG\*

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRIT, BLINDNESS. SKIN: IRRIT,  
SENSITIZATION. INHAL: IRRIT OF RESPIRATORY TRACT. MAY CAUSE DELAYED  
LUNG

INJURY AND CHEMICAL PNEUMONIA. INGEST: TOXIC, FATIGUE, MUSCLE  
WEAKNESS, GI IRRIT, NAUSEA, V OMIT, DIARRHEA. CHRONIC: LUNG DAMAGE,  
CHEMICAL PNEUMONITIS & SKIN SENSITIZATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE, SKIN AND LUNG  
CONDITIONS.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, LIFTING LIDS. SKIN: REMOVE  
CONTAM CLOTHES/SHOES. WASH THOROUGHLY W/SOAP & WARM WATER. INHAL:  
GET FRESH AIR. OX

YGEN IF NEEDED. INGEST: DONT INDUCE VOMIT. DRINK  
LARGE AMOUNTS OF WATER FOLLOWED BY MILK. IN ALL CASES, GET MED  
AID.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F,>93C

Lower Limits:NE

Upper Limits:NE

Extinguishing Media:WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE SCBA AND PROTECTIVE CLOTHING IN CONFINED  
AREAS. USE WATER TO COOL CONTAINERS.

Unusual Fire/Explosion Hazard:TOXIC SMOKE AND VAPO

RS MAY FORM DURING

COMBUSTION. HAZARDOUS PRODUCTS OF COMBUSTION: OXIDES OF CARBON,  
OXIDES OF SULFUR & OXIDES OF NITROGEN.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITS. VENT AREA. DIKE, CONTAIN &  
ABSORB W/SUITABLE MATERIAL. LGSP: PUMP TO STORAGE/SALVAGE VESSELS.  
SOAK UP RESIDUE W/ABSORBENT. FLUSH AREA W/WATER. PREVENT FROM  
ENTERING DRAINAGE/SEWER SY STEM/WATERWAYS/SURFACE WATERS.

===== Handlin

g and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY AREA AWAY FROM  
HIGH TEMPS AND FLAMES.

Other Precautions:DISCARD CONTAM LEATHER ARTICLES. HANDLE MIXED RESIN &  
HARDENER IN ACCORDANCE W/POTENTIAL HAZARD OF CURING AGENT USED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:POORLY VENTED AREA, CREATING DUST/MIST, USE  
NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. PROVIDE VENT/RESP  
PROTECTION AGAINST DEC  
OMP PRODUCTS WHEN WELDING/FLAME CUTTING & TO  
PROTECT AGAINST NUISANCE DUST WHEN SANDING/GRINDING/CURING  
PRODUCT.

Ventilation:GENERAL, MECHANICAL OR LOCAL EXHAUST

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES W/SIDESHIELDS CHEM GOGGLE

Other Protective Equipment:EMERGENCY SHOWER AND EYEWASH STATION  
AVAILABLE.

Work Hygienic Practices:WASH THOROUGHLY W/SOAP & WATER AFTER USING &  
BEFORE EATING, SMOKING, APPLYING COSMETICS, USING TOILET.

Supplemental Safety and He

alth

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NE

Melt/Freeze Pt:M.P/F.P Text:NE

Vapor Pres: