View NSN Online: https://aerobasegroup.com/nsn/8040-00-841-9773

RUBATEX CORP SUB OF GREAT AMERICAN INDUSTRIES INC -- R-373 RUBBER INSUL. ADHESIVE

#373 -- 8040-00-841-9773

============= Product Identification =================

Product ID:R-373 RUBBER INSUL. ADHESIVE #373

MSDS Date:01/01/1996

FSC:8040

NIIN:00-841-9773

MSDS Number: CGNHB === Responsible Party ===

Company Name: RUBATEX CORP SUB OF GREAT AMERICAN INDUSTRIES INC

Address:605 ADAMS ST

Box:340

City:BEDFORD

State:VA ZIP:24 523

Country:US

Preparer's Name: CAROL N. BUSH

CAGE:82942

=== Contractor Identification ===

Company Name: RUBATEX CORP SUB OF GREAT AMERICAN INDUSTRIES INC

Address:605 ADAMS ST

Box:340

City:BEDFORD

State:VA ZIP:24523 Country:US CAGE:82942

======= Composition/Information on Ingredients ========

Ingred Name: TOLUENE (SARA 313) (CERCLA)(VP = 22.0 @ 68F)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 16.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM ACGIH TLV:100 PPM EPA Rpt Qty:10 00 LBS

DOT Rpt Qty:1000 LBS

Ingred Name: NORMAL HEXANE (CERCLA)(SARA 313)(VP = 320.0 @ 100F)

CAS:110-54-3

RTECS #:MN9275000 Fraction by Wt: 15.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:500 PPM ACGIH TLV:400 PPM EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ACETONE (SARA 313) (CERCLA)(VP = 186 @ 68F)

CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 35.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:750 PPM ACGIH TLV:750 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANE (SARA 313) (CERCLA) (VP = 320.0 @ 100F)

CAS:110-82-7

RTECS #:GU6300000 Fraction by Wt: AIR Spec Gravity:0.8

Evaporation Rate & Department Reference: SLOWER THAN ETHER

Solubility in Water:NO

Appearance and Odor:BLUE, OFFENSIVE ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
ALKALINE MATERIALS, STRONG ACIDS, OXIDIZING MATERIALS.
Stability Condition to Avoid:EXCESSIVE HEAT, POOR VENTILATION,
CORROSIVE ATMOSPHERE, EXCESSIVE AGING.
Hazardou

s Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE
OXIDES OF NITROGEN, POSSIBLE ACROLEIN.

======= Disposal Considerations ===========

Waste Disposal Methods:COLLECT ABSORBENT/SPILLED LIQUID MIXTURE, PLACE INTO METAL CONTAINERS. CONSULT LOCAL, STATE, FEDERAL HAZARDOUS WASTE REGS BEFORE DISPOSING INTO APPROVED HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by ele ments of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.