

METALCRETE MANUFACTURING CO -- INSTAROK CABLE SEALING CEMENT SC-4-OZ --
8030-01-084-9759

===== Product Identification =====

Product ID:INSTAROK CABLE SEALING CEMENT SC-4-OZ

MSDS Date:05/29/1997

FSC:8030

NIIN:01-084-9759

MSDS Number: CGWFQ

=== Responsible Party ===

Company Name:METALCRETE MANUFACTURING CO

Address:10330 BRECKSVILLE RD

City:CLEVELAND

State:OH

ZIP:44141-5000

Country:US

Info Phone Num

:216-526-5600

Emergency Phone Num:216-526-5600

CAGE:MCRET

=== Contractor Identification ===

Company Name:METALCRETE MANUFACTURING CO

Address:10330 BRECKSVILLE RD

City:CLEVELAND

State:OH

ZIP:44141

Country:US

Phone:216-526-5600;800-424-9300(CHEMTREC)

CAGE:MCRET

===== Composition/Information on Ingredients =====

Ingred Name:PORTLAND CEMENT *98-1*

CAS:65997-15-1

RTECS #:VV8770000

Fraction by Wt: 55%

Other REC Limits:50 MPPCF (MSHA)

OSHA PEL:15 MG/CUM (DUST)

ACGIH TLV:10 MG/CUM (

DUST)

Ingred Name:CALCIUM SILICON OXIDE

CAS:12168-85-3

Fraction by Wt: 24%

Ingred Name:DICALCIUM SILICATE *98-1*

CAS:10034-77-2

Fraction by Wt: 20%

Ingred Name:FLOW CONTROL AGENT

CAS:64787-97-9

Fraction by Wt: 1%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES/SKIN: MAY CAUSE IRRITATION.

INGESTION: THIS PRODUCT HARDENS WHE

N WETTED & IF INGESTED MAY

RESULT IN OBSTRUCTION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION

=====
===== First Aid Measures =====

First Aid:EYES: FLOOD IMMEDIATELY W/WATER FOR 15 MINS. SKIN: REMOVE BY WASHING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point:NONCOMBUSTIBLE

Extinguishing Media:USE EXTINGUISHING MEDIA APPROPRIATE TO THE SURROUNDING AREA

=====
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP & PLACE IN SUITABLE CONTAINERS. AVOID CREATING EXCESSIVE DUST. DON'T WASH SLURRY DOWN DRAINS SINCE THIS MAY CAUSE PLUGGING.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY LOCATION AWAY FROM WATER/HIGH HUMIDITY CONDITIONS TO AVOID PREMATURE HARDENING.

=====
===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:USE NIOSH APPROVED NUISANCE DUST RESPIRATOR IF ABOVE TLV.

Ventilation:GENERAL MECHANICAL EXHAUST IF ABOVE TLV.

Protective Gloves:PROTECTIVE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:2.7

pH:9

Solubility in Water:2%

Appearance and Odor:GRAY, ODORLESS POWDER

===== Stability and Reactivity Data =====

Stab

ility Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS SOLID WASTE IN LANDFILL IAW/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and discla

ims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.