

VARFLEX CORPORATION -- VARGLAS SILICONE RUBBER,ES4400,SR9400,240(REX OXIDE) --
5970-01-218-0757

=====
===== Product Identification =====

Product ID:VARGLAS SILICONE RUBBER,ES4400,SR9400,240(REX OXIDE)

MSDS Date:11/07/1996

FSC:5970

NIIN:01-218-0757

MSDS Number: CGXDZ

=== Responsible Party ===

Company Name:VARFLEX CORPORATION

Address:512 WEST COURT STREET

Box:551

City:ROME

State:NY

ZIP:13440

Country:US

In

fo Phone Num:315-336-4400

Emergency Phone Num:315-336-4400

CAGE:79074

=== Contractor Identification ===

Company Name:VARFLEX CORPORATION

Address:512 WEST COURT STREET

Box:City:ROME

State:NY

ZIP:13440

Country:US

Phone:315-336-4400

CAGE:79074

=====
===== Composition/Information on Ingredients =====

Ingred Name:FIBROUS GLASS

Fraction by Wt: NP

Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICONE RUBBER, VINYL, METHOL, PHENYL

SILICONES-OSI-O-SI-OSI

Fraction by Wt: NP

Other REC L

imits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN CONTACT-ACUTE:TRANSIENT
MEHCANICAL IRRITATION;CHORNIC:NONE.EYE CONTACT-ACUTE:DIRECT CONTACT
WILL CAUSE MECHANICAL
IRRITATION.CHRONIC:NONE.INGESTION-ACUTE:UNLIKELY TO
OCCUR;CHRONIC:NONE.

Explanati
on of Carcinogenicity:PER
MSDS:CARCINOGENICITY:NTP/IARC/OSHA:NA.
Effects of Overexposure:OBSERVE INDIVIDUAL.IF SYMPTOMS DEVELOPS CONSULT
PHYSICIAN.
Medical Cond Aggravated by Exposure:SKIN PROBLEMS.

=====
===== First Aid Measures =====

First Aid:WASH EXPOSED AREAS WITH SOAP AND WATER.

=====
===== Fire Fighting Measures =====

Flash Point:NA
Autoignition Temp:Autoignition Temp Text:NP
Lower Limits:NA
Upper Limits:NA
Extinguish
ing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL AND FOAM.
Fire Fighting Procedures:IN A SUSTAINED FIRE WEAR SELF-CONTAINED
BREATHING APPARATUS APPROVED BY USE BUREAU OF MINES.
Unusual Fire/Explosion Hazard:NO EXPLOSIVE HAZARD.

=====
===== Accidental Release Measures =====

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NONE
Other Precautions:NONE

=====

= Exposure Controls/Personal Protection =====

Respiratory Protection:IN A SUSTAINED FIRE WEAR SELF-CONTAINED
BREATHING APPARATUS APPROVED BY THE USE BUREAU OF MINES.
Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION.
Protective Gloves:NOT REQUIRED.
Eye Protection:SAFETY GLASSES IF NEEDED.
Other Protective Equipment:NONE
Work Hygienic Practices:WASH EXPOSED AREAS W/SOAP AND WATER.
Supplemental Safety and Health

===== Physical/Chemical Properties =====
=====

HCC:N1
Boiling Pt:B.P. Text:NA
Melt/Freeze Pt:M.P/F.P Text:NA
Decomp Temp:Decomp Text:NP
Vapor Pres:NA
Vapor Density:NA
Spec Gravity:2.54
pH:NP
Viscosity:NP
Evaporation Rate & Reference:NA
Solubility in Water:INSOLUBLE
Appearance and Odor:CONTINUOUS FILM OF SILICONE RUBBER ON
"FIBERGLAS"BRAID, NO ODOR.
Percent Volatiles by Volume:NP
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stabilit
y Condition to Avoid:CONDITIONS ABOVE 250C W/OUT ADEQUATE
VENTILATION.
Hazardous Decomposition Products:METHYL AND PHENYL BY-PRODUCTS.
Conditions to Avoid Polymerization:TEMEPRATURES IN EXCESS OF 240C.

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL IS PREFERRED, BUT DISPOSAL METHODS MUST
CONFORM TO LOCAL, STATE AND FEDERAL REGULATIONS.BURNING IS NOT
RECOMMENDED.

Disclaimer (provided with this information by the compiling agenci

es):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.