

DOW CORNING CORP -- 734 FLOWABLE SEALANT, CLEAR -- 8040-00-880-7332

=====
Product Identification
=====

Product ID:734 FLOWABLE SEALANT, CLEAR

MSDS Date:12/28/1995

FSC:8040

NIIN:00-880-7332

Kit Part:Y

MSDS Number: CGXNC

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-49

6-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:ELLSWORTH ADHESIVE SYSTEM

Box:UNKNOW

CAGE:0HNT2

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLTRACETOXY

SILANE (ACETIC ACID IS FOMRED ON CONTACT
W/WATER/HUMID AIR. PEL 10 PPM, TLV 10 PPM, STEL 15 PPM)

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2%

Other REC Limits:SEE ACETIC COMMENTS

Ingred Name:SILICA, AMORPHOUS

Fraction by Wt: 8.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:ETHYLTRIACETOXYSILANE (ACETIC ACID IS FOMRED ON CONTACT
W/WATER OR HUMID AIR. PEL 10 PPM, TLV 10 PPM, STEL 15 PPM)

CAS:17689-77-9

Fraction by Wt: 3.0%

Other REC Limits:SEE

ACETIC COMMENTS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRIT, REDNESS, SWELLING. SKIN:
IRRIT. INHAL: IRRIT TO EYES/NOSE/THROAT. INGEST: DIGESTIVE
DISCOMFORT.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: REMOVE AND WASY
W/SOAP & WA
TER OR WATERLESS CLEANSER. INHAL: REMOVE TO FRESH AIR.
IN ALL CASES, GET IMMED MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:189F,87C
Autoignition Temp:Autoignition Temp Text:NE
Extinguishing Media:CARBON DIOXIDE, WATER SPRAY, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:USE WATER TO COOL CONTAINERS. USE SCBA AND
PROTECTIVE CLOTHES. DETERMINE THE NEED TO EVACUATE OR ISOLATE AREA.
Unusual Fire/Explosion Hazard:VAPORS >AIR

, MAY TRAVEL TO IGNITS. STATIC
ELECTRICITY MAY COLLECT& IGNITE VAPORS. PREVENT FIRE HAZARDS BY
BINDING/GROUNDING/INERT GAS PURGE/VAPOR DISOLUTION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITS. USE NON-SPARKING TOOLS &
EQUIPMENT. PREVENT SPONTANEOUS COMBUSTION. STORE CLEAN-UP ITEMS IN
CONTAINER OR COVER W/WATER. MOP/WIPE/SOAK UP W/ABSORBENT & CONTAIN
FOR SALVAGE/DISPOSAL. LGSP: DIKE TO KEEP FROM SPREADING.*

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED AND AWAY FROM
IGNITS & AWAY FROM WATER AND MOISTURE.

Other Precautions:* FOR NONSILICONES: USE INDUSTRIAL CLEANING
MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR/DUST/MIST TYPE
Ventilation:LOCAL EXHAUST OR GENERAL VENTILATION RECOMMENDED
Eye Protection:SAFETY GLASSES
Work Hygienic Practices:WASH AT ME
ALTIME AND AT END OF SHIFT.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NE
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:NE
Vapor Density:NE
Spec Gravity:1.03 @ 25C
pH:NA
Viscosity:350.00 CST
Solubility in Water:NE
Appearance and Odor:COLORLESS VISCOUS LIQUID, ACETIC ACID ODOR.
Percent Volatiles by Volume: