View NSN Online: https://aerobasegroup.com/nsn/8010-01-285-1328

HANLEY PAINTS -- PRIMER COATING, CONDITIONER FOR CHALKING -- 8010-01-285-1328

Product ID:PRIMER COATING, CONDITIONER FOR CHALKING

MSDS Date:01/10/1997

FSC:8010

NIIN:01-285-1328

MSDS Number: CGXPX === Responsible Party ===

Company Name: HANLEY PAINTS

Address:6050 LUCKETT ST.

City:EL PASO State:TX

ZIP:79932 Country:US

Info Phone Num:915-585-2061

Emergency Phone Num

:800-228-5635

Preparer's Name: JAMIE NICHOLS

CAGE:JO927

=== Contractor Identification === Company Name: HANLEY PAINTS

Address:6050 LUCKETT ST.

Box:City:EL PASO

State:TX ZIP:79932 Country:US

Phone:915-585-2061

CAGE:JO927

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS

CAS:64742-47-8 Fraction by Wt: 11.0%

Other REC Limits: NONE RECOMMENDED

Ingred Name: MAGNESIUM SILICATE HYDRATE

CAS:14807-96-6

RTECS #:MW2700000 Fraction by Wt: 8.96% Other REC Limits:

NONE RECOMMENDED Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRIT. SKIN: IRRIT, DERMATITIS, DEFATTING. INHAL: NASALL/RESPIRATORY TRACT IRRIT, DIZZY, WEAKNESS, HEADACHE, UNCONSCIOUS, ASPHYXIATION. INGEST: GI IRRIT, NAUSEA, VOMIT. First Aid:EY E: FLUSH W/WATER. SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES, WASH BEFORE REUSE. INHAL: GET FRESH AIR. INGEST: CALL POISON CONTROL. IN ALL CASES, GET IMMED MED AID. Flash Point: 105F,41C Lower Limits:.9 Upper Limits:7.0 Extinguishing Media: ALCOHOL FOAM, WATER FOAM, WATER FOG, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: USE SCBA & PROTECTIVE CLOTHES. COVER LIQUID SPILLS W/FOAM. AVOID SPRAYING WA TER DIRECTLY INTO CONTAINERS. USE WATER TO COOL CONTAINERS. Unusual Fire/Explosion Hazard:NONE =========== Accidental Release Measures ================

Spill Release Procedures:ELIMINATE IGNITS. STOP SPILL AT SOURCE. DIKE AREA. PUMP LIQUID TO SALVAGE TANK. ABSORB REMAINING LIQUID ON NONFLAMMABLE ABSORBENT MATERIAL. SHOVEL (NONSPARKING) INTO CONTAINERS. PREVENT RUNOFF TO DRAI NS, SEWER OR STREAMS.

========== Handling and Storage ================

Η

andling and Storage Precautions:EMPTY CONTAINERS RETAIN RESIDUE. FOLLOW PRECAUTION IN MSDS. STORE W/CONTAINERS CLOSED, AVOID EXCESS UPPER AND LOWER TEMPERATURES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF TLV IS EXCEEDED, USE NIOSH APPROVED RESPIRATORS TO PREVENT OVER-EXPOSURE. Ventilation:PROVIDE EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV. Protective Gloves:CHEMICAL RESISTANT/NITRILE RUBBER Eye Protection:SPLASH GOGGLES Ot
her Protective Equipment:IMPERVIOUS CLOTHES Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING, DRINKING & AFTER HANDLING MATERIAL. Supplemental Safety and Health NK
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:NA Vapor Density:NA Spec Gravity:1.42 H2O=1 VOC Grams/Liter:2.81 Evaporation Rate & Description Rate & Des
========= Stability and Reactivity Data =========
Stabilit y Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:KEEP AWAY FROM HEAT, OPEN FLAMES, IGNIT SOURCES. Hazardous Decomposition Products:MAY INCLUDE AND ARE NOT LIMITED TO CARBON DIOXIDE & CARBON MONOXIDE.
======= Disposal Considerations ==========
Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS
=========== Other Information ==============
=======================================

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this i nformation to their particular situation.