View NSN Online: https://aerobasegroup.ae/nsn/6750-01-363-8343

EASTMAN KODAK COMPANY -- 813 5048 3000 FIXER AND REPLENISHER, PART A

6750-01-363-8343

Product ID:813 5048 3000 FIXER AND REPLENISHER, PART A

MSDS Date:02/25/1998

FSC:6750

NIIN:01-363-8343

MSDS Number: CHHVX === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-477-3 194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

====== Composition/Information on Ingred

ients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 40-45%

Other REC Limits: NONE RECOMMENDED

Ingred Name: AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000 Fraction by Wt: 40-45%

Other REC Limits: NONE RECOMMENDED

Ingred Name:SODIUM ACETATE

CAS:127-09-3

RTECS #:AJ4300010 Fraction by Wt: 5-10%

Other REC Limits: NONE RECOMMENDED

Ingred Name:BORIC ACID

CAS:10043-35-3 RTECS #:ED4550000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

**OSHA PEL:10 MG BORATE** 

S/M3

ACGIH TLV:5 MG BORATES/M3

Ingred Name: AMMONIUM SULFITE (CERCLA)

CAS:10196-04-0 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ACETIC ACID (CERCLA)

CAS:64-19-7

RTECS #:AF1225000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9596

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: SODIUM BISULFITE (SASA III) (CERCLA)

CAS:7631-90-5

RTECS #:VZ2000000 Fraction by Wt: < 1%


Other

REC Limits: NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS ========== Hazards Identification =============== LD50 LC50 Mixture: ORAL LD50 RAT > 2540 MG/KG Routes of Entry: Inhalation: NO Skin: YES Ingestion: YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EXPECTED TO BE A LOW INHALATION HAZARD. MAY LIBERATE SULFUR DIOXIDE GAS WHICH IS IRRITATING TO RESPIRATORY TRACT. MAY CAUSE TRANSIENT EYE IRRITATION. MAY BE ABSORBED IN TOXIC AMOUNTS THROUGH DAMAGED S KIN. MAY BE HARMFUL IF SWALLOWED. Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure: RESPIRATORY TRACT IRRITATION, EYE IRRITATION, SKIN IRRITATION, DIFFICULT BREATHING, SKIN SENSITIZATION, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS, DIARRHEA. **BASED ON REP** EATED-DOSE ING ESTION STUDIES IN ANIMALS, MAY CAUSE ADVERSE REPRODUCTIVE & DEVELOPMENTAL EFFECTS. Medical Cond Aggravated by Exposure: SOME ASTHMATICS OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS & DIARRHEA. First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: ANY MATERIAL THAT CONTACTS EYES SHOULD BE WASHED OUT IMEEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SY MPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: ONLY INDUCE VOMITING AT THE INSTRUCTION OF MEDICAL PERSONNEL. CALL PHYSICIAN OR

POISON CONTROL ASAP.

============= Fire Fighting Measures ========================

Flash Point: NONFLAMMABLE Lower Limits: NOT GIVEN Upper Limits:NOT GIVEN Extinguishing Media: USE APPROPRIATE AGENT FOR ADJACENT FIRE.



HCC:C1

Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Decomp Temp:Decomp Text:NOT GIVEN Va por Pres:18MM Vapor Density:0.6 Spec Gravity:1.32

pH:5.0

Evaporation Rate & Evaporation R

Solubility in Water: COMPLETE.

Appearance and Odor:LIQUID, LIGHT YELLOW, SLIGHT SULFUR & ACETIC ACID ODOR.

Percent Volatiles by Volume:40-45

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG ACIDS. CONTACT W/BASE LIBERATES FLAMM MATL.

Stability Condition to Avo

id:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: AMMONIA, NITROGEN OXIDES (NOX), SULFUR DIOXIDE, CHLORAMINE, CARBON MONOXIDE, CARBON DIOXIDE

====== Disposal Considerations ===========

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.