View NSN Online: https://aerobasegroup.ae/nsn/8030-01-396-5754

ESGARD, INC. -- PL-5 HYDROCARBON COMPLEX -- 8030-01-396-5754

Product ID:PL-5 HYDROCARBON COMPLEX

MSDS Date:09/20/1994

FSC:8030

NIIN:01-396-5754

MSDS Number: CHKLD === Responsible Party === Company Name:ESGARD, INC. Address:PO DRAWER 2698

City:LAFAYETTE,

State:LA ZIP:70502 Country:US

Info Phone Num:318-234-6327

Emergency Phone Num:800-888-2511

CAGE:ESGAR

=== Contr

actor Identification ===

Company Name: ESGARD INC Address: 515 DEBONNAIRE RD

Box:City:SCOTT

State:LA ZIP:70583 Country:US

Phone:318-234-6327

CAGE:0N1W9

Company Name: ESGARD, INC. Address: PO DRAWER 2698

Box:2698

City:LAFAYETTE

State:LA ZIP:70502 Country:US

Phone:318-234-6327

CAGE:ESGAR

======= Composition/Information on Ingredients ========

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000 Fraction by Wt: 2.08%

Other REC Limits:TWA 500 PPM

OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name: VOC = 0.16 LBS/GL RTECS #:9999999VO Other REC Limits: NONE RECOMMENDED OSHA PEL:NOT RELEVANT **ACGIH TLV:NOT RELEVANT** ========== Hazards Identification =============== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION. INHAL: IRRITATION, NARCOTIC, ANESTHETIC. INGEST: GI DISTRESS, IRRITATION, NAUSEA. CHRONIC: LIVER/KIDNEY DAMAGE. E ffects of Overexposure: INHAL: IRRITATION OF RESPIRATORY TRACT, NS DEPRESSION, HEADACHE, DIZZY, STAGGERING, CONFUSION, UNCONSCIOUSNESS, COMA. Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN DISORDERS. First Aid:EYE: FLUSH W/WATER 15 MINUTES, GET MED AID. SKIN: WASH W/SOAP & WATER 15 MINUTES, GET MED AID. INGEST: DONT INDUCE VOMIT, GET IMMED MED AID. INHAL: REMOVE TO FRESH AIR, ARTIF RESP. GIVE OXYGEN IF DIFF BREATHING. GET IMMED MED AID. Flash Point Method: PMCC Flash Point: 205F, 96C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media: DRY POWDER, CARBON DIOXIDE, EATER FOG OR SPRAY. Fire Fighting Procedures: APPROACH FIRE FROM UPWIND. AVOID SMOKE, FUMES, MIST/VAPORS DOWNWIND, PROTECTIVE CLOTHES, SCBA.

Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT & MAY IGNITE ON WATER. IF STORED IN DRUMS, CONTAINERS MAY RUPTURE,

COOL W/WATER. EVAC PERSONNEL FROM AREA. ======== Accidental Release Measures ============ Spill Release Procedures: SM SPILL: ABSORBENT MEDIA. STORE AS NON-HAZARDOUS OIL WASTE. LG SPILLS: CONTAIN W/DIKES. PICK UP W/VACUUM TRUCK. HANDLE AS NON-HAZARDOUS OIL WASTE. ============= Handling and Storage ========================== Handling and Storage Precautions: STORE IN COOL, VENTILATED AREA AWAY FROM IGNIT SOURCES, OXIDIZERS OR MATERIALS W/YELLOW DOT LABEL Other Precautions: CLEAN LEAKS/SPILLS IMMED TO PREVENT WATER/SOIL CONTAMINATION. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NOT NORMALLY NEEDED. Ventilation: LOCAL EXHAUST AND MECHANICAL VENT. Protective Gloves: CHEMICAL RESISTANT Eye Protection: CHEMICAL GOGGLES/FULL FACE SHIELD. Other Protective Equipment: BOOTS, APRONS, DRENCH SHOWER, EYEWASH STATION. Work Hygienic Practices: AVOID CONTACT W/SKIN/EYES/CLOTHES. WASH HANDS **BEFORE EATING/** DRINKING/SMOKING. REMOVE CONTAM CLOTHES. WASH BEFORE REUSE. Supplemental Safety and Health NK ========= Physical/Chemical Properties =========== Boiling Pt:B.P. Text:>300F,>149C Melt/Freeze Pt:M.P/F.P Text:NA Vapor Pres:4 Spec Gravity: 0.91 (H20 +1)

P-8:Ha

Evaporation Rate & Day; Reference: BUAC -1