View NSN Online: https://aerobasegroup.ae/nsn/8010-01-435-2120

DEL PAINT CORP. -- TT-E-2784 ENAMEL BLUE #15526 -- 8010-01-435-2120

Product ID:TT-E-2784 ENAMEL BLUE #15526 MSDS Date:06/14/1995 FSC:8010 NIIN:01-435-2120 MSDS Number: CHKMH === Responsible Party === Company Name: DEL PAINT CORP. Address:3105 E. RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Info Phone Num:405-672-1431/FAX 405-672-0804 **Emergency Phone Num:8** 00-424-9300 24 HRS Preparer's Name: ONEY FLEMING CAGE: JO954 === Contractor Identification === Company Name: DEL PAINT CORP. Address:3105 E. RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431/FAX 405-672-0804 CAGE:JO954 Company Name: DEL PAINT MFG Address:3105 EAST RENO Box:City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431 CAGE:39934

Ingred Name:PROPYLENE GLYCOL CAS:57-55-6 RTECS #:TY200000 0 Fraction by Wt: 6.25% Other REC Limits:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-3,3,-PENTANEDIOL MONOISOBUTYRATE CAS:25265-77-4 RTECS #:UF6000000 Fraction by Wt: 4.86% Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-1-ISOTHAZOLIN-3-ONE CAS:26530-20-2 Fraction by Wt: .18% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS Fraction by Wt: 88.33% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC CAS:108-01-0 RTECS #:KK6125000 Fraction by Wt: .38% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: SLIGHT IRRITATION. SKIN: SLIGHT IRRITATION. INHAL: HEADACHE, NAUSEA, IRRIT TO NOSE/THROAT/LUNGS. Medical Cond Aggravated by Exposure:PRE-EXISTING DISEASES.

======= Firs

First Aid:EYE: FLUSH W/WATER 15 MINUTES, GET MED AID. SKIN: WASH THOROUGHLY W/SOAP & WATER. INGEST: GIVE 2 GLASSES OF WATER TO DRINK, GET MED AID.

Flash Point Method:SCC Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures:SCBA, NIOSH APPROVED PRESSURE DEMAND, FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:CAN SPLATTER ABOVE 10

======================================
Spill Release Procedures: KEEP PEOPLE AWAY. FLOOR MAY BE SLIPPERY. USE CARE. CONTAIN SPILL W/INERT ABSORBENT. TRANSFER LIQUID/SOLID DIKING MATERIAL TO SEPARATE SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL.
======================================
Handling and Storage Precautions: KEEP FROM FREEZING. Other Precautions: DONT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:MECHANICAL FILTER RESPIRATOR Ventilation:NORMAL, SUCH AS FAN Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES OR GOGGLES Other Protective Equipment:EYEWASH STATION Supplemental Safety and Health NK
======================================
Boiling Pt:B.P. Text:212 TO 644F Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C Decomp Temp:Decomp Text:351F,177C Vapor Pres:NONE Vapor Densi ty:>AIR Spec Gravity:1.01 pH:9.0 Viscosity:77-95 KU Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:SLIGHT Appearance and Odor:BLUE LIQUID/SLIGHT ODOR. Percent Volatiles by Volume:60.6 Corrosion Rate:NA
======================================
Stability Indicator/Materials to Avoid:YES NK Hazardous Decomposition Products:ACRYLIC MONOMERS
======================================
Waste Disposal Methods:KEEP SPILLS/CLE

ANING RUNOFF OUT OF SEWERS/OPEN BODIES OF WATER. CONSULT FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person uti lizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.